



FortiOS - Log Reference

Version 5.6.7

FORTINET DOCUMENT LIBRARY

<https://docs.fortinet.com>

FORTINET VIDEO GUIDE

<https://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTINET COOKBOOK

<http://cookbook.fortinet.com>

FORTINET TRAINING & CERTIFICATION PROGRAM

<https://www.fortinet.com/support-and-training/training.html>

NSE INSTITUTE

<https://training.fortinet.com>

FORTIGUARD CENTER

<https://fortiguard.com/>

END USER LICENSE AGREEMENT

<https://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdocs@fortinet.com



November 27, 2018

FortiOS 5.6.7 Log Reference

01-565-414447-20181127

TABLE OF CONTENTS

Change Log	28
Introduction	29
Before you begin	29
Overview	29
What's new	30
FortiOS 5.6.7	30
FortiOS 5.6.6	30
FortiOS 5.6.5	30
FortiOS 5.6.4	30
FortiOS 5.6.3	30
FortiOS 5.6.2	30
FortiOS 5.6.1	30
FortiOS 5.6.0	30
Log Types and Subtypes	32
Type	32
Subtype	32
List of log types and subtypes	32
FortiOS priority levels	34
Log field format	35
Log Schema Structure	36
Log message fields	36
Log ID numbers	39
Log ID definitions	40
FortiGuard Web Filter Categories	43
CEF Support	47
FortiOS to CEF log field mapping guidelines	47
CEF priority levels	48
Examples of CEF support	48
Anomaly log support for CEF	48
Antivirus log support for CEF	49
DLP log support for CEF	49
Email Spamfilter log support for CEF	50
Webfilter log support for CEF	51
Traffic log support for CEF	51
Event log system subtype support for CEF	52
Log Messages	54
Anomaly	54
18432 - LOGID_ATTCK_ANOMALY_TCP_UDP	54
18433 - LOGID_ATTCK_ANOMALY_ICMP	55
18434 - LOGID_ATTCK_ANOMALY_OTHERS	57

App	59
28672 - LOGID_APP_CTRL_IM_BASIC	59
28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS	60
28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT	61
28675 - LOGID_APP_CTRL_IM_FILE	63
28676 - LOGID_APP_CTRL_IM_CHAT	64
28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK	66
28678 - LOGID_APP_CTRL_IM_BLOCK	67
28704 - LOGID_APP_CTRL_IPS_PASS	68
28705 - LOGID_APP_CTRL_IPS_BLOCK	70
28706 - LOGID_APP_CTRL_IPS_RESET	72
28720 - LOGID_APP_CTRL_SSH_PASS	74
28721 - LOGID_APP_CTRL_SSH_BLOCK	76
AV	77
8192 - MSGID_INFECT_WARNING	77
8193 - MSGID_INFECT_NOTIF	79
8194 - MSGID_INFECT_MIME_WARNING	81
8195 - MSGID_INFECT_MIME_NOTIF	83
8200 - MSGID_MIME_FILETYPE_EXE_WARNING	85
8201 - MSGID_MIME_FILETYPE_EXE_NOTIF	87
8448 - MSGID_BLOCK_WARNING	89
8449 - MSGID_BLOCK_NOTIF	91
8450 - MSGID_BLOCK_MIME_WARNING	93
8451 - MSGID_BLOCK_MIME_NOTIF	95
8452 - MSGID_BLOCK_COMMAND	97
8453 - MSGID_INTERCEPT	98
8454 - MSGID_INTERCEPT_MIME	100
8455 - MSGID_EXEMPT	102
8456 - MSGID_EXEMPT_MIME	104
8457 - MSGID_MMS_CHECKSUM	106
8458 - MSGID_MMS_CHECKSUM_NOTIF	107
8704 - MSGID_OVERSIZE_WARNING	109
8705 - MSGID_OVERSIZE_NOTIF	111
8706 - MSGID_OVERSIZE_MIME_WARNING	112
8707 - MSGID_OVERSIZE_MIME_NOTIF	114
8720 - MSGID_SWITCH_PROTO_WARNING	116
8721 - MSGID_SWITCH_PROTO_NOTIF	117
8960 - MSGID_SCAN_UNCOMPSIZELIMIT_WARNING	119
8961 - MSGID_SCAN_UNCOMPSIZELIMIT_NOTIF	121
8962 - MSGID_SCAN_ARCHIVE_ENCRYPTED_WARNING	123
8963 - MSGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF	125
8964 - MSGID_SCAN_ARCHIVE_CORRUPTED_WARNING	127
8965 - MSGID_SCAN_ARCHIVE_CORRUPTED_NOTIF	129
8966 - MSGID_SCAN_ARCHIVE_MULTIPART_WARNING	131
8967 - MSGID_SCAN_ARCHIVE_MULTIPART_NOTIF	133
8968 - MSGID_SCAN_ARCHIVE_NESTED_WARNING	135

8969 - MESGID_SCAN_ARCHIVE_NESTED_NOTIF	137
8970 - MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING	139
8971 - MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF	141
8972 - MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING	143
8973 - MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF	145
8974 - MESGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR	147
9233 - MESGID_ANALYTICS_SUBMITTED	149
9234 - MESGID_ANALYTICS_INFECT_WARNING	151
9235 - MESGID_ANALYTICS_INFECT_NOTIF	153
9236 - MESGID_ANALYTICS_INFECT_MIME_WARNING	155
9237 - MESGID_ANALYTICS_INFECT_MIME_NOTIF	157
9238 - MESGID_ANALYTICS_FSA_RESULT	159
9248 - MESGID_BOTNET_WARNING	160
9249 - MESGID_BOTNET_NOTIF	162
DLP	164
24576 - LOG_ID_DLP_WARN	164
24577 - LOG_ID_DLP_NOTIF	166
24578 - LOG_ID_DLP_DOC_SOURCE	168
24579 - LOG_ID_DLP_DOC_SOURCE_ERROR	169
DNS	170
54000 - LOG_ID_DNS_QUERY	170
54200 - LOG_ID_DNS_RESOLV_ERROR	171
54400 - LOG_ID_DNS_URL_FILTER_BLOCK	173
54401 - LOG_ID_DNS_URL_FILTER_ALLOW	174
54600 - LOG_ID_DNS_BOTNET_IP	176
54601 - LOG_ID_DNS_BOTNET_DOMAIN	177
54800 - LOG_ID_DNS_FTGD_WARNING	179
54801 - LOG_ID_DNS_FTGD_ERROR	180
54802 - LOG_ID_DNS_FTGD_CAT_ALLOW	182
54803 - LOG_ID_DNS_FTGD_CAT_BLOCK	183
Email	185
20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF	185
20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF	187
20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF	188
20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF	190
20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF	192
20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING	194
20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF	196
20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING	198
20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF	199
20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING	201
20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF	203
20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF	205
20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING	207
20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF	209
20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING	211

20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF	212
20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING	214
20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF	216
20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING	218
20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF	220
20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF	222
20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF	223
20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF	225
20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF	227
20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF	229
20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF	231
20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF	233
20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF	235
20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF	236
20509 - LOGID_ANTISPAM_FTGD_ERR	238
Event	240
20002 - LOG_ID_DOMAIN_UNRESOLVABLE	240
20003 - LOG_ID_MAIL_SENT_FAIL	241
20004 - LOG_ID_POLICY_TOO_BIG	242
20005 - LOG_ID_PPP_LINK_UP	243
20006 - LOG_ID_PPP_LINK_DOWN	243
20007 - LOG_ID_SOCKET_EXHAUSTED	244
20008 - LOG_ID_POLICY6_TOO_BIG	245
20010 - LOG_ID_KERNEL_ERROR	246
20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT	246
20017 - LOG_ID_MODEM_FAIL_TO_OPEN	247
20020 - LOG_ID_MODEM_USB_DETECTED	248
20021 - LOG_ID_MAIL_RESENT	248
20022 - LOG_ID_MODEM_USB_REMOVED	249
20023 - LOG_ID_MODEM_USBLTE_DETECTED	250
20024 - LOG_ID_MODEM_USBLTE_REMOVED	251
20025 - LOG_ID_REPORTD_REPORT_SUCCESS	251
20026 - LOG_ID_REPORTD_REPORT_FAILURE	252
20027 - LOG_ID_REPORT_DEL_OLD_REC	253
20028 - LOG_ID_REPORT_RECREATE_DB	253
20031 - LOG_ID_RAD_OUT_OF_MEM	254
20032 - LOG_ID_RAD_NOT_FOUND	255
20033 - LOG_ID_RAD_MOBILE_IPV6	255
20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE	256
20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE	257
20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE	257
20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE	258
20039 - LOG_ID_RAD_MTU_TOO_SMALL	259
20040 - LOG_ID_RAD_TIME_TOO_SMALL	259
20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE	260
20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE	261

20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE	261
20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET	262
20045 - LOG_ID_RAD_PREFIX_TOO_LONG	263
20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL	263
20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET	264
20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO	265
20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM	265
20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS	266
20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS	267
20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT	267
20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6	268
20054 - LOG_ID_RAD_EXIT_BY_SIGNAL	269
20055 - LOG_ID_RAD_FAIL_CMDB_QUERY	269
20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH	270
20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF	271
20058 - LOG_ID_RAD_UNLOAD_INTF	271
20059 - LOG_ID_RAD_NO_PKT_INFO	272
20060 - LOG_ID_RAD_INV_ICMPV6_LEN	273
20061 - LOG_ID_RAD_INV_ICMPV6_TYPE	273
20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN	274
20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR	275
20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN	275
20065 - LOG_ID_RAD_INV_ICMPV6_CODE	276
20066 - LOG_ID_RAD_INV_ICMPV6_HOP	277
20067 - LOG_ID_RAD_MISMATCH_HOP	277
20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG	278
20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG	279
20070 - LOG_ID_RAD_MISMATCH_TIME	279
20071 - LOG_ID_RAD_MISMATCH_TIMER	280
20072 - LOG_ID_RAD_EXTRA_DATA	281
20073 - LOG_ID_RAD_NO_OPT_DATA	281
20074 - LOG_ID_RAD_INV_OPT_LEN	282
20075 - LOG_ID_RAD_MISMATCH_MTU	283
20077 - LOG_ID_RAD_MISMATCH_PREF_TIME	283
20078 - LOG_ID_RAD_INV_OPT	284
20079 - LOG_ID_RAD_READY	285
20080 - LOG_ID_RAD_FAIL_TO_RCV	285
20081 - LOG_ID_RAD_INV_HOP	286
20082 - LOG_ID_RAD_INV_PKTINFO	287
20083 - LOG_ID_RAD_FAIL_TO_CHECK	287
20084 - LOG_ID_RAD_FAIL_TO_SEND	288
20085 - LOG_ID_SESSION_CLASH	289
20086 - LOG_ID_XH0_EVENT	290
20090 - LOG_ID_INTF_LINK_STA_CHG	290
20099 - LOG_ID_INTF_STA_CHG	291
20100 - LOG_ID_WEB_CAT_UPDATED	292

20101 - LOG_ID_WEB_LIC_EXPIRE	292
20102 - LOG_ID_SPAM_LIC_EXPIRE	293
20103 - LOG_ID_AV_LIC_EXPIRE	294
20104 - LOG_ID_IPS_LIC_EXPIRE	294
20105 - LOG_ID_LOG_UPLOAD_SKIP	295
20107 - LOG_ID_LOG_UPLOAD_ERR	296
20108 - LOG_ID_LOG_UPLOAD_DONE	297
20109 - LOG_ID_WEB_LIC_EXPIRED	298
20113 - LOG_ID_IPSA_DOWNLOAD_FAIL	298
20115 - LOG_ID_IPSA_STATUSUPD_FAIL	299
20116 - LOG_ID_SPAM_LIC_EXPIRED	300
20118 - LOG_ID_WEBF_STATUS_REACH	300
20119 - LOG_ID_WEBF_STATUS_UNREACH	301
20200 - LOG_ID_FIPS_SELF_TEST	302
20201 - LOG_ID_FIPS_SELF_ALL_TEST	302
20202 - LOG_ID_DISK_FORMAT_ERROR	303
20203 - LOG_ID_DAEMON_SHUTDOWN	304
20204 - LOG_ID_DAEMON_START	305
20205 - LOG_ID_DISK_FORMAT_REQ	305
20206 - LOG_ID_DISK_SCAN_REQ	306
20207 - LOG_ID_RAD_MISMATCH_VALID_TIME	307
20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP	308
20209 - LOG_ID_DISK_UNAVAIL	308
20210 - LOG_ID_DISK_TRIM_START	309
20211 - LOG_ID_DISK_TRIM_END	310
20212 - LOG_ID_DISK_SCAN_NEEDED	311
20220 - LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT	311
20221 - LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT	312
20300 - LOG_ID_BGP_NB_STAT_CHG	313
20301 - LOG_ID_VZ_LOG	313
20302 - LOG_ID_OSPF_NB_STAT_CHG	314
20303 - LOG_ID_OSPF6_NB_STAT_CHG	315
20401 - LOG_ID_ROUTER_CLEAR	315
22000 - LOG_ID_INV_PKT_LEN	316
22001 - LOG_ID_UNSUPPORTED_PROT_VER	317
22002 - LOG_ID_INV_REQ_TYPE	318
22003 - LOG_ID_FAIL_SET_SIG_HANDLER	318
22004 - LOG_ID_FAIL_CREATE_SOCKET	319
22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY	320
22006 - LOG_ID_FAIL_REG_CMDB_EVENT	320
22009 - LOG_ID_FAIL_FIND_AV_PROFILE	321
22010 - LOG_ID_SENDTO_FAIL	322
22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE	322
22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE	323
22013 - LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED	324
22014 - LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED	325

22015 - LOG_ID_IPPOOLPBA_CREATE	326
22016 - LOG_ID_IPPOOLPBA_DEALLOCATE	327
22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT	327
22018 - LOG_ID_EXCEED_VD_RES_LIMIT	328
22020 - LOG_ID_FAIL_CREATE_HA_SOCKET	329
22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY	330
22030 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FAZ	330
22031 - LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED	331
22032 - LOG_ID_CSF_LOOP_FOUND	332
22100 - LOG_ID_QUAR_DROP_TRAN_JOB	333
22101 - LOG_ID_QUAR_DROP_TLL_JOB	334
22102 - LOG_ID_LOG_DISK_FAILURE	334
22103 - LOG_ID_QUAR_LIMIT_REACHED	335
22104 - LOG_ID_POWER_RESTORE	336
22105 - LOG_ID_POWER_FAILURE	337
22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED	337
22107 - LOG_ID_VOLT_ANOM	338
22108 - LOG_ID_FAN_ANOM	339
22109 - LOG_ID_TEMP_TOO_HIGH	340
22110 - LOG_ID_SPARE_BLOCK_LOW	340
22111 - LOG_ID_POWER_RESTORE_NOTIF	341
22112 - LOG_ID_POWER_FAILURE_WARNING	342
22113 - LOG_ID_FNBAM_FAILURE	342
22150 - LOG_ID_VOLT_NOM	343
22151 - LOG_ID_FAN_NOM	344
22152 - LOG_ID_TEMP_TOO_LOW	345
22153 - LOG_ID_TEMP_NORM	345
22200 - LOG_ID_AUTO_UPT_CERT	346
22201 - LOG_ID_AUTO_GEN_CERT	347
22203 - LOG_ID_AUTO_GEN_CERT_FAIL	348
22204 - LOG_ID_AUTO_GEN_CERT_PENDING	349
22205 - LOG_ID_AUTO_GEN_CERT_SUCC	349
22206 - LOG_ID_CRL_EXPIRED	350
22700 - LOG_ID_IPS_FAIL_OPEN	351
22701 - LOG_ID_IPS_FAIL_OPEN_END	352
22800 - LOG_ID_SCAN_SERV_FAIL	352
22802 - LOG_ID_ENTER_FD_CONSERVE_MODE	353
22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE	354
22804 - LOG_ID_LIC_STATUS_CHG	355
22805 - LOG_ID_FAIL_TO_VALIDATE_LIC	356
22806 - LOG_ID_DUP_LIC	356
22807 - LOG_ID_LEAVE_FD_CONSERVE_MODE_NOTIF	357
22808 - LOG_ID_LIC_EXPIRE	358
22809 - LOG_ID_LIC_WILL_EXPIRE	359
22891 - LOG_ID_FLCFGD	359
22892 - LOG_ID_FLCFGD_INFO	360

22893 - LOG_ID_FLCFGD_WARNING	361
22900 - LOG_ID_CAPUTP_SESSION	362
22901 - LOG_ID_FAZ_CON	362
22902 - LOG_ID_FAZ_DISCON	363
22903 - LOG_ID_FAZ_CON_ERR	364
22904 - LOG_ID_CAPUTP_SESSION_NOTIF	365
22912 - LOG_ID_FDS_SRV_ERRCON	365
22913 - LOG_ID_FDS_SRV_DISCON	366
22914 - LOG_ID_FDS_SRV_CHG	367
22915 - LOG_ID_FDS_SRV_CON	368
22916 - LOG_ID_FDS_STATUS	368
22917 - LOG_ID_FDS_SMS_QUOTA	369
22918 - LOG_ID_FDS_CTRL_STATUS	370
22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED	370
22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS	371
22923 - LOG_ID_EVENT_VWL_LQTY_STATUS	372
22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS	373
22950 - LOG_ID_FDS_LOGIN_SUCC	373
22951 - LOG_ID_FDS_LOGOUT	374
22952 - LOG_ID_FDS_LOGIN_FAIL	375
23101 - LOG_ID_IPSEC_TUNNEL_UP	376
23102 - LOG_ID_IPSEC_TUNNEL_DOWN	376
23103 - LOG_ID_IPSEC_TUNNEL_STAT	377
26001 - LOG_ID_DHCP_ACK	378
26002 - LOG_ID_DHCP_RELEASE	379
26003 - LOG_ID_DHCP_STAT	380
26004 - LOG_ID_DHCP_CLIENT_LEASE	381
26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH	381
26006 - LOG_ID_DHCP_LEASE_USAGE_FULL	382
26007 - LOG_ID_DHCP_BLOCKED_MAC	383
26008 - LOG_ID_DHCP_DDNS_ADD	384
26009 - LOG_ID_DHCP_DDNS_DELETE	384
26010 - LOG_ID_DHCP_DDNS_COMPLETED	385
26011 - LOG_ID_DHCPV6_REPLY	386
26012 - LOG_ID_DHCPV6_RELEASE	387
27001 - LOG_ID_VRRP_STATE_CHG	388
29001 - LOG_ID_PPPD_MSG	388
29002 - LOG_ID_PPPD_AUTH_SUC	389
29003 - LOG_ID_PPPD_AUTH_FAIL	390
29010 - LOG_ID_PPPOE_STATUS_REPORT_NOTIF	391
29011 - LOG_ID_PPPD_FAIL_TO_EXEC	392
29012 - LOG_ID_PPP_OPT_ERR	392
29013 - LOG_ID_PPPD_START	393
29014 - LOG_ID_PPPD_EXIT	394
29015 - LOG_ID_PPP_RCV_BAD_PEER_IP	394
29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP	395

29017 - LOG_ID_PPP_OPT_NOTIF	396
29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED	396
29022 - LOG_ID_DDNS_UPDATE_FAIL	397
32001 - LOG_ID_ADMIN_LOGIN_SUCC	398
32002 - LOG_ID_ADMIN_LOGIN_FAIL	399
32003 - LOG_ID_ADMIN_LOGOUT	400
32005 - LOG_ID_ADMIN_OVERRIDE_VDOM	401
32006 - LOG_ID_ADMIN_ENTER_VDOM	402
32007 - LOG_ID_ADMIN_LEFT_VDOM	403
32008 - LOG_ID_VIEW_DISK_LOG_FAIL	403
32009 - LOG_ID_SYSTEM_START	404
32010 - LOG_ID_DISK_LOG_FULL	405
32011 - LOG_ID_LOG_ROLL	406
32014 - LOG_ID_CS_LIC_EXPIRE	406
32015 - LOG_ID_DISK_LOG_USAGE	407
32016 - LOG_ID_FDS_QUOTA_WARN	408
32017 - LOG_ID_FDS_DAILY_QUOTA_FULL	408
32018 - LOG_ID_FIPS_ENTER_ERR_MOD	409
32019 - LOG_ID_CC_ENTER_ERR_MOD	410
32020 - LOG_ID_SSH_CORRPUT_MAC	410
32021 - LOG_ID_ADMIN_LOGIN_DISABLE	411
32022 - LOG_ID_VDOM_ENABLED	412
32023 - LOG_ID_MEM_LOG_FIRST_FULL	413
32024 - LOG_ID_ADMIN_PASSWD_EXPIRE	413
32025 - LOG_ID_SSH_REKEY	414
32026 - LOG_ID_SSH_BAD_PACKET_LENGTH	415
32027 - LOG_ID_VIEW_DISK_LOG_SUCC	416
32028 - LOG_ID_LOG_DEL_DIR	416
32029 - LOG_ID_LOG_DEL_FILE	417
32030 - LOG_ID_SEND_FDS_STAT	418
32031 - LOG_ID_VIEW_MEM_LOG_FAIL	419
32032 - LOG_ID_DISK_DLP_ARCH_FULL	419
32033 - LOG_ID_DISK_QUAR_FULL	420
32034 - LOG_ID_DISK_REPORT_FULL	421
32035 - LOG_ID_VDOM_DISABLED	421
32036 - LOG_ID_DISK_IPS_ARCH_FULL	422
32037 - LOG_ID_DISK_LOG_FIRST_FULL	423
32038 - LOG_ID_LOG_ROLL_FORTICRON	423
32039 - LOG_ID_VIEW_MEM_LOG_SUCC	424
32040 - LOG_ID_REPORT_DELETED	425
32041 - LOG_ID_REPORT_DELETED_GUI	426
32042 - LOG_ID_MEM_LOG_SECOND_FULL	426
32043 - LOG_ID_MEM_LOG_FINAL_FULL	427
32044 - LOG_ID_LOG_DELETE	428
32045 - LOG_ID_MGR_LIC_EXPIRE	429
32046 - LOG_ID_SSL_CORRPUT_MAC	429

32048 - LOG_ID_SCHEDULE_EXPIRE	430
32049 - LOG_ID_FC_EXPIRE	431
32050 - LOG_ID_POL_PKT_CAPTURE_FULL	431
32051 - LOG_ID_LOG_UPLOAD	432
32052 - LOG_ID_UPLOAD_RUN_SCRIPT	433
32053 - LOG_ID_ADMIN_MTNER_LOGIN_SUCC	433
32054 - LOG_ID_ADMIN_MTNER_LOGOUT	434
32055 - LOG_ID_FDS_QUOTA_WARN_WARNING	435
32056 - LOG_ID_FDS_QUOTA_WARN_INFO	436
32057 - LOG_ID_VIEW_FAZ_LOG_FAIL	437
32058 - LOG_ID_VIEW_FAZ_LOG_SUCC	437
32095 - LOG_ID_GUI_CHG_SUB_MODULE	438
32097 - LOG_ID_DELETE_CAPTURE_PKT	439
32100 - LOG_ID_FORTI_TOKEN_SYNC	440
32102 - LOG_ID_CHG_CONFIG	441
32103 - LOG_ID_NEW_FIRMWARE	441
32104 - LOG_ID_CHG_CONFIG_GUI	442
32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE	443
32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE	444
32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE	444
32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE	445
32109 - LOG_ID_UPD_SIGN_AV_DB	446
32110 - LOG_ID_UPD_SIGN_IPS_DB	447
32111 - LOG_ID_UPD_SIGN_AVIPS_DB	448
32113 - LOG_ID_UPD_SIGN_SRCVIS_DB	448
32114 - LOG_ID_UPD_SIGN_GEOIP_DB	449
32115 - LOG_ID_UPD_SIGN_SERVER_LIST	450
32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE	451
32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS	451
32118 - LOG_ID_UPD_ADMIN_AV_DB	452
32119 - LOG_ID_UPD_SCANUNIT_AV_DB	453
32120 - LOG_ID_RPT_ADD_DATASET	454
32122 - LOG_ID_RPT_DEL_DATASET	454
32125 - LOG_ID_RPT_ADD_CHART	455
32126 - LOG_ID_RPT_DEL_CHART	456
32129 - LOG_ID_ADD_GUEST	457
32130 - LOG_ID_CHG_USER	458
32131 - LOG_ID_DEL_GUEST	458
32132 - LOG_ID_ADD_USER	459
32138 - LOG_ID_REBOOT	460
32140 - LOG_ID_TIME_USER_SETTING_CHG	461
32141 - LOG_ID_TIME_NTP_SETTING_CHG	462
32142 - LOG_ID_BACKUP_CONF	462
32143 - LOG_ID_BACKUP_CONF_BY_SCP	463
32144 - LOG_ID_BACKUP_CONF_ERROR	464
32145 - LOG_ID_BACKUP_CONF_ALERT	465

32148 - LOG_ID_GET_CRL	466
32149 - LOG_ID_COMMAND_FAIL	466
32151 - LOG_ID_ADD_IP6_LOCAL_POL	467
32152 - LOG_ID_CHG_IP6_LOCAL_POL	468
32153 - LOG_ID_DEL_IP6_LOCAL_POL	469
32155 - LOG_ID_ACT_FTOKEN_REQ	469
32156 - LOG_ID_ACT_FTOKEN_SUCC	470
32157 - LOG_ID_SYNC_FTOKEN_SUCC	471
32158 - LOG_ID_SYNC_FTOKEN_FAIL	472
32159 - LOG_ID_ACT_FTOKEN_FAIL	473
32160 - LOG_ID_FTM_PUSH_SUCC	473
32161 - LOG_ID_FTM_PUSH_FAIL	474
32168 - LOG_ID_REACH_VDOM_LIMIT	475
32169 - LOG_ID_ALARM_DLP_DB	475
32170 - LOG_ID_ALARM_MSG	476
32171 - LOG_ID_ALARM_ACK	477
32172 - LOG_ID_ADD_IP4_LOCAL_POL	478
32173 - LOG_ID_CHG_IP4_LOCAL_POL	479
32174 - LOG_ID_DEL_IP4_LOCAL_POL	479
32190 - LOG_ID_UPT_INVALID_IMG	480
32191 - LOG_ID_UPT_INVALID_IMG_CC	481
32192 - LOG_ID_UPT_INVALID_IMG_RSA	482
32193 - LOG_ID_UPT_IMG_RSA	482
32194 - LOG_ID_UPT_IMG_FAIL	483
32199 - LOG_ID_RESTORE_IMG_USB	484
32200 - LOG_ID_SHUTDOWN	485
32201 - LOG_ID_LOAD_IMG_SUCC	486
32202 - LOG_ID_RESTORE_IMG	486
32203 - LOG_ID_RESTORE_CONF	487
32204 - LOG_ID_RESTORE_FGD_SVR	488
32205 - LOG_ID_RESTORE_VDOM_LIC	489
32206 - LOG_ID_RESTORE_SCRIPT	489
32207 - LOG_ID_RETRIEVE_CONF_LIST	490
32208 - LOG_ID_IMP_PKCS12_CERT	491
32209 - LOG_ID_RESTORE_USR_DEF_IPS	492
32210 - LOG_ID_BACKUP_IMG_SUCC	493
32211 - LOG_ID_UPLOAD_REVISION	493
32212 - LOG_ID_DEL_REVISION	494
32213 - LOG_ID_RESTORE_TEMPLATE	495
32214 - LOG_ID_RESTORE_FILE	496
32215 - LOG_ID_UPT_IMG	496
32217 - LOG_ID_UPD_IPS	497
32218 - LOG_ID_UPD_DLP	498
32219 - LOG_ID_BACKUP_OUTPUT	499
32220 - LOG_ID_BACKUP_COMMAND	499
32221 - LOG_ID_UPD_VDOM_LIC	500

32222 - LOG_ID_GLB_SETTING_CHG	501
32223 - LOG_ID_BACKUP_USER_DEF_IPS	502
32224 - LOG_ID_BACKUP_DISK_LOG	503
32225 - LOG_ID_DEL_ALL_REVISION	504
32226 - LOG_ID_LOAD_IMG_FAIL	504
32227 - LOG_ID_UPD_DLP_FAIL	505
32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG	506
32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA	507
32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA	507
32231 - LOG_ID_RESTORE_FGD_SVR_FAIL	508
32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL	509
32233 - LOG_ID_BACKUP_IMG_FAIL	510
32234 - LOG_ID_RESTORE_IMG_INVALID_CC	511
32235 - LOG_ID_RESTORE_IMG_FORTIGUARD	511
32236 - LOG_ID_BACKUP_MEM_LOG	512
32237 - LOG_ID_BACKUP_MEM_LOG_FAIL	513
32238 - LOG_ID_BACKUP_DISK_LOG_FAIL	514
32239 - LOG_ID_BACKUP_DISK_LOG_USB	514
32240 - LOG_ID_SYS_USB_MODE	515
32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL	516
32242 - LOG_ID_UPD_VDOM_LIC_FAIL	517
32243 - LOG_ID_UPD_IPS_SCP	517
32244 - LOG_ID_UPD_IPS_SCP_FAIL	518
32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL	519
32246 - LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL	520
32247 - LOG_ID_SSH_NEGOTIATION_FAILURE	521
32252 - LOG_ID_FACTORY_RESET	521
32253 - LOG_ID_FORMAT_RAID	522
32254 - LOG_ID_ENABLE_RAID	523
32255 - LOG_ID_DISABLE_RAID	524
32300 - LOG_ID_UPLOAD_RPT_IMG	524
32301 - LOG_ID_ADD_VDOM	525
32302 - LOG_ID_DEL_VDOM	526
32400 - LOG_ID_CONF_CHG	527
32545 - LOG_ID_SYS_RESTART	528
32546 - LOG_ID_APPLICATION_CRASH	528
32547 - LOG_ID_AUTOSCRIPT_START	529
32548 - LOG_ID_AUTOSCRIPT_STOP	530
32549 - LOG_ID_AUTOSCRIPT_STOP_AUTO	531
32550 - LOG_ID_AUTOSCRIPT_DELETE_RSLT	531
32551 - LOG_ID_AUTOSCRIPT_BACKUP_RSLT	532
32552 - LOG_ID_AUTOSCRIPT_CHECK_STATUS	533
32553 - LOG_ID_AUTOSCRIPT_STOP_REACH_LIMIT	534
32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT	534
32562 - LOG_ID_STORE_CONF_FAIL_SPACE	535
32564 - LOG_ID_RESTORE_CONF_FAIL	536

32565 - LOG_ID_RESTORE_CONF_BY_MGMT	537
32566 - LOG_ID_RESTORE_CONF_BY_SCP	538
32567 - LOG_ID_RESTORE_CONF_BY_USB	538
32568 - LOG_ID_DEL_REVISION_DB	539
32569 - LOG_ID_FSW_SWITCH_LOG_EVENT	540
32570 - LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT	541
32571 - LOG_ID_RESTORE_CONF_FAIL_WARNING	542
32601 - LOG_ID_FGT_SWITCH_LOG_DISCOVER	543
32602 - LOG_ID_FGT_SWITCH_LOG_AUTH	543
32603 - LOG_ID_FGT_SWITCH_LOG_DEAUTH	544
32604 - LOG_ID_FGT_SWITCH_LOG_DELETE	545
32605 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP	546
32606 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN	546
32607 - LOG_ID_FGT_SWITCH_PUSH_IMAGE	547
32608 - LOG_ID_FGT_SWITCH_STAGE_IMAGE	548
32693 - LOG_ID_FGT_SWITCH_GROUP_SWC	549
32694 - LOG_ID_FGT_SWITCH_GROUP_POE	549
32695 - LOG_ID_FGT_SWITCH_GROUP_LINK	550
32696 - LOG_ID_FGT_SWITCH_GROUP_STP	551
32697 - LOG_ID_FGT_SWITCH_GROUP_SWITCH	552
32698 - LOG_ID_FGT_SWITCH_GROUP_ROUTER	553
32699 - LOG_ID_FGT_SWITCH_GROUP_SYSTEM	554
35001 - LOG_ID_HA_SYNC_VIRDB	555
35002 - LOG_ID_HA_SYNC_ETDB	555
35003 - LOG_ID_HA_SYNC_EXDB	556
35004 - LOG_ID_HA_SYNC_FLDB	557
35005 - LOG_ID_HA_SYNC_IPS	557
35007 - LOG_ID_HA_SYNC_AV	558
35009 - LOG_ID_HA_SYNC_CID	559
35010 - LOG_ID_HA_SYNC_UWDB	559
35011 - LOG_ID_HA_SYNC_FAIL	560
35012 - LOG_ID_CONF_SYNC_FAIL	561
36880 - LOG_ID_EVENT_SYSTEM_MAC_HOST_STORE_LIMIT	561
36881 - LOG_ID_EVENT_SYSTEM_CFG_REVERT	562
36882 - LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED	563
37120 - MSGID_NEG_GENERIC_P1_NOTIF	563
37121 - MSGID_NEG_GENERIC_P1_ERROR	565
37122 - MSGID_NEG_GENERIC_P2_NOTIF	566
37123 - MSGID_NEG_GENERIC_P2_ERROR	567
37124 - MSGID_NEG_I_P1_ERROR	568
37125 - MSGID_NEG_I_P2_ERROR	570
37126 - MSGID_NEG_NO_STATE_ERROR	571
37127 - MSGID_NEG_PROGRESS_P1_NOTIF	572
37128 - MSGID_NEG_PROGRESS_P1_ERROR	573
37129 - MSGID_NEG_PROGRESS_P2_NOTIF	575
37130 - MSGID_NEG_PROGRESS_P2_ERROR	576

37131 - MESSAGESID_ESP_ERROR	577
37132 - MESSAGESID_ESP_CRITICAL	579
37133 - MESSAGESID_INSTALL_SA	580
37134 - MESSAGESID_DELETE_P1_SA	581
37135 - MESSAGESID_DELETE_P2_SA	582
37136 - MESSAGESID_DPD_FAILURE	583
37137 - MESSAGESID_CONN_FAILURE	585
37138 - MESSAGESID_CONN_UPDOWN	586
37139 - MESSAGESID_P2_UPDOWN	587
37141 - MESSAGESID_CONN_STATS	588
37184 - MESSAGESID_NEG_GENERIC_P1_NOTIF_IKEV2	590
37185 - MESSAGESID_NEG_GENERIC_P1_ERROR_IKEV2	591
37186 - MESSAGESID_NEG_GENERIC_P2_NOTIF_IKEV2	592
37187 - MESSAGESID_NEG_GENERIC_P2_ERROR_IKEV2	593
37188 - MESSAGESID_NEG_I_P1_ERROR_IKEV2	595
37189 - MESSAGESID_NEG_I_P2_ERROR_IKEV2	596
37190 - MESSAGESID_NEG_NO_STATE_ERROR_IKEV2	597
37191 - MESSAGESID_NEG_PROGRESS_P1_NOTIF_IKEV2	598
37192 - MESSAGESID_NEG_PROGRESS_P1_ERROR_IKEV2	600
37193 - MESSAGESID_NEG_PROGRESS_P2_NOTIF_IKEV2	601
37194 - MESSAGESID_NEG_PROGRESS_P2_ERROR_IKEV2	602
37195 - MESSAGESID_ESP_ERROR_IKEV2	604
37196 - MESSAGESID_ESP_CRITICAL_IKEV2	605
37197 - MESSAGESID_INSTALL_SA_IKEV2	606
37198 - MESSAGESID_DELETE_P1_SA_IKEV2	607
37199 - MESSAGESID_DELETE_P2_SA_IKEV2	609
37200 - MESSAGESID_DPD_FAILURE_IKEV2	610
37201 - MESSAGESID_CONN_FAILURE_IKEV2	611
37202 - MESSAGESID_CONN_UPDOWN_IKEV2	612
37203 - MESSAGESID_P2_UPDOWN_IKEV2	613
37204 - MESSAGESID_CONN_STATS_IKEV2	615
37888 - MESSAGESID_HA_GROUP_DELETE	616
37889 - MESSAGESID_VC_DELETE	617
37890 - MESSAGESID_VC_MOVE_VDOM	617
37891 - MESSAGESID_VC_ADD_VDOM	618
37892 - MESSAGESID_VC_MOVE_MEMB_STATE	619
37893 - MESSAGESID_VC_DETECT_MEMB_DEAD	620
37894 - MESSAGESID_VC_DETECT_MEMB_JOIN	620
37895 - MESSAGESID_VC_ADD_HADEV	621
37896 - MESSAGESID_VC_DEL_HADEV	622
37897 - MESSAGESID_HADEV_READY	623
37898 - MESSAGESID_HADEV_FAIL	623
37899 - MESSAGESID_HADEV_PEERINFO	624
37900 - MESSAGESID_HBDEV_DELETE	625
37901 - MESSAGESID_HBDEV_DOWN	626
37902 - MESSAGESID_HBDEV_UP	626

37903 - MESSAGESID_SYNC_STATUS	627
37904 - MESSAGESID_HA_ACTIVITY	628
37905 - MESSAGESID_HA_ENABLE_SET_AS_MASTER	629
37906 - MESSAGESID_HA_DISABLE_SET_AS_MASTER	629
37907 - MESSAGESID_VLAN_HB_UP	630
37908 - MESSAGESID_VLAN_HB_DOWN	631
37909 - MESSAGESID_VLAN_HB_DOWN_SUM	631
37910 - MESSAGESID_HA_ACTIVITY_INFO	632
38010 - LOG_ID_FIPS_ENCRY_FAIL	633
38011 - LOG_ID_FIPS_DECRY_FAIL	634
38012 - LOG_ID_ENTROPY_TOKEN	634
38031 - LOG_ID_FSSO_LOGON	635
38032 - LOG_ID_FSSO_LOGOFF	636
38033 - LOG_ID_FSSO_SVR_STATUS	637
38400 - LOGID_EVENT_NOTIF_SEND_SUCC	638
38401 - LOGID_EVENT_NOTIF_SEND_FAIL	639
38402 - LOGID_EVENT_NOTIF_DNS_FAIL	640
38403 - LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE	641
38404 - LOGID_EVENT_NOTIF_HOSTNAME_ERROR	641
38405 - LOGID_NOTIF_CODE_SENDTO_SMS_PHONE	642
38406 - LOGID_NOTIF_CODE_SENDTO_SMS_TO	643
38407 - LOGID_NOTIF_CODE_SENDTO_EMAIL	644
38408 - LOGID_EVENT_OFTP_SSL_CONNECTED	644
38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED	645
38410 - LOGID_EVENT_OFTP_SSL_FAILED	646
38411 - LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO	647
38412 - LOGID_EVENT_TOKEN_CODE_SENDTO	648
38420 - LOGID_EVENT_HTTPS_CONNECTION	648
38656 - LOGID_EVENT_RAD_RPT_PROTO_ERROR	649
38657 - LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND	650
38658 - LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND	651
38659 - LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED	651
38660 - LOGID_EVENT_RAD_RPT_ACCT_EVENT	652
38661 - LOGID_EVENT_RAD_RPT_OTHER	653
38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR	654
38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND	654
38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED	655
38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT	656
38667 - LOGID_EVENT_RAD_STAT_OTHER	657
38668 - LOGID_EVENT_RAD_STAT_EP_BLK	658
39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP	659
39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN	659
39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL	660
39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS	661
39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY	662
39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS	663

39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT	664
39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE	665
39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY	666
39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK	667
39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON	668
39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT	669
39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL	670
39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR	671
39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP	672
39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN	673
39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS	674
39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG	675
39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR	676
39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE	677
39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE	678
40001 - LOG_ID_PPTP_TUNNEL_UP	679
40002 - LOG_ID_PPTP_TUNNEL_DOWN	680
40003 - LOG_ID_PPTP_TUNNEL_STAT	681
40014 - LOG_ID_PPTP_REACH_MAX_CON	682
40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL	683
40019 - LOG_ID_L2TPD_CLIENT_DISCON	683
40021 - LOG_ID_PPTP_NOT_CONIG	684
40022 - LOG_ID_PPTP_NO_IP_AVAIL	685
40024 - LOG_ID_PPTP_OUT_MEM	686
40034 - LOG_ID_PPTP_START	686
40035 - LOG_ID_PPTP_START_FAIL	687
40036 - LOG_ID_PPTP_EXIT	688
40037 - LOG_ID_PPTPD_SVR_DISCON	689
40038 - LOG_ID_PPTPD_CLIENT_CON	689
40039 - LOG_ID_PPTPD_CLIENT_DISCON	690
40101 - LOG_ID_L2TP_TUNNEL_UP	691
40102 - LOG_ID_L2TP_TUNNEL_DOWN	692
40103 - LOG_ID_L2TP_TUNNEL_STAT	693
40114 - LOG_ID_L2TPD_START	694
40115 - LOG_ID_L2TPD_EXIT	694
40118 - LOG_ID_L2TPD_CLIENT_CON	695
40704 - LOG_ID_EVENT_SYS_PERF	696
40960 - LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR	697
41000 - LOG_ID_UPD_FGT_SUCC	698
41001 - LOG_ID_UPD_FGT_FAIL	698
41002 - LOG_ID_UPD_SRC_VIS	699
41006 - LOG_ID_UPD_FSA_VIRDB	700
41984 - LOG_ID_EVENT_VPN_CERT_LOAD	701
41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL	701
41986 - LOG_ID_EVENT_VPN_CERT_REGEN	702
41987 - LOG_ID_EVENT_VPN_CERT_UPDATE	703

41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE	704
41989 - LOG_ID_EVENT_VPN_CERT_ERR	705
41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED	706
41991 - LOG_ID_EVENT_VPN_CERT_EXPORT	707
42201 - LOG_ID_NETX_VMX_ATTACH	707
42202 - LOG_ID_NETX_VMX_DETACH	708
42203 - LOG_ID_NETX_VMX_DENIED	709
43008 - LOG_ID_EVENT_AUTH_SUCCESS	709
43009 - LOG_ID_EVENT_AUTH_FAILED	710
43010 - LOG_ID_EVENT_AUTH_LOCKOUT	711
43011 - LOG_ID_EVENT_AUTH_TIME_OUT	712
43012 - LOG_ID_EVENT_AUTH_FSAE_AUTH_SUCCESS	713
43013 - LOG_ID_EVENT_AUTH_FSAE_AUTH_FAIL	714
43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON	715
43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF	716
43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS	717
43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL	718
43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL	719
43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS	720
43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS	721
43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED	722
43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT	723
43028 - LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED	724
43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS	725
43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL	726
43032 - LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED	727
43033 - LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN	728
43034 - LOG_ID_EVENT_AUTH_PROXY_NO_RESP	729
43037 - LOG_ID_EVENT_AUTH_IPV4_FLUSH	730
43038 - LOG_ID_EVENT_AUTH_IPV6_FLUSH	730
43039 - LOG_ID_EVENT_AUTH_LOGON	731
43040 - LOG_ID_EVENT_AUTH_LOGOUT	732
43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT	733
43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE	734
43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS	735
43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL	736
43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS	737
43046 - LOG_ID_EVENT_AUTH_8021X_FAIL	738
43050 - LOG_ID_EVENT_AUTH_FSAE_CONNECT	739
43051 - LOG_ID_EVENT_AUTH_FSAE_DISCONNECT	739
43264 - LOGID_MMS_STATS	740
43520 - LOG_ID_EVENT_WIRELESS_SYS	741
43521 - LOG_ID_EVENT_WIRELESS_ROGUE	742
43522 - LOG_ID_EVENT_WIRELESS_WTP	743
43524 - LOG_ID_EVENT_WIRELESS_STA	744
43525 - LOG_ID_EVENT_WIRELESS_ONWIRE	745

43526 - LOG_ID_EVENT_WIRELESS_WTPR	747
43527 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG	748
43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR	749
43529 - LOG_ID_EVENT_WIRELESS_CLB	750
43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE	751
43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH	752
43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP	753
43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI	754
43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR	756
43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV	757
43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD	758
43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD	759
43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH	760
43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP	762
43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE	763
43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN	764
43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE	765
43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL	766
43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE	766
43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET	767
43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK	768
43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE	769
43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR	770
43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH	771
43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED	772
43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP	773
43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN	774
43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT	774
43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR	776
43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR	777
43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE	779
43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT	780
43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR	782
43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED	783
43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED	785
43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG	786
43572 - LOG_ID_EVENT_WIRELESS_STA ASSO	788
43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH	789
43574 - LOG_ID_EVENT_WIRELESS_STA_DASS	790
43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT	792
43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE	793
43577 - LOG_ID_EVENT_WIRELESS_STA_DENY	794
43578 - LOG_ID_EVENT_WIRELESS_STA_KICK	795
43579 - LOG_ID_EVENT_WIRELESS_STA_IP	796
43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP	798
43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN	799

43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED	800
43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED	801
43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE	802
43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED	803
43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN	803
43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START	804
43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN	805
43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR	806
43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL	807
43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS	808
43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY	809
43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER	810
43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER	811
43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY	812
43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY	813
43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD	814
43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS	815
43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL	816
43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP	817
43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON	818
43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS	819
43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE	821
43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST	822
43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS	823
43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE	824
43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK	826
43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE	827
43609 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_START	828
43610 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_STOP	829
43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP	829
43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED	830
43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR	831
43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION	832
43615 - LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL	833
43617 - LOG_ID_EVENT_WIRELESS_WTPPROF_ADJUSTED	834
43618 - LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS	834
43621 - LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG	835
43776 - LOG_ID_EVENT_NAC_QUARANTINE	836
43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE	837
43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN	839
43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE	840
43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND	840
43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST	841
43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE	842
43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND	843
43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST	844

43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE	845
43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE	845
43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE	846
44544 - LOGID_EVENT_CONFIG_PATH	847
44545 - LOGID_EVENT_CONFIG_OBJ	848
44546 - LOGID_EVENT_CONFIG_ATTR	849
44547 - LOGID_EVENT_CONFIG_OBJATTR	850
44548 - LOGID_EVENT_CONFIG_EXEC	850
44549 - LOGID_EVENT_CONFIG_OBJATTR_MTNER	851
44550 - LOGID_EVENT_CONFIG_OBJ_MTNER	852
44551 - LOGID_EVENT_CONFIG_ATTR_MTNER	853
44552 - LOGID_EVENT_CONFIG_PATH_MTNER	854
44553 - LOGID_EVENT_CONFIG_FIXEDPORT_DIS	855
45000 - LOG_ID_VSD_SSL_RCV_HS	856
45001 - LOG_ID_VSD_SSL_RCV_WRG_HS	857
45002 - LOG_ID_VSD_SSL_SENT_HS	858
45003 - LOG_ID_VSD_SSL_WRG_HS_LEN	859
45004 - LOG_ID_VSD_SSL_RCV_CCS	860
45005 - LOG_ID_VSD_SSL_RSA_DH_FAIL	860
45006 - LOG_ID_VSD_SSL_SENT_CCS	861
45007 - LOG_ID_VSD_SSL_BAD_HASH	862
45009 - LOG_ID_VSD_SSL_DECRY_FAIL	863
45010 - LOG_ID_VSD_SSL_SESSION_CLOSED	864
45011 - LOG_ID_VSD_SSL_LESS_MINOR	865
45012 - LOG_ID_VSD_SSL_REACH_MAX_CON	866
45013 - LOG_ID_VSD_SSL_NOT_SUPPORT_CS	867
45016 - LOG_ID_VSD_SSL_HS_FIN	868
45017 - LOG_ID_VSD_SSL_HS_TOO_LONG	869
45018 - LOG_ID_VSD_SSL_MORE_MINOR	870
45019 - LOG_ID_VSD_SSL_SENT_ALERT_ERR	871
45020 - LOG_ID_VSD_SSL_SESSION_EXPIRE	872
45021 - LOG_ID_VSD_SSL_SENT_ALERT	873
45022 - LOG_ID_VSD_SSL_RCV_CH	874
45023 - LOG_ID_VSD_SSL_RCV_SH	875
45024 - LOG_ID_VSD_SSL_SENT_SH	877
45025 - LOG_ID_VSD_SSL_RCV_ALERT	878
45026 - LOG_ID_VSD_SSL_RCV_ALERT_DEBUG	879
45027 - LOG_ID_VSD_SSL_INVALID_CONT_TYPE	880
45029 - LOG_ID_VSD_SSL_BAD_CCS_LEN	881
45031 - LOG_ID_VSD_SSL_BAD_DH	882
45032 - LOG_ID_VSD_SSL_PUB_KEY_TOO_BIG	883
45033 - LOG_ID_VSD_SSL_NOT_SUPPORT_CM	884
45034 - LOG_ID_VSD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH	885
45035 - LOG_ID_VSD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH	886
45057 - LOG_ID_FCC_ADD	887

45058 - LOG_ID_FCC_CLOSE	888
45061 - LOG_ID_FCC_CLOSE_BY_TYPE	889
45071 - LOG_ID_FCC_VULN_SCAN	890
45081 - LOG_ID_FCC_COMPL_CHANGE	891
45082 - LOG_ID_FCC_NOT_COMPL	892
45083 - LOG_ID_FCC_NOT_COMPL_DEBUG	893
45100 - LOG_ID_EC_REG_FAIL_LIMIT	894
45101 - LOG_ID_EC_REG_SUCCEED	895
45102 - LOG_ID_EC_REG_RENEWED	896
45103 - LOG_ID_EC_REG_BLOCK	897
45104 - LOG_ID_EC_REG_UNBLOCK	897
45105 - LOG_ID_EC_REG_DEREG	898
45106 - LOG_ID_EC_REG_LIC_UPGRADED	899
45107 - LOG_ID_EC_CONF_DISTRIBUTED	899
45108 - LOG_ID_EC_FTCL_UNREG	900
45109 - LOG_ID_EC_FTCL_LOGOFF	901
45110 - LOG_ID_EC_FTCL_ENABLE_NOTSYNC	902
45111 - LOG_ID_EC_REG_SYNC_FAIL	903
45112 - LOG_ID_EC_REG_FAIL_KEY	904
45113 - LOG_ID_EC_REG_FAIL_BLOCKED	904
45114 - LOG_ID_EC_REG_QUARANTINE	905
45115 - LOG_ID_EC_REG_UNQUARANTINE	906
45116 - LOG_ID_EC_REG_UNQUARANTINE_ALL	907
45117 - LOG_ID_EC_REG_FAIL_VER	908
45151 - LOG_ID_EVENT_DSSCC_FAIL	908
45152 - LOG_ID_EVENT_DSSCC_PASS	909
45161 - LOG_ID_EVENT_DSSCC_EXEC	910
46000 - LOG_ID_VIP_REAL_SVR_ENA	911
46001 - LOG_ID_VIP_REAL_SVR_DISA	912
46002 - LOG_ID_VIP_REAL_SVR_UP	913
46003 - LOG_ID_VIP_REAL_SVR_DOWN	913
46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN	914
46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN	915
46006 - LOG_ID_VIP_REAL_SVR_FAIL	916
46400 - LOG_ID_EVENT_EXT_SYS	917
46401 - LOG_ID_EVENT_EXT_LOCAL	918
46402 - LOG_ID_EVENT_EXT_REMOTE	918
46403 - LOG_ID_EVENT_EXT_LOCAL_ERROR	919
46501 - LOG_ID_INTERNAL_LTE_MODEM_DETECTION	920
46502 - LOG_ID_INTERNAL_LTE_MODEM_GPSD	921
46503 - LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION	921
46504 - LOG_ID_INTERNAL_LTE_MODEM_BILLD	922
46505 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED	923
46506 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG	923
46507 - LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE	924
46508 - LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION	925

46509 - LOG_ID_INTERNAL_LTE_MODEM_REBOOT	925
46510 - LOG_ID_INTERNAL_LTE_MODEM_OP_MODE	926
46511 - LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF	927
46512 - LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE	927
46513 - LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION	928
46514 - LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER	929
46515 - LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR	929
46900 - LOG_ID_POE_STATUS_REPORT	930
47201 - LOG_ID_AMC_ENTER_BYPASS	931
47202 - LOG_ID_AMC_EXIT_BYPASS	931
47203 - LOG_ID_ENTER_BYPASS	932
47204 - LOG_ID_EXIT_BYPASS	933
48000 - LOG_ID_WAD_SSL_RCV_HS	933
48001 - LOG_ID_WAD_SSL_RCV_WRG_HS	934
48002 - LOG_ID_WAD_SSL_SENT_HS	935
48003 - LOG_ID_WAD_SSL_WRG_HS_LEN	936
48004 - LOG_ID_WAD_SSL_RCV_CCS	937
48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL	938
48006 - LOG_ID_WAD_SSL_SENT_CCS	939
48007 - LOG_ID_WAD_SSL_BAD_HASH	940
48009 - LOG_ID_WAD_SSL_DECRY_FAIL	941
48011 - LOG_ID_WAD_SSL_LESS_MINOR	942
48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS	943
48016 - LOG_ID_WAD_SSL_HS_FIN	944
48017 - LOG_ID_WAD_SSL_HS_TOO_LONG	944
48019 - LOG_ID_WAD_SSL_SENT_ALERT	945
48023 - LOG_ID_WAD_SSL_RCV_ALERT	946
48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE	947
48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN	948
48031 - LOG_ID_WAD_SSL_BAD_DH	949
48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG	950
48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT	951
48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT	952
48101 - LOG_ID_WAD_AUTH_FAIL_PSK	953
48102 - LOG_ID_WAD_AUTH_FAIL_OTH	954
48300 - LOG_ID_WRG_SVR_FGT_CONF	955
48301 - LOG_ID_UNEXP_APP_TYPE	956
51000 - LOG_ID_NB_TBL_CHG	957
52000 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY	958
52001 - LOG_ID_EVENT_SECURITY_AUDIT_DEVICE_SUMMARY	958
52002 - LOG_ID_EVENT_SECURITY_AUDIT_CHECK_RESULT	959
52003 - LOG_ID_EVENT_SECURITY_AUDIT_CHECK_RESULT_NOT_PASS	960
53000 - LOG_ID_SDNC_CONNECTED	961
53001 - LOG_ID_SDNC_DISCONNECTED	962
53002 - LOG_ID_SDNC_SUBSCRIBE	962
53003 - LOG_ID_SDNC_UNSUBSCRIBE	963

GTP	964
41216 - LOGID_GTP_FORWARD	964
41217 - LOGID_GTP_DENY	965
41218 - LOGID_GTP_RATE_LIMIT	967
41219 - LOGID_GTP_STATE_INVALID	968
41220 - LOGID_GTP_TUNNEL_LIMIT	970
41221 - LOGID_GTP_TRAFFIC_COUNT	971
41222 - LOGID_GTP_USER_DATA	973
41223 - LOGID_GTPV2_FORWARD	974
41224 - LOGID_GTPV2_DENY	975
41225 - LOGID_GTPV2_RATE_LIMIT	977
41226 - LOGID_GTPV2_STATE_INVALID	978
41227 - LOGID_GTPV2_TUNNEL_LIMIT	979
41228 - LOGID_GTPV2_TRAFFIC_COUNT	981
41229 - LOGID_GTPU_FORWARD	982
41230 - LOGID_GTPU_DENY	983
IPS	984
16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP	984
16385 - LOGID_ATTCK_SIGNATURE_ICMP	986
16386 - LOGID_ATTCK_SIGNATURE_OTHERS	988
16399 - LOGID_ATTACK_MALICIOUS_URL	989
Traffic	991
2 - LOG_ID_TRAFFIC_ALLOW	991
3 - LOG_ID_TRAFFIC_DENY	994
4 - LOG_ID_TRAFFIC_OTHER_START	997
5 - LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW	1001
6 - LOG_ID_TRAFFIC_OTHER_ICMP_DENY	1004
7 - LOG_ID_TRAFFIC_OTHER_INVALID	1007
8 - LOG_ID_TRAFFIC_WANOPT	1010
9 - LOG_ID_TRAFFIC_WEBCACHE	1012
10 - LOG_ID_TRAFFIC_EXPLICIT_PROXY	1015
11 - LOG_ID_TRAFFIC_FAIL_CONN	1017
12 - LOG_ID_TRAFFIC_MULTICAST	1019
13 - LOG_ID_TRAFFIC_END_FORWARD	1022
14 - LOG_ID_TRAFFIC_END_LOCAL	1026
15 - LOG_ID_TRAFFIC_START_FORWARD	1029
16 - LOG_ID_TRAFFIC_START_LOCAL	1032
17 - LOG_ID_TRAFFIC_SNIFFER	1035
19 - LOG_ID_TRAFFIC_BROADCAST	1039
20 - LOG_ID_TRAFFIC_STAT	1042
21 - LOG_ID_TRAFFIC_SNIFFER_STAT	1046
VoIP	1049
44032 - LOGID_EVENT_VOIP_SIP	1049
44033 - LOGID_EVENT_VOIP_SIP_BLOCK	1050
44034 - LOGID_EVENT_VOIP_SIP_FUZZING	1052
44035 - LOGID_EVENT_VOIP_SCCP_REGISTER	1053

44036 - LOGID_EVENT_VOIP_SCCP_UNREGISTER	1054
44037 - LOGID_EVENT_VOIP_SCCP_CALL_BLOCK	1056
44038 - LOGID_EVENT_VOIP_SCCP_CALL_INFO	1057
WAF	1058
30248 - LOGID_WAF_SIGNATURE_BLOCK	1058
30249 - LOGID_WAF_SIGNATURE_PASS	1060
30250 - LOGID_WAF_SIGNATURE_ERASE	1061
30251 - LOGID_WAF_CUSTOM_SIGNATURE_BLOCK	1063
30252 - LOGID_WAF_CUSTOM_SIGNATURE_PASS	1065
30253 - LOGID_WAF_METHOD_BLOCK	1066
30255 - LOGID_WAF_ADDRESS_LIST_BLOCK	1068
30257 - LOGID_WAF_CONSTRAINTS_BLOCK	1069
30258 - LOGID_WAF_CONSTRAINTS_PASS	1071
30259 - LOGID_WAF_URL_ACCESS_PERMIT	1072
30260 - LOGID_WAF_URL_ACCESS_BYPASS	1074
30261 - LOGID_WAF_URL_ACCESS_BLOCK	1075
Web	1077
12288 - LOG_ID_WEB_CONTENT_BANWORD	1077
12289 - LOG_ID_WEB_CONTENT_MMS_BANWORD	1079
12290 - LOG_ID_WEB_CONTENT_EXEMPTWORD	1081
12291 - LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD	1082
12292 - LOG_ID_WEB_CONTENT_KEYWORD	1084
12293 - LOG_ID_WEB_CONTENT_SEARCH	1086
12305 - LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF	1088
12544 - LOG_ID_URL_FILTER_BLOCK	1090
12545 - LOG_ID_URL_FILTER_EXEMPT	1091
12546 - LOG_ID_URL_FILTER_ALLOW	1093
12547 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK	1095
12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK	1097
12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS	1098
12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS	1100
12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK	1101
12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS	1102
12553 - LOG_ID_URL_FILTER_INVALID_CERT	1104
12554 - LOG_ID_URL_FILTER_INVALID_SESSION	1105
12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK	1107
12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS	1108
12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE	1110
12558 - LOG_ID_URL_FILTER_RATING_ERR	1111
12559 - LOG_ID_URL_FILTER_PASS	1112
12560 - LOG_ID_URL_WISP_BLOCK	1113
12561 - LOG_ID_URL_WISP_REDIR	1115
12562 - LOG_ID_URL_WISP_ALLOW	1117
12800 - LOG_ID_WEB_FTGD_ERR	1118
12801 - LOG_ID_WEB_FTGD_WARNING	1120
12802 - LOG_ID_WEB_FTGD_QUOTA	1122

13056 - LOG_ID_WEB_FTGD_CAT_BLK	1123
13057 - LOG_ID_WEB_FTGD_CAT_WARN	1125
13312 - LOG_ID_WEB_FTGD_CAT_ALLOW	1126
13313 - LOG_ID_WEB_FTGD_RULE_ALLOW	1128
13314 - LOG_ID_WEB_FTGD_OFF_SITE_ALLOW	1130
13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING	1132
13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED	1134
13317 - LOG_ID_WEB_URL	1136
13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX	1138
13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE	1139
13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET	1141
13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER	1143
13601 - LOG_ID_WEB_WF_COOKIE	1145
13602 - LOG_ID_WEB_WF_REFERERER	1146
13603 - LOG_ID_WEB_WF_COMMAND_BLOCK	1148
13616 - LOG_ID_CONTENT_TYPE_BLOCK	1149

Change Log

Date	Change Description
2018-11-27	Initial release.

Introduction

This document provides information about all the log messages applicable to the FortiGate devices running FortiOS version 5.6.7 or higher. The logs are intended for administrators to use as reference for more information about a specific log entry and message generated by FortiOS.

This document also provides information about log fields when FortiOS sends log messages to remote syslog servers in Common Event Format (CEF). See [CEF Support on page 47](#).

Before you begin

Before you begin using this reference, read the following notes:

- Information in this document applies to all FortiGate units that are currently running FortiOS 5.6.7 or higher.
- Ensure that you have enabled logging for the FortiOS unit. For more information, see the *Logging and Reporting* chapter in the *FortiOS Handbook*.
- Each log message is displayed in the *Log & Report* pane of the GUI. You can also download the RAW format from the *Log & Report* pane.
- Each log message is documented similar to how it appears in the RAW format. For more information, see the *Logging and Reporting* chapter in the *FortiOS Handbook*.



This reference contains detailed information for each log type and subtype; however, this reference contains only information gathered at publication and, as a result, not every log message field contains detailed information.

Overview

The log types described in this document report traffic, security, and event log information useful for system administrators when recording, monitoring, and tracing the operation of a FortiGate device running FortiOS. The logs provide information regarding the following:

- Firewall attacks
- Configuration changes
- Successful and unsuccessful system operations

What's new

This section identifies major changes in the Log Reference from version 5.6.0 and later.

FortiOS 5.6.7

There are no major log changes between FortiOS 5.6.6 and 5.6.7.

FortiOS 5.6.6

There are no major log changes between FortiOS 5.6.5 and 5.6.6.

FortiOS 5.6.5

There are no major log changes between FortiOS 5.6.4 and 5.6.5.

FortiOS 5.6.4

There are no major log changes between FortiOS 5.6.3 and 5.6.4.

FortiOS 5.6.3

The `logtime` field has been renamed to `eventtime`.

FortiOS 5.6.2

There are no major log changes between FortiOS 5.6.1 and 5.6.2.

FortiOS 5.6.1

There are no major log changes between FortiOS 5.6.0 and 5.6.1.

FortiOS 5.6.0

DNS

- DNS was added as a new log type with a log type ID of 15.

CEF

- CEF (Common Event Format) is supported when sending logs to remote syslog servers.

Log Types and Subtypes

This section describes the log types, subtypes, and priority levels. It also describes the log field format.

Type

Each log entry contains a Type (type) or category field that indicates its log type and which log file stores the log entry.

Subtype

Each log entry contains a Sub Type (subtype) or subcategory field within a log type, based on the feature associated with the cause of the log entry.

For example:

- In event logs, some log entries have a subtype of user, system, or other subtypes.
- In traffic logs, the subtypes are: local, forward, multicast, and sniffer.

List of log types and subtypes

FortiGate devices can record the following types and subtypes of log entry information:

Type	Description	Subtype
Traffic	Records traffic flow information, such as an HTTP/HTTPS request and its response, if any.	<ul style="list-style-type: none">• Forward• Local• Multicast• Sniffer

Type	Description	Subtype
Event	Records system and administrative events, such as downloading a backup copy of the configuration, or daemon activities.	<ul style="list-style-type: none"> • Compliance-check • Endpoint Control • High Availability • Router • Security-audit • System • User • Virtual Private Network (VPN) • WAD • Wireless
Anomaly	Records intrusion attempts.	<ul style="list-style-type: none"> • Anomaly
App	Records intrusion attempts. Application Control log is output when a signature matches an application pattern.	<ul style="list-style-type: none"> • App-CTRL-All
Antivirus	Records virus attacks.	<ul style="list-style-type: none"> • Analytics • Botnet • Filename (Blocked) • Filetype Executable • Infected • Mime Fragmented • Oversized • Scan Error • Suspicious • Switch Proto
DLP	Records data leak prevention events.	<ul style="list-style-type: none"> • DLP • Document Source
DNS	Records domain name server events.	<ul style="list-style-type: none"> • DNS-query • DNS-response
Email	Records email filter events.	<ul style="list-style-type: none"> • Carrier Endpoint Filter • FTGD Error • Google Gmail • IMAP • MAPI • MMS • MSN Hotmail • POP3 • SMTP • Yahoo Mail

Type	Description	Subtype
GTP	Records GPRS Tunneling Protocol (GTP) traffic for FortiCarrier devices.	<ul style="list-style-type: none"> GTP-All
IPS	Records intrusion prevention events.	<ul style="list-style-type: none"> Malicious URL Signature
VoIP	Records voice over IP events.	<ul style="list-style-type: none"> VoIP
WAF	Records web application firewall information for FortiWeb appliances and virtual appliances	<ul style="list-style-type: none"> Address List Custom Signature HTTP Constraint HTTP Method Signature URL Access
Web Filtering	Records web filter events.	<ul style="list-style-type: none"> ActiveX Filter Applet Filter Command Block Content Cookie Filter FortiGuard Allow FortiGuard Block FortiGuard Error FortiGuard Quota FortiGuard Quota Counting FortiGuard Quota Expired Script Filter URL Filter URL Monitor

FortiOS priority levels

Each log entry contains a Level (level) field that indicates the estimated severity of the event that caused the log entry, such as `level=warning`, and therefore how high a priority it is likely to be. Level (level) associations with the descriptions below are not always uniform. They also may not correspond with your own definitions of how severe each event is. If you require notification when a specific event occurs, either configure SNMP traps or alert email by administrator-defined Severity Level (severity_level) or ID (logid), not by Level (level).

Level (0 is highest)	Name	Description
0	Emergency	The system is unusable or not responding.
1	Alert	Immediate action required. Used in security logs.

Level (0 is highest)	Name	Description
2	Critical	Functionality is affected.
3	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
5	Notification	Information about normal events.
6	Information	General information about system operations. Used in event logs to record configuration changes.

For each location where the FortiGate device can store log files (disk, memory, Syslog or FortiAnalyzer), you can define a severity threshold. FortiOS stores all log messages equal to or exceeding the log severity level selected. For example, if you select Error, FortiOS will store log messages whose log severity level is Error, Critical, Alert, and Emergency.

Log field format

The following table describes the standard format in which each log type is described in this document. For documentation purposes, all log types and subtypes follow this generic table format to present the log entry information.

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16

Log Schema Structure

This section describes the schema of the FortiOS log messages.

Log message fields

Each log message consists of several sections of fields. In the FortiOS GUI, you can view the logs in the *Log & Report* pane, which displays the formatted view. If you want to view logs in raw format, you must download the log and view it in a text editor.

Following is an example of a traffic log message in raw format:

```
date=2017-11-15 time=11:44:16 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1510775056 srcip=10.1.100.155 srcname="pc1"
srcport=40772 srcintf="port12" srcintfrole="undefined" dstip=35.197.51.42
dstname="fortiguard.com" dstport=443 dstintf="port11" dstintfrole="undefined"
poluid="707a0d88-c972-51e7-bbc7-4d421660557b" sessionid=8058 proto=6 action="close"
policyid=1 policytype="policy" policymode="learn" service="HTTPS" dstcountry="United
States" srccountry="Reserved" trandisp="snat" transip=172.16.200.2 transport=40772
appid=40568 app="HTTPS.BROWSER" appcat="Web.Client" apprisk="medium" duration=2
sentbyte=1850 rcvdbyte=39898 sentpkt=25 rcvdpkt=37 utmaction="allow" countapp=1
devtype="Linux PC" osname="Linux" mastersrcmac="a2:e9:00:ec:40:01"
srcmac="a2:e9:00:ec:40:01" srcserver=0 utmref=0-220586
```

The following table provides an example of the log field information in the FortiOS GUI in the detailed view of the *Log & Report* pane and in the downloaded, raw log file.

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
General		
Date (date)	Day, month, and year when the log message was recorded.	date=2017-11-15
Time (time)	Hour clock when the log message was recorded.	time=11:44:16
Duration (duration)	Duration of the session.	duration=2
Session ID (sessionid)	ID for the session.	sessionid=8058
Virtual Domain (vd)	Name of the virtual domain in which the log message was recorded.	vd="vdom1"
NAT Translation (transport)	NAT source port.	transport=40772
Source		

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
IP (srcip)	IP address of the traffic's origin. The source varies by the direction: <ul style="list-style-type: none"> In HTTP requests, this is the web browser or other client. In HTTP responses, this is the physical server. 	srcip=10.1.100.155
NAT IP (transip)	NAT source IP.	transip=172.16.200.2
Source Port (srcport)	Port number of the traffic's origin.	srcport=40772
Country (srccountry)	Name of the source country.	srccountry="Reserved"
Source Interface (srcintf)	Interface name of the traffic's origin.	srcintf="port12"
Source Name (srcname)	Name of the source.	srcname="pcl"
Source Interface Name (srcintfrole)	Name of the source interface.	srcintfrole="undefined"
Device Type (devtype)	Device type of the source.	devtype="Linux PC"
OS Name (osname)	OS of the source.	osname="Linux"
Master Source MAC (mastersrcmac)	The master MAC address for a host that has multiple network interfaces.	mastersrcmac="a2:e9:00:ec:40:01"
Source MAC (srcmac)	MAC address associated with the source IP address.	srcmac="a2:e9:00:ec:40:01"
Source Server (srcserver)	Server of the source.	srcserver=0
Device ID (devid)	Serial number of the device for the traffic's origin.	devid="FGVM02Q105060010"
Destination		
IP (dstip)	Destination IP address for the web.	dstip=35.197.51.42
Port (dstport)	Port number of the traffic's destination.	dstport=443
Country (dstcountry)	Name of the destination country.	dstcountry="United States"
Destination Interface (dstintf)	Interface of the traffic's destination.	dstintf="port11"
Destination Name (dstname)	Name of the destination.	dstname="fortiguard.com"
Destination Interface Name (dstintfrole)	Name of the destination interface.	dstintfrole="undefined"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
Application		
Application Name (app)	Name of the application.	app="HTTPS.BROWSER"
Category (appcat)	Category of the application.	appcat="Web.Client"
Service (service)	Name of the service.	service="HTTPS"
Application ID (appid)	ID of the application.	appid=40568
Application Risk (apprisk)	Risk level of the application.	apprisk="medium"
countapp	Number of App Ctrl logs associated with the session.	countapp=1
Data		
Received bytes (rcvdbyte)	Number of bytes received.	rcvdbyte=39898
Received packets (rcvdpkt)	Number of packets received.	rcvdpkt=37
Sent bytes (sentbyte)	Number of bytes sent.	sentbyte=1850
Sent packets (sentpkt)	Number of packets sent.	sentpkt=25
Action		
Action (action)	Status of the session. Uses following definitions: <ul style="list-style-type: none"> • Deny: blocked by firewall policy • Start: session start log (special option to enable logging at start of a session). This means firewall allowed. • All Others: allowed by Firewall Policy and the status indicates how it was closed. 	action=[deny, accept, start, dns, ip-conn, close, timeout, client-rst, server-rst]
Policy (policyid)	Name of the firewall policy governing the traffic which caused the log message.	policyid=1
Policy UUID (poluuid)	UUID for the firewall policy.	poluuid="707a0d88-c972-51e7-bbc7-4d421660557b"
Policy Type (policytype)		policytype="policy"
Policy Mode (policymode)	Firewall policy mode.	policymode="learn"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
Security		
Level (level)	Security level rating.	level="notice"
Other		
Event Time (eventtime)	Epoch time the log was triggered by FortiGate. If you convert the epoch time to human readable time, it might not match the Date and Time in the header owing to a small delay between the time the log was triggered and recorded. The Log Time field is the same for the same log among all log devices, but the Date and Time might differ.	eventtime=1510775056
Protocol Number (proto)	tcp: The protocol used by web traffic (tcp by default)	proto=6
Type (type)	Log type. See Type on page 32	type="traffic"
Log ID (logid)	Log ID. See Log ID definitions on page 40	logid="00000000013"
Sub Type(subtype)	Subtype of the traffic. See Subtype on page 32 .	subtype="forward"
trandisp	NAT translation type.	trandisp="snat"
UTM Action (utmaction)	Security action performed by UTM.	utmaction="allow"
UTM Reference (utmref)	UTM reference number.	utmref=0-220586



In ICMP UTM logs, the `dstport` field shows the ICMP code as listed in <https://www.iana.org/assignments/icmp-parameters/icmp-parameters.xhtml>. The `srcport` shows the sequence number of the ICMP payload.

Log ID numbers

The ID (logid) is a 10-digit field. It is a unique identifier for that specific log and includes the following information about the log entry.

Log ID number components	Description	Examples
Log Type	Represented by the first two digits of the log ID.	<ul style="list-style-type: none"> Traffic log IDs begin with "00". Event log IDs begin with "01".
Sub Type or Event Type	Represented by the second two digits of the log ID.	<ul style="list-style-type: none"> VPN log subtype is represented with "01" which belongs to the Event log type that is represented with "01". <p>Therefore, all VPN related Event log IDs will begin with the 0101 log ID series.</p>
Message ID	The last six digits of the log ID represent the message ID.	<ul style="list-style-type: none"> An administrator account always has the log ID 0000003401.

The logid field is a number assigned to all permutations of the same message. It classifies a log entry by the nature of the cause of the log message, such as administrator authentication failures or traffic. Other log messages that share the same cause will share the same logid.

Log ID definitions

Following are the definitions for the log type IDs and subtype IDs applicable to FortiOS version 5.2.1 and later.

Log Type IDs	Subtype IDs
traffic: 0	<ul style="list-style-type: none"> forward: 0 local: 1 multicast: 2 sniffer: 4
event: 1	<ul style="list-style-type: none"> system: 0 vpn: 1 user: 2 router: 3 wireless: 4 wad: 5 endpoint: 7 ha: 8 compliance-check: 9 security_audit: 10

Log Type IDs	Subtype IDs
virus: 2	<ul style="list-style-type: none"> • infected: 11 • blocked: 12 • oversized: 13 • scanerror: 62 • suspicious: 0 • analytics: 1 • switchproto: 63 • mimefragmented: 61 • virus_filetype_exe: 3 • botnet: 2
webfilter: 3	<ul style="list-style-type: none"> • content: 14 • urlfilter: 15 • ftgd_blk: 16 • ftgd_allow: 17 • ftgd_err: 18 • url_monitor: 19 • scriptfilter_activex: 35 • scriptfilter_cookie: 36 • scriptfilter_applet: 37 • ftgd_quota_counting: 38 • ftgd_quota_expired: 39 • ftgd_quota: 40 • scriptfilter_other: 41 • webfilter_command_block: 43
ips: 4	<ul style="list-style-type: none"> • signature: 19 • malicious_url: 21
antispam: 5	<ul style="list-style-type: none"> • smtp: 8 • pop3: 9 • imap: 10 • mapi: 11 • endpoint_filter: 47 • mms: 52 • msn: 5 • yahoo: 6 • google: 7 • ftgd_err: 53
anomaly: 7	<ul style="list-style-type: none"> • anomaly: 20
voip: 8	<ul style="list-style-type: none"> • viop: 14
dlp: 9	<ul style="list-style-type: none"> • dlp: 54 • dlp-docsource: 55

Log Type IDs	Subtype IDs
app_ctrl: 10	<ul style="list-style-type: none">• app-ctrl-all: 59
WAF: 12	<ul style="list-style-type: none">• signature: 0• custom_signature: 1• method: 2• constraints: 3• address_list: 4• url_access: 5
GTP: 14	<ul style="list-style-type: none">• all: 0
DNS: 15	<ul style="list-style-type: none">• dns-query: 0• dns-response: 1

FortiGuard Web Filter Categories

The below details the mapping between FortiGuard Web Filter category names and numbers.

Number	Category
0	Unrated
1	Drug abuse
2	Alternative beliefs
3	Hacking
4	Illegal or unethical
5	Discrimination
6	Explicit violence
7	Abortion
8	Other adult materials
9	Advocacy organizations
11	Gambling
12	Extremist groups
13	Nudity and risque
14	Pornography
15	Dating
16	Weapons (sales)
17	Advertising
18	Brokerage and trading
19	Freeware and software downloads
20	Games
23	Web-based email
24	File sharing and storage
25	Streaming media and download
26	Malicious websites

Number	Category
28	Entertainment
29	Arts and culture
30	Education
31	Finance and banking
33	Health and wellness
34	Job search
35	Medicine
36	News and media
37	Social networking
38	Political organizations
39	Reference
40	Global religion
41	Search engines and portals
42	Shopping
43	General organizations
44	Society and lifestyles
46	Sports
47	Travel
48	Personal vehicles
49	Business
50	Information and computer security
51	Government and legal organizations
52	Information technology
53	Armed forces
54	Dynamic content
55	Meaningless content
56	Web hosting
57	Marijuana

Number	Category
58	Folklore
59	Proxy avoidance
61	Phishing
62	Plagiarism
63	Sex education
64	Alcohol
65	Tobacco
66	Lingerie and swimsuit
67	Sports hunting and war games
68	Web chat
69	Instant messaging
70	Newsgroups and message boards
71	Digital postcards
72	Peer-to-peer file sharing
75	Internet radio and TV
76	Internet telephony
77	Child education
78	Real estate
79	Restaurant and dining
80	Personal websites and blogs
81	Secure websites
82	Content servers
83	Child abuse
84	Web-based applications
85	Domain parking
86	Spam URLs
87	Personal privacy
88	Dynamic DNS

Number	Category
89	Auction
90	Newly observed domain
91	Newly registered domain
92	Charitable organizations
93	Remote access
94	Web analytics
95	Online meeting

CEF Support

You can configure FortiOS 5.6.7 to send logs to remote syslog servers in Common Event Format (CEF) by using the `config log syslogd setting` command. For more information, see the *Logging and Reporting* chapter in the *FortiOS Handbook* and the *FortiOS CLI Reference*.

When CEF is enabled, FortiOS sends logs to syslog servers in CEF. This section describes how FortiOS logs support CEF.



You can view logs in CEF on remote syslog servers or FortiAnalyzer, but not in the FortiOS GUI.

FortiOS to CEF log field mapping guidelines

The following CEF format:

```
Date/Time host CEF:Version|Device Vendor|Device Product|Device Version|Signature
ID|Name|Severity| [Extension]
```

Displays as following in FortiOS logs with CEF enabled:

```
"MMM dd HH:mm:ss" "hostname of the fortigate"
CEF:0|Fortinet|Fortigate|version|logid|type:subtype +[eventtype] +[action] +
[status]|reversed level|...
```

The `SignatureId` field in FortiOS logs maps to the `logid` field in CEF and should be last 5 digits of `logid`.

The `Name` field in CEF uses the following formula:

```
type:subtype + [eventtype] + [action] + [status]
```

Following is an example of the header and one key-value pair for extension from the Event VPN log in CEF:

```
#Feb 12 10:31:04 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|37127|event:vpn negotiate
success|3|FTNTFGTlogid=0101037127
```

The `type:subtype` field in FortiOS logs maps to the `cat` field in CEF.

Any fields in FortiOS logs that are unmatched to fields in CEF include the `FTNTFGT` prefix.

Quotes (") are removed from FortiOS logs to support CEF.

Forward slashes (/) in string values as well as the equal sign (=) and backward slashes (\) are escaped in FortiOS logs to support CEF.

CEF priority levels

Following are the CEF priority levels. They are opposite of FortiOS priority levels. See also [FortiOS priority levels on page 34](#).

Level (8 is highest)	Name	Description
8	Emergency	The system is unusable or not responding.
7	Alert	Immediate action required. Used in security logs.
6	Critical	Functionality is affected.
5	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
3	Notification	Information about normal events.
2	Information	General information about system operations. Used in event logs to record configuration changes.
1	Debug	Debug information.

Examples of CEF support

This section includes examples of how the different types of log message support CEF.

Anomaly log support for CEF

Following is an example of an anomaly log on the FortiGate disk:

```
date=2016-02-12 time=14:10:42 logid=0720018433 type=anomaly subtype=anomaly level=alert
vd="vdom1" severity=critical srcip=192.168.1.183 dstip=192.168.70.184 srcintf="port15"
sessionid=0 action=clear_session proto=1 service="icmp/146/81" count=306 attack="icmp_
flood" dstport=20882 icmptype=0x92 icmpcode=0x51 attackid=16777316 profile="DoS-policy1"
ref="http://www.fortinet.com/ids/VID16777316"
msg="anomaly: icmp_flood, 34 > threshold 25, repeats 306 times" crscore=50 crlevel=critical
```

Following is an example of an anomaly log sent in CEF format to a syslog server:

```
Feb 12 14:10:42 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|18433|anomaly:anomaly clear_
session|7|FTNTFGTlogid=0720018433 cat=anomaly:anomaly FTNTFGTsubtype=anomaly
FTNTFGTlevel=alert FTNTFGTvd=vdom1 FTNTFGTseverity=critical src=192 168 1 183 dst=192 168
70 184 deviceInboundInterface=port15 externalId=0 act=clear_session proto=1
app=icmp/146/81 cnt=306 FTNTFGTattack=icmp_flood dpt=20882 FTNTFGTicmptype=0x92
FTNTFGTicmpcode=0x51 FTNTFGTattackid=16777316 FTNTFGTprofile=DoS-policy1
cs2=http://www.fortinet.com/ids/VID16777316 cs2Label=Reference msg=anomaly: icmp_flood,
34 > threshold 25, repeats 306 times FTNTFGTcrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
count	cnt

Antivirus log support for CEF

Following is an example of an antivirus log on the FortiGate disk:

```
date=2016-02-12 time=11:11:25 logid=0211008192 type=utm subtype=virus eventtype=infected
level=warning vd="vdom1" msg="File is infected." action=blocked service=HTTP
sessionid=56633 srcip=192.168.1.183 dstip=192.168.70.184 srcport=45719 dstport=80
srcintf="port15" dstintf="port19" proto=6 direction=incoming filename="eicar.com"
checksum="1dd02bdb" quarskip=No-skip virus="EICAR_TEST_FILE" dtype="Virus"
ref="http://www.fortinet.com/ve?vn=EICAR_TEST_FILE" virusid=2172
url="http://192.168.70.184/eicar.com" profile="default" user="" agent="Wget/1.10.2"
analyticsscksum="131f95c51cc819465fa1797f6ccacf9d494aaaff46fa3eac73ae63ffbfdf8267"
analyticsssubmit=false crscore=50 crlevel=critical
```

Following is an example of an antivirus log sent in CEF format to a syslog server:

```
Feb 12 11:11:25 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|08192|utm:virus infected
blocked|4|FTNTFGTlogid=0211008192 cat=utm:virus FTNTFGTsubtype=virus FTNTFGTeventtype=infected
FTNTFGTlevel=warning FTNTFGTvd=vdom1 msg=File is infected act=blocked app=HTTP
externalId=56633 src=192.168.1.183 dst=192.168.70.184 spt=45719 dpt=80
deviceInboundInterface=port15 deviceOutboundInterface=port19 proto=6 deviceDirection=0
fname=eicar.com FTNTFGTchecksum=1dd02bdb FTNTFGTquarskip=No-skip cs1=EICAR_TEST_FILE
cs1Label=Virus FTNTFGTdtype=Virus cs2=http://www.fortinet.com/ve?vn=EICAR_TEST_FILE
cs2Label=Reference FTNTFGTvirusid=2172 request=http://192.168.70.184/eicar.com
FTNTFGTprofile=default duser= requestClientApplication=Wget/1 10 2
FTNTFGTanalyticsscksum=131f95c51cc819465fa1797f6ccacf9d494aaaff46fa3eac73ae63ffbfdf8267
FTNTFGTanalyticsssubmit=false FTNTFGTcrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
direction	deviceDirection (inbound/outbound mapping to 0/1)
filename	fname
virus	cs1=xxx cs1Label=Virus
ref	cs2=xxx cs2Label=Reference
url	request
agent	requestClientApplication

DLP log support for CEF

Following is an example of a DLP log on the FortiGate disk:

```
date=2016-02-12 time=14:16:32 logid=0954024576 type=utm subtype=dlp eventtype=dlp
level=warning vd="vdom1" filteridx=2 filtertype=ssn filtercat=file severity=medium
sessionid=65177 epoch=2015044633 eventid=0 user="" srcip=192.168.1.183 srcport=36171
srcintf="port15" dstip=192.168.70.184 dstport=80 dstintf="port19" proto=6 service=HTTP
filetype=unknown sentbyte=151 rcvdbyte=90170 direction=incoming action=block
```

```
hostname="192.168.70.184" url="/dlp/ssn/ssn-docx-pdf-valid.tar" agent="Wget/1.10.2"
filename="ssn-docx-pdf-valid.tar" filesize=89831 profile="SSN"
```

Following is an example of a DLP log sent in CEF format to a syslog server:

```
Feb 12 14:16:32 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|24576|utm:dlp dlp
block|4|FTNTFGTlogid=0954024576 cat=utm:dlp FTNTFGTsubtype=dlp FTNTFGTeventtype=dlp
FTNTFGTlevel=warning FTNTFGTvd=vdom1 FTNTFGTfilteridx=2 cs1=ssn cs1Label=Filter Type
FTNTFGTfiltercat=file FTNTFGTseverity=medium externalId=65177 FTNTFGTepoch=2015044633
FTNTFGTeventid=0 duser= src=192.168.1.183 spt=36171 deviceInboundInterface=port15
dst=192.168.70.184 dpt=80 deviceOutboundInterface=port19 proto=6 app=HTTP
FTNTFGTfiletype=unknown out=151 in=90170 deviceDirection=0 act=block dhost=192.168.70.184
request=/dlp/ssn/ssn-docx-pdf-valid.tar requestClientApplication=Wget/1.10.2 fname=ssn-
docx-pdf-valid.tar fsize=89831 FTNTFGTprofile=SSN
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
filtertype	cs1=xxx cs1Label=Filter Type
filesize	fsize

Email Spamfilter log support for CEF

Following is an example of an email spamfilter log on the FortiGate disk:

```
date=2016-02-12 time=14:01:12 logid=0509020482 type=utm subtype=emailfilter eventtype=pop3
level=notice vd="vdom1" sessionid=64465 user="" srcip=192.168.1.183 srcport=33244
srcintf="port15" dstip=192.168.70.184 dstport=110 dstintf="port19" proto=6 service=POP3
profile="default" action=tagged from="jj@fortinet.com" to="mm@fortinet.com"
recipient="testpc3" sentbyte=27 rcvdbyte=1592 direction=incoming msg="email is reported
as spam by ASE" subject="[SMTP]: MyTest" attachment=no
```

Following is an example of an email spamfilter log sent in CEF format to a syslog server:

```
Feb 12 14:01:12 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|20482|utm:emailfilter pop3
tagged|3|FTNTFGTlogid=0509020482 cat=utm:emailfilter FTNTFGTsubtype=emailfilter
FTNTFGTeventtype=pop3 FTNTFGTlevel=notice FTNTFGTvd=vdom1 externalId=64465 duser=
src=192.168.1.183 spt=33244 deviceInboundInterface=port15 dst=192.168.70.184 dpt=110
deviceOutboundInterface=port19 proto=6 app=POP3 FTNTFGTprofile=default act=tagged
suser=jj@fortinet.com duser=mm@fortinet.com FTNTFGTrecipient=testpc3 out=27 in=1592
deviceDirection=0 msg=email is reported as spam by ASE FTNTFGTsubject=[SMTP]: MyTest
FTNTFGTattachment=no
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
from	suser
to	duser

Webfilter log support for CEF

Following is an example of a webfilter log on the FortiGate disk:

```
date=2016-02-12 time=11:40:47 logid=0316013056 type=utm subtype=webfilter eventtype=ftgd_blk
level=warning vd="vdom1" sessionid=58014 user="" srcip=192.168.1.183 srcport=48676
srcintf="port15" dstip=202.46.41.172 dstport=80 dstintf="port19" proto=6 service=HTTP
hostname="www.youku.com" profile="default" action=blocked reqtype=direct url="/"
sentbyte=120 rcvdbyte=948 direction=outgoing msg="URL belongs to a denied category in
policy" method=domain cat=25 catdesc="Streaming Media and Download" crscore=30
crlevel=high
```

Following is an example of a webfilter log sent in CEF format to a syslog server:

```
Feb 12 11:40:47 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|13056|utm:webfilter ftgd_blk
blocked|4|FTNTFGTlogid=0316013056 cat=utm:webfilter FTNTFGTsubtype=webfilter
FTNTFGTeventtype=ftgd_blk FTNTFGTlevel=warning FTNTFGTvd=vdom1 externalId=58014 duser=
src=192.168.1.183 spt=48676 deviceInboundInterface=port15 dst=202.46.41.172 dpt=80
deviceOutboundInterface=port19 proto=6 app=HTTP dhost=www.youku.com
FTNTFGTprofile=default act=blocked FTNTFGTreqtype=direct request=/ out=120 in=948
deviceDirection=1 msg=URL belongs to a denied category in policy FTNTFGTmethod=domain
FTNTFGTcat=25 requestContext=Streaming Media and Download FTNTFGTcrscore=30
FTNTFGTcrlevel=high
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
hostname	dhost
catdesc	requestContext

Traffic log support for CEF

Following is an example of a traffic log on the FortiGate disk:

```
date=2016-02-12 time=11:11:29 logid=0000000013 type=traffic subtype=forward level=notice
vd=vdom1 srcip=192.168.1.183 srcname="192.168.1.183" srcport=45719 srcintf="port15"
dstip=192.168.70.184 dstname="192.168.70.184" dstport=80 dstintf="port19"
poluid=61c4243a-34ba-51e5-c32a-3859389a5162 sessionid=56633 proto=6 action=close
policyid=10 dstcountry="Reserved" srccountry="Reserved" trandisp=snat
transip=192.168.70.214 transport=45719 service="HTTP" appid=38783 app="Wget.Like"
appcat="General.Interest" apprisk=low applist="default" appact=detected duration=7
sentbyte=398 rcvdbyte=1605 sentpkt=5 rcvpkt=5 utmaction=block countav=1 countapp=1
crscore=50 craction=2 utmref=65502-0
```

Following is an example of an event log sent in CEF format to a syslog server:

```
Feb 12 11:11:30 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|00013|traffic:forward
close|3|FTNTFGTlogid=0000000013 cat=traffic:forward FTNTFGTsubtype=forward
FTNTFGTlevel=notice FTNTFGTvd=vdom1 src=192.168.1.183 shost=192.168.1.183 spt=45719
deviceInboundInterface=port15 dst=192.168.70.184 dhost=192.168.70.184 dpt=80
deviceOutboundInterface=port19 FTNTFGTpoluid=61c4243a-34ba-51e5-c32a-3859389a5162
externalId=56633 proto=6 act=close cs5=10 cs5Label=Policy Id FTNTFGTdstcountry=Reserved
FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat sourceTranslatedAddress=192.168.70.214
sourceTranslatedPort=45719 app=HTTP FTNTFGTappid=38783 FTNTFGTapp=Wget.Like
FTNTFGTappcat=General.Interest FTNTFGTapprisk=low FTNTFGTapplist=default
FTNTFGTappact=detected cn1=7 cn1Label=Duration out=398 in=1605 cn2=5 cn2Label=Packets
```

```
Sent cn3=5 cn3Label=Packets Received FTNTFGTutmaction=block FTNTFGTcountav=1
FTNTFGTcountapp=1 FTNTFGTcrscore=50 FTNTFGTcraction=2
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
type: subtype	cat
srcip	src
srcport	spt
srcintf	deviceInboundInterface
dstip	dst
dstname	dhost
dstport	dpt
dstintf	deviceOutboundInterface
sessionid	externalID
proto	proto
action	act
policyid	cs5=xx cs5Label=Policy Id
transip	sourceTranslatedAddress
transport	sourceTranslatedPort
service	app
duration	cn1=xx cn1Label=Duration
sentbyte	out
rcvdbyte	in
sentpkt	cn2=xx cn2Label=Packets Sent
rcvdpkt	cn3=xx cn3Label=Packets Received

Event log system subtype support for CEF

Following is an example of a system subtype log on the FortiGate disk:

```
date=2016-02-12 time=10:48:12 logid=0100032001 type=event subtype=system level=information
vd="vdom1" logdesc="Admin login successful" sn=1455302892 user="admin" ui=console
action=login status=success reason=none profile="super_admin" msg="Administrator admin
logged in successfully from console"
```

Following is an example of a system subtype log sent in CEF format to a syslog server:

```
Feb 12 10:48:12 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|32001|event:system login
success|2|FTNTFGTlogid=0100032001 cat=event:system FTNTFGTsubtype=system
```

```
FTNTFGTlevel=information FTNTFGTvd=vdom1 FTNTFGTlogdesc=Admin login successful  
FTNTFGTsn=1455302892 duser=admin sproc=console act=login outcome=success reason=none  
FTNTFGTprofile=super_admin msg=Administrator admin logged in successfully from console
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
msg	msg
cookies	requestCookies
user	duser
group	cs6
status	outcome
role	sourceServiceName
ui	sproc
reason	reason

Log Messages

The following sections list the FortiOS 5.6.7 log messages by log ID number.

Anomaly

18432 - LOGID_ATTCK_ANOMALY_TCP_UDP

Message ID: 18432

Message Description: LOGID_ATTCK_ANOMALY_TCP_UDP

Message Meaning: Attack detected by UCP/TCP anomaly

Type: Anomaly

Category: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32

18433 - LOGID_ATTCK_ANOMALY_ICMP

Message ID: 18433

Message Description: LOGID_ATTCK_ANOMALY_ICMP

Message Meaning: Attack detected by ICMP anomaly

Type: Anomaly

Category: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
icmpcode	ICMP code	string	6
icmpid	ICMP ID	string	8
icmptype	ICMP Type	string	6
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
severity	Severity	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32

18434 - LOGID_ATTCK_ANOMALY_OTHERS

Message ID: 18434

Message Description: LOGID_ATTCK_ANOMALY_OTHERS

Message Meaning: Attack detected by other anomaly

Type: Anomaly

Category: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	
service	Name of Service	string	36
sessionid	Session ID	uint32	10
severity	Severity	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32

App

28672 - LOGID_APP_CTRL_IM_BASIC

Message ID: 28672

Message Description: LOGID_APP_CTRL_IM_BASIC

Message Meaning: Application control IM-basic

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS

Message ID: 28673

Message Description: LOGID_APP_CTRL_IM_BASIC_WITH_STATUS

Message Meaning: Application control IM

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT

Message ID: 28674

Message Description: LOGID_APP_CTRL_IM_BASIC_WITH_COUNT

Message Meaning: Application control IM (chat message count)

Type: App

Category: APP-CTRL-ALL**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28675 - LOGID_APP_CTRL_IM_FILE

Message ID: 28675

Message Description: LOGID_APP_CTRL_IM_FILE

Message Meaning: Application control IM (file)

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28676 - LOGID_APP_CTRL_IM_CHAT

Message ID: 28676

Message Description: LOGID_APP_CTRL_IM_CHAT

Message Meaning: Application control IM (chat)

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64

Log Field Name	Description	Data Type	Length
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK

Message ID: 28677

Message Description: LOGID_APP_CTRL_IM_CHAT_BLOCK

Message Meaning: Application control IM (chat blocked)

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28678 - LOGID_APP_CTRL_IM_BLOCK

Message ID: 28678

Message Description: LOGID_APP_CTRL_IM_BLOCK

Message Meaning: Application control IM (blocked)

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28704 - LOGID_APP_CTRL_IPS_PASS

Message ID: 28704

Message Description: LOGID_APP_CTRL_IPS_PASS

Message Meaning: Application control (IPS) (pass)

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
appid	Application ID	uint32	10
applist	Application Control profile name	string	64
apprisk	Application risk level	string	16
ccertissuer		string	64
cloudaction	Action performed by cloud application	string	32
clouduser	User login ID detected by the Deep Application Control feature	string	256
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
incidentserialno		uint32	10
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
scertcname		string	64
scertissuer		string	64
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

28705 - LOGID_APP_CTRL_IPS_BLOCK

Message ID: 28705

Message Description: LOGID_APP_CTRL_IPS_BLOCK

Message Meaning: Application control (IPS) (block)

Type: App

Category: APP-CTRL-ALL

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
appid	Application ID	uint32	10
applist	Application Control profile name	string	64
apprisk	Application risk level	string	16
ccertissuer		string	64
cloudaction	Action performed by cloud application	string	32
clouduser	User login ID detected by the Deep Application Control feature	string	256
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
incidentserialno		uint32	10
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
scertcname		string	64
scertissuer		string	64
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

28706 - LOGID_APP_CTRL_IPS_RESET

Message ID: 28706

Message Description: LOGID_APP_CTRL_IPS_RESET

Message Meaning: Application control (IPS) (reset)

Type: App

Category: APP-CTRL-ALL

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
appid	Application ID	uint32	10
applist	Application Control profile name	string	64
apprisk	Application risk level	string	16
ccertissuer		string	64
cloudaction	Action performed by cloud application	string	32
clouduser	User login ID detected by the Deep Application Control feature	string	256
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
incidentserialno		uint32	10
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
scertcname		string	64
scertissuer		string	64
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

28720 - LOGID_APP_CTRL_SSH_PASS

Message ID: 28720

Message Description: LOGID_APP_CTRL_SSH_PASS

Message Meaning: Application control IM (SSH) (pass)

Type: App

Category: APP-CTRL-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

28721 - LOGID_APP_CTRL_SSH_BLOCK

Message ID: 28721

Message Description: LOGID_APP_CTRL_SSH_BLOCK

Message Meaning: Application control IM (SSH) (block)

Type: App

Category: APP-CTRL-ALL

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by App Control	string	16
app	Application name	string	96
appcat	Application category name	string	64
applist	Application Control profile name	string	64
date	Date	string	10
direction	Direction of the packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	App Control Event Type	string	32
fctuid		string	32
group	User group name	string	64
level	Log level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profiletype	Profile Type	string	36
proto	Protocol number	uint8	3
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

AV

8192 - MESGID_INFECT_WARNING

Message ID: 8192

Message Description: MESGID_INFECT_WARNING

Message Meaning: Infected file detected by the FortiGate unit and blocked

Type: AV

Category: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8193 - MESGID_INFECT_NOTIF

Message ID: 8193

Message Description: MESGID_INFECT_NOTIF

Message Meaning: Infected file detected by the FortiGate unit and it passed

Type: AV

Category: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8194 - MESGID_INFECT_MIME_WARNING

Message ID: 8194

Message Description: MESGID_INFECT_MIME_WARNING

Message Meaning: MIME header detected to have a virus and blocked

Type: AV

Category: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8195 - MESGID_INFECT_MIME_NOTIF

Message ID: 8195

Message Description: MESGID_INFECT_MIME_NOTIF

Message Meaning: MIME header infected and passed

Type: AV

Category: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8200 - MESGID_MIME_FILETYPE_EXE_WARNING

Message ID: 8200

Message Description: MESGID_MIME_FILETYPE_EXE_WARNING

Message Meaning: File is an executable (warning)

Type: AV

Category: FILETYPE-EXECUTABLE

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	11
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
checksum		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10

8201 - MESGID_MIME_FILETYPE_EXE_NOTIF

Message ID: 8201

Message Description: MESGID_MIME_FILETYPE_EXE_NOTIF

Message Meaning: File is an executable (notice)

Type: AV

Category: FILETYPE-EXECUTABLE

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	11
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
checksum		string	16
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10

8448 - MESGID_BLOCK_WARNING

Message ID: 8448

Message Description: MESGID_BLOCK_WARNING

Message Meaning: FortiGate unit blocked a file because it contains a virus

Type: AV

Category: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8449 - MESGID_BLOCK_NOTIF

Message ID: 8449

Message Description: MESGID_BLOCK_NOTIF

Message Meaning: FortiGate unit blocked a file because it contains a virus

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8450 - MESGID_BLOCK_MIME_WARNING

Message ID: 8450

Message Description: MESGID_BLOCK_MIME_WARNING

Message Meaning: FortiGate unit blocked a file because it contains a virus (MIME)

Type: AV

Category: MIMEFRAGMENTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8451 - MESGID_BLOCK_MIME_NOTIF

Message ID: 8451

Message Description: MESGID_BLOCK_MIME_NOTIF

Message Meaning: FortiGate unit blocked a file because it contains a virus (MIME)

Type: AV

Category: MIMEFRAGMENTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8452 - MESGID_BLOCK_COMMAND

Message ID: 8452

Message Description: MESGID_BLOCK_COMMAND

Message Meaning: FortiGate unit blocked a virus command

Type: AV

Category: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
command	FTP Command info	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8453 - MESGID_INTERCEPT

Message ID: 8453

Message Description: MESGID_INTERCEPT

Message Meaning: FortiGate unit intercepted a file containing a virus

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8454 - MESGID_INTERCEPT_MIME

Message ID: 8454

Message Description: MESGID_INTERCEPT_MIME

Message Meaning: FortiGate unit intercepted a file (MIME)

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8455 - MESGID_EXEMPT

Message ID: 8455

Message Description: MESGID_EXEMPT

Message Meaning: File exempted

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8456 - MESGID_EXEMPT_MIME

Message ID: 8456

Message Description: MESGID_EXEMPT_MIME

Message Meaning: File exempted

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12

Log Field Name	Description	Data Type	Length
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8457 - MESGID_MMS_CHECKSUM

Message ID: 8457

Message Description: MESGID_MMS_CHECKSUM

Message Meaning: MMS content checksum blocked an infected file

Type: AV

Category: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8458 - MESGID_MMS_CHECKSUM_NOTIF

Message ID: 8458

Message Description: MESGID_MMS_CHECKSUM_NOTIF

Message Meaning: MMS content checksum was matched

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8704 - MESGID_OVERSIZE_WARNING

Message ID: 8704

Message Description: MESGID_OVERSIZE_WARNING

Message Meaning: Defined file size limit was exceeded

Type: AV

Category: OVERSIZE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8705 - MESGID_OVERSIZE_NOTIF

Message ID: 8705

Message Description: MESGID_OVERSIZE_NOTIF

Message Meaning: File size limit was exceeded

Type: AV

Category: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8706 - MESGID_OVERSIZE_MIME_WARNING

Message ID: 8706

Message Description: MESGID_OVERSIZE_MIME_WARNING

Message Meaning: File (MIME) size exceed the defined size limit

Type: AV

Category: OVERSIZE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8707 - MESGID_OVERSIZE_MIME_NOTIF

Message ID: 8707

Message Description: MESGID_OVERSIZE_MIME_NOTIF

Message Meaning: File (MIME) size exceed the defined size limit

Type: AV

Category: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8720 - MESGID_SWITCH_PROTO_WARNING

Message ID: 8720

Message Description: MESGID_SWITCH_PROTO_WARNING

Message Meaning: Switching protocols request (warning)

Type: AV

Category: SWITCHPROTO

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8721 - MESGID_SWITCH_PROTO_NOTIF

Message ID: 8721

Message Description: MESGID_SWITCH_PROTO_NOTIF

Message Meaning: Switching protocols request (notice)

Type: AV

Category: SWITCHPROTO

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

8960 - MESGID_SCAN_UNCOMPSizeLIMIT_WARNING

Message ID: 8960

Message Description: MESGID_SCAN_UNCOMPSizeLIMIT_WARNING

Message Meaning: File reached the uncompressed nested limit

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8961 - MESGID_SCAN_UNCOMPSizeLIMIT_NOTIF

Message ID: 8961

Message Description: MESGID_SCAN_UNCOMPSizeLIMIT_NOTIF

Message Meaning: File reached the uncompressed size limit

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8962 - MESGID_SCAN_ARCHIVE_ENCRYPTED_WARNING

Message ID: 8962

Message Description: MESGID_SCAN_ARCHIVE_ENCRYPTED_WARNING

Message Meaning: Archived file is corrupted

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8963 - MESGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF

Message ID: 8963

Message Description: MESGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF

Message Meaning: Archived file is encrypted

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8964 - MESGID_SCAN_ARCHIVE_CORRUPTED_WARNING

Message ID: 8964

Message Description: MESGID_SCAN_ARCHIVE_CORRUPTED_WARNING

Message Meaning: Corrupted archive (warning)

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8965 - MESGID_SCAN_ARCHIVE_CORRUPTED_NOTIF

Message ID: 8965

Message Description: MESGID_SCAN_ARCHIVE_CORRUPTED_NOTIF

Message Meaning: Corrupted archive (notice)

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8966 - MESGID_SCAN_ARCHIVE_MULTIPART_WARNING

Message ID: 8966

Message Description: MESGID_SCAN_ARCHIVE_MULTIPART_WARNING

Message Meaning: File is a multipart archive or contains multiple files within the archive

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8967 - MESGID_SCAN_ARCHIVE_MULTIPART_NOTIF

Message ID: 8967

Message Description: MESGID_SCAN_ARCHIVE_MULTIPART_NOTIF

Message Meaning: File is a multipart archive or contains multiple files within the archive

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8968 - MESGID_SCAN_ARCHIVE_NESTED_WARNING

Message ID: 8968

Message Description: MESGID_SCAN_ARCHIVE_NESTED_WARNING

Message Meaning: File is a nested archived file

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8969 - MESGID_SCAN_ARCHIVE_NESTED_NOTIF

Message ID: 8969

Message Description: MESGID_SCAN_ARCHIVE_NESTED_NOTIF

Message Meaning: File is an archived type unhandled

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8970 - MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING

Message ID: 8970

Message Description: MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING

Message Meaning: Archived file is oversized

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8971 - MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF

Message ID: 8971

Message Description: MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF

Message Meaning: Archived file is oversized

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8972 - MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING

Message ID: 8972

Message Description: MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING

Message Meaning: Unhandled archive (warning)

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8973 - MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF

Message ID: 8973

Message Description: MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF

Message Meaning: Unhandled archive (notice)

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

8974 - MESGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR

Message ID: 8974

Message Description: MESGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR

Message Meaning: AV Engine load failed

Type: AV

Category: SCANERROR

Severity: Error

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9233 - MESGID_ANALYTICS_SUBMITTED

Message ID: 9233

Message Description: MESGID_ANALYTICS_SUBMITTED

Message Meaning: File submitted to Sandbox

Type: AV

Category: ANALYTICS

Severity: Information

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9234 - MESGID_ANALYTICS_INFECT_WARNING

Message ID: 9234

Message Description: MESGID_ANALYTICS_INFECT_WARNING

Message Meaning: File reported infected by FortiSandbox (warning)

Type: AV

Category: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9235 - MESGID_ANALYTICS_INFECT_NOTIF

Message ID: 9235

Message Description: MESGID_ANALYTICS_INFECT_NOTIF

Message Meaning: File reported infected by FortiSandbox (notice)

Type: AV

Category: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9236 - MESGID_ANALYTICS_INFECT_MIME_WARNING

Message ID: 9236

Message Description: MESGID_ANALYTICS_INFECT_MIME_WARNING

Message Meaning: File reported infected by FortiSandbox (warning)

Type: AV

Category: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10

Log Field Name	Description	Data Type	Length
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9237 - MESGID_ANALYTICS_INFECT_MIME_NOTIF

Message ID: 9237

Message Description: MESGID_ANALYTICS_INFECT_MIME_NOTIF

Message Meaning: File reported infected by FortiSandbox (notice)

Type: AV

Category: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512

Log Field Name	Description	Data Type	Length
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9238 - MESGID_ANALYTICS_FSA_RESULT

Message ID: 9238

Message Description: MESGID_ANALYTICS_FSA_RESULT

Message Meaning: File verdict returned from FortiSandbox

Type: AV

Category: ANALYTICS

Severity: Notice

Log Field Name	Description	Data Type	Length
analyticscksum	The checksum of the file submitted for analytics	string	64
date	Date	string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
fsaverdict		string	32
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
service	Proxy service which scanned this traffic	string	5
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
vd	VDOM name	string	32

9248 - MESGID_BOTNET_WARNING

Message ID: 9248

Message Description: MESGID_BOTNET_WARNING

Message Meaning: Botnet C&C Communication (warning)

Type: AV

Category: BOTNET

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

9249 - MESGID_BOTNET_NOTIF

Message ID: 9249

Message Description: MESGID_BOTNET_NOTIF

Message Meaning: Botnet C&C Communication (notice)

Type: AV

Category: BOTNET

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
checksum	The checksum of the scanned file	string	16
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10

DLP

24576 - LOG_ID_DLP_WARN

Message ID: 24576

Message Description: LOG_ID_DLP_WARN

Message Meaning: Data leak detected by specified DLP sensor rule

Type: DLP

Category: DLP

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
date	Date	string	10
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	128
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

24577 - LOG_ID_DLP_NOTIF

Message ID: 24577

Message Description: LOG_ID_DLP_NOTIF

Message Meaning: Data leak detected by specified DLP sensor rule

Type: DLP**Category:** DLP**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
date	Date	string	10
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	128
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

24578 - LOG_ID_DLP_DOC_SOURCE

Message ID: 24578

Message Description: LOG_ID_DLP_DOC_SOURCE

Message Meaning: DLP fingerprint document source notice

Type: DLP

Category: DLP

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
vd	Virtual domain name	string	32

24579 - LOG_ID_DLP_DOC_SOURCE_ERROR

Message ID: 24579

Message Description: LOG_ID_DLP_DOC_SOURCE_ERROR

Message Meaning: DLP fingerprint document source error

Type: DLP

Category: DLP

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
dlpextra	DLP extra information	string	256
docsource	DLP fingerprint document source	string	515
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
sensitivity	Sensitivity for document fingerprint	string	36
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
vd	Virtual domain name	string	32

DNS

54000 - LOG_ID_DNS_QUERY

Message ID: 54000

Message Description: LOG_ID_DNS_QUERY

Message Meaning: DNS query message

Type: DNS

Category: DNS-QUERY

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54200 - LOG_ID_DNS_RESOLV_ERROR

Message ID: 54200

Message Description: LOG_ID_DNS_RESOLV_ERROR

Message Meaning: DNS resolution error message

Type: DNS

Category: DNS-RESPONSE

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54400 - LOG_ID_DNS_URL_FILTER_BLOCK

Message ID: 54400

Message Description: LOG_ID_DNS_URL_FILTER_BLOCK

Message Meaning: Domain blocked because it is in the domain-filter list

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54401 - LOG_ID_DNS_URL_FILTER_ALLOW

Message ID: 54401

Message Description: LOG_ID_DNS_URL_FILTER_ALLOW

Message Meaning: Domain allowed because it is in the domain-filter list

Type: DNS

Category: DNS-RESPONSE

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
date	Date	string	10
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54600 - LOG_ID_DNS_BOTNET_IP

Message ID: 54600

Message Description: LOG_ID_DNS_BOTNET_IP

Message Meaning: Domain blocked by DNS botnet C&C (IP)

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54601 - LOG_ID_DNS_BOTNET_DOMAIN

Message ID: 54601

Message Description: LOG_ID_DNS_BOTNET_DOMAIN

Message Meaning: Domain blocked by DNS botnet C&C (Domain)

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54800 - LOG_ID_DNS_FTGD_WARNING

Message ID: 54800

Message Description: LOG_ID_DNS_FTGD_WARNING

Message Meaning: FortiGuard rating error warning

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54801 - LOG_ID_DNS_FTGD_ERROR

Message ID: 54801

Message Description: LOG_ID_DNS_FTGD_ERROR

Message Meaning: FortiGuard rating error occurred

Type: DNS

Category: DNS-RESPONSE

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16

Log Field Name	Description	Data Type	Length
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54802 - LOG_ID_DNS_FTGD_CAT_ALLOW

Message ID: 54802

Message Description: LOG_ID_DNS_FTGD_CAT_ALLOW

Message Meaning: Domain is monitored

Type: DNS

Category: DNS-RESPONSE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54803 - LOG_ID_DNS_FTGD_CAT_BLOCK

Message ID: 54803

Message Description: LOG_ID_DNS_FTGD_CAT_BLOCK

Message Meaning: Domain belongs to a denied category in policy

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrold		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
exchange	Mail Exchanges from DNS response answer section	string	256
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrold		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

Email

20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF

Message ID: 20480

Message Description: LOGID_ANTISPAM_EMAIL_SMTP_NOTIF

Message Meaning: SMTP warning

Type: Email

Category: SMTP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF

Message ID: 20481

Message Description: LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF

Message Meaning: SMTP warning

Type: Email

Category: SMTP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF

Message ID: 20482

Message Description: LOGID_ANTISPAM_EMAIL_POP3_NOTIF

Message Meaning: POP3 warning

Type: Email

Category: POP3

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF

Message ID: 20483

Message Description: LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF

Message Meaning: POP3 notice

Type: Email

Category: POP3

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF

Message ID: 20484

Message Description: LOGID_ANTISPAM_EMAIL_IMAP_NOTIF

Message Meaning: IMAP notice

Type: Email

Category: IMAP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING

Message ID: 20485

Message Description: LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING

Message Meaning: Endpoint filter warning

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguadresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF

Message ID: 20486

Message Description: LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF

Message Meaning: Endpoint filter notice

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32

20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING

Message ID: 20487

Message Description: LOGID_ANTISPAM_ENDPOINT_MM7_WARNING

Message Meaning: MM7 warning

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF

Message ID: 20488

Message Description: LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF

Message Meaning: MM7 notice

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING

Message ID: 20489

Message Description: LOGID_ANTISPAM_ENDPOINT_MM1_WARNING

Message Meaning: MM1 warning

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF

Message ID: 20490

Message Description: LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF

Message Meaning: MM1 notice

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF

Message ID: 20491

Message Description: LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF

Message Meaning: IMAP banned word notice

Type: Email

Category: IMAP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING

Message ID: 20492

Message Description: LOGID_ANTISPAM_MM1_FLOOD_WARNING

Message Meaning: MM1 flood detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF

Message ID: 20493

Message Description: LOGID_ANTISPAM_MM1_FLOOD_NOTIF

Message Meaning: MM1 flood detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguareesp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING

Message ID: 20494

Message Description: LOGID_ANTISPAM_MM4_FLOOD_WARNING

Message Meaning: MM4 flood detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF

Message ID: 20495

Message Description: LOGID_ANTISPAM_MM4_FLOOD_NOTIF

Message Meaning: MM4 flood detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING

Message ID: 20496

Message Description: LOGID_ANTISPAM_MM1_DUPE_WARNING

Message Meaning: MM1 duplicate detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguadresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF

Message ID: 20497

Message Description: LOGID_ANTISPAM_MM1_DUPE_NOTIF

Message Meaning: MM1 duplicate detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING

Message ID: 20498

Message Description: LOGID_ANTISPAM_MM4_DUPE_WARNING

Message Meaning: MM4 duplicate detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF

Message ID: 20499

Message Description: LOGID_ANTISPAM_MM4_DUPE_NOTIF

Message Meaning: MM4 duplicate detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32

20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF

Message ID: 20500

Message Description: LOGID_ANTISPAM_EMAIL_MSN_NOTIF

Message Meaning: MSN Hotmail email message

Type: Email

Category: MSN-HOTMAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF

Message ID: 20501

Message Description: LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF

Message Meaning: Yahoo! email message

Type: Email

Category: YAHOO-MAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF

Message ID: 20502

Message Description: LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF

Message Meaning: Gmail email message

Type: Email

Category: GMAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF

Message ID: 20503

Message Description: LOGID_EMAIL_SMTP_GENERAL_NOTIF

Message Meaning: SMTP warning

Type: Email

Category: SMTP

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF

Message ID: 20504

Message Description: LOGID_EMAIL_POP3_GENERAL_NOTIF

Message Meaning: POP3 warning

Type: Email

Category: POP3

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF

Message ID: 20505

Message Description: LOGID_EMAIL_IMAP_GENERAL_NOTIF

Message Meaning: IMAP notice

Type: Email

Category: IMAP

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF

Message ID: 20506

Message Description: LOGID_EMAIL_MAPI_GENERAL_NOTIF

Message Meaning: MAPI notice

Type: Email

Category: MAPI

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguareesp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF

Message ID: 20507

Message Description: LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF

Message Meaning: MAPI banned word notice

Type: Email

Category: MAPI

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF

Message ID: 20508

Message Description: LOGID_ANTISPAM_EMAIL_MAPI_NOTIF

Message Meaning: MAPI email message

Type: Email

Category: MAPI

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

20509 - LOGID_ANTISPAM_FTGD_ERR

Message ID: 20509

Message Description: LOGID_ANTISPAM_FTGD_ERR

Message Meaning: FortiGuard error message

Type: Email

Category: MAPI

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
attachment	The flag for email attachement	string	3
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	
date	Date	string	10
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

Event

20002 - LOG_ID_DOMAIN_UNRESOLVABLE

Message ID: 20002

Message Description: LOG_ID_DOMAIN_UNRESOLVABLE

Message Meaning: Domain name of alert email sender unresolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20003 - LOG_ID_MAIL_SENT_FAIL

Message ID: 20003

Message Description: LOG_ID_MAIL_SENT_FAIL

Message Meaning: Alert email send status failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20004 - LOG_ID_POLICY_TOO_BIG

Message ID: 20004

Message Description: LOG_ID_POLICY_TOO_BIG

Message Meaning: Policy too big for installation

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20005 - LOG_ID_PPP_LINK_UP

Message ID: 20005

Message Description: LOG_ID_PPP_LINK_UP

Message Meaning: Modem PPP link up

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20006 - LOG_ID_PPP_LINK_DOWN

Message ID: 20006

Message Description: LOG_ID_PPP_LINK_DOWN

Message Meaning: Modem PPP link down

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20007 - LOG_ID_SOCKET_EXHAUSTED

Message ID: 20007

Message Description: LOG_ID_SOCKET_EXHAUSTED

Message Meaning: NAT port exhausted

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
proto	Protocol Number	uint8	3

Log Field Name	Description	Data Type	Length
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20008 - LOG_ID_POLICY6_TOO_BIG

Message ID: 20008

Message Description: LOG_ID_POLICY6_TOO_BIG

Message Meaning: Policy6 too big for installation

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

20010 - LOG_ID_KERNEL_ERROR

Message ID: 20010

Message Description: LOG_ID_KERNEL_ERROR

Message Meaning: Kernel error

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT

Message ID: 20016

Message Description: LOG_ID_MODEM_EXCEED_REDIAL_COUNT

Message Meaning: Modem exceeded redial limit

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20017 - LOG_ID_MODEM_FAIL_TO_OPEN

Message ID: 20017

Message Description: LOG_ID_MODEM_FAIL_TO_OPEN

Message Meaning: Modem failed to open

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20020 - LOG_ID_MODEM_USB_DETECTED

Message ID: 20020

Message Description: LOG_ID_MODEM_USB_DETECTED

Message Meaning: USB modem detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20021 - LOG_ID_MAIL_RESENT

Message ID: 20021

Message Description: LOG_ID_MAIL_RESENT

Message Meaning: Alert email resent

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20022 - LOG_ID_MODEM_USB_REMOVED

Message ID: 20022

Message Description: LOG_ID_MODEM_USB_REMOVED

Message Meaning: USB modem removed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20023 - LOG_ID_MODEM_USBLTE_DETECTED

Message ID: 20023

Message Description: LOG_ID_MODEM_USBLTE_DETECTED

Message Meaning: USB LTE modem detected

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20024 - LOG_ID_MODEM_USBLTE_REMOVED

Message ID: 20024

Message Description: LOG_ID_MODEM_USBLTE_REMOVED

Message Meaning: USB LTE modem removed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20025 - LOG_ID_REPORTD_REPORT_SUCCESS

Message ID: 20025

Message Description: LOG_ID_REPORTD_REPORT_SUCCESS

Message Meaning: Report generated successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
datarange	data range for reports	string	50
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
file	File Name for Generated Report?	string	256
filesize	Report File Size in Bytes	uint32	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
processtime	process time for reports	uint32	
reporttype	Report Type	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20026 - LOG_ID_REPORTD_REPORT_FAILURE

Message ID: 20026

Message Description: LOG_ID_REPORTD_REPORT_FAILURE

Message Meaning: Report generation failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20027 - LOG_ID_REPORT_DEL_OLD_REC

Message ID: 20027

Message Description: LOG_ID_REPORT_DEL_OLD_REC

Message Meaning: Outdated report files deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20028 - LOG_ID_REPORT_RECREATE_DB

Message ID: 20028

Message Description: LOG_ID_REPORT_RECREATE_DB

Message Meaning: Report database recreated

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20031 - LOG_ID_RAD_OUT_OF_MEM

Message ID: 20031

Message Description: LOG_ID_RAD_OUT_OF_MEM

Message Meaning: RADVD out of memory

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20032 - LOG_ID_RAD_NOT_FOUND

Message ID: 20032

Message Description: LOG_ID_RAD_NOT_FOUND

Message Meaning: RADVD interface not found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20033 - LOG_ID_RAD_MOBILE_IPV6

Message ID: 20033

Message Description: LOG_ID_RAD_MOBILE_IPV6

Message Meaning: RADVD mobile IPv6 extensions used

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE

Message ID: 20034

Message Description: LOG_ID_RAD_IPV6_OUT_OF_RANGE

Message Meaning: RADVD mobile IPv6 MinRtrAdvInterval out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE

Message ID: 20035

Message Description: LOG_ID_RAD_MIN_OUT_OF_RANGE

Message Meaning: RADVD MinRtrAdvInterval out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE

Message ID: 20036

Message Description: LOG_ID_RAD_MAX_OUT_OF_RANGE

Message Meaning: RADVD mobile IPv6 MaxRtrAdvInterval out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE

Message ID: 20037

Message Description: LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE

Message Meaning: RADVD MaxRtrAdvInterval out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20039 - LOG_ID_RAD_MTU_TOO_SMALL

Message ID: 20039

Message Description: LOG_ID_RAD_MTU_TOO_SMALL

Message Meaning: RADVD AdvLinkMTU too small

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20040 - LOG_ID_RAD_TIME_TOO_SMALL

Message ID: 20040

Message Description: LOG_ID_RAD_TIME_TOO_SMALL

Message Meaning: RADVD AdvReachableTime too small

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE

Message ID: 20041

Message Description: LOG_ID_RAD_HOP_OUT_OF_RANGE

Message Meaning: RADVD AdvCurHopLimit too big

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE

Message ID: 20042

Message Description: LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE

Message Meaning: RADVD AdvCurHopLimit out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE

Message ID: 20043

Message Description: LOG_ID_RAD_AGENT_OUT_OF_RANGE

Message Meaning: RADVD HomeAgentLifetime out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET

Message ID: 20044

Message Description: LOG_ID_RAD_AGENT_FLAG_NOT_SET

Message Meaning: RADVD AdvHomeAgentFlag not set

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20045 - LOG_ID_RAD_PREFIX_TOO_LONG

Message ID: 20045

Message Description: LOG_ID_RAD_PREFIX_TOO_LONG

Message Meaning: RADVD invalid prefix length

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL

Message ID: 20046

Message Description: LOG_ID_RAD_PREF_TIME_TOO_SMALL

Message Meaning: RADVD AdvValidLifetime less than AdvPreferredLifetime

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET

Message ID: 20047

Message Description: LOG_ID_RAD_FAIL_IPV6_SOCKET

Message Meaning: RADVD failed to create an IPv6 socket

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO

Message ID: 20048

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO

Message Meaning: RADVD failed to set IPV6_PKTINFO

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM

Message ID: 20049

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM

Message Meaning: RADVD failed to set IPV6_CHECKSUM

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS

Message ID: 20050

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS

Message Meaning: RADVD failed to set IPV6_UNICAST_HOPS

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS

Message ID: 20051

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS

Message Meaning: RADVD failed to set IPV6_MULTICAST_HOPS

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT

Message ID: 20052

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT

Message Meaning: RADVD failed to set IPV6_HOPLIMIT

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6

Message ID: 20053

Message Description: LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6

Message Meaning: RADVD failed to set ICMPV6_FILTER

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20054 - LOG_ID_RAD_EXIT_BY_SIGNAL

Message ID: 20054

Message Description: LOG_ID_RAD_EXIT_BY_SIGNAL

Message Meaning: RADVD exited due to received signal

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20055 - LOG_ID_RAD_FAIL_CMDB_QUERY

Message ID: 20055

Message Description: LOG_ID_RAD_FAIL_CMDB_QUERY

Message Meaning: RADVD interface query creation failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH

Message ID: 20056

Message Description: LOG_ID_RAD_FAIL_CMDB_FOR_EACH

Message Meaning: RADVD query error

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF

Message ID: 20057

Message Description: LOG_ID_RAD_FAIL_FIND_VIRT_INTF

Message Meaning: RADVD virtual interface not found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20058 - LOG_ID_RAD_UNLOAD_INTF

Message ID: 20058

Message Description: LOG_ID_RAD_UNLOAD_INTF

Message Meaning: RADVD unloaded interface

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20059 - LOG_ID_RAD_NO_PKT_INFO

Message ID: 20059

Message Description: LOG_ID_RAD_NO_PKT_INFO

Message Meaning: RADVD received packet with no pkt_info

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20060 - LOG_ID_RAD_INV_ICMPV6_LEN

Message ID: 20060

Message Description: LOG_ID_RAD_INV_ICMPV6_LEN

Message Meaning: RADVD received ICMPv6 packet with invalid length

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20061 - LOG_ID_RAD_INV_ICMPV6_TYPE

Message ID: 20061

Message Description: LOG_ID_RAD_INV_ICMPV6_TYPE

Message Meaning: RADVD received unwanted ICMPv6 packet

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN

Message ID: 20062

Message Description: LOG_ID_RAD_INV_ICMPV6_RA_LEN

Message Meaning: RADVD received ICMPv6 RA packet with invalid length

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR

Message ID: 20063

Message Description: LOG_ID_RAD_ICMPV6_NO_SRC_ADDR

Message Meaning: RADVD received ICMPv6 RA packet with non-linklocal source address

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN

Message ID: 20064

Message Description: LOG_ID_RAD_INV_ICMPV6_RS_LEN

Message Meaning: RADVD received ICMPv6 RS packet with invalid length

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20065 - LOG_ID_RAD_INV_ICMPV6_CODE

Message ID: 20065

Message Description: LOG_ID_RAD_INV_ICMPV6_CODE

Message Meaning: RADVD received ICMPv6 RS/RA packet with invalid code

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20066 - LOG_ID_RAD_INV_ICMPV6_HOP

Message ID: 20066

Message Description: LOG_ID_RAD_INV_ICMPV6_HOP

Message Meaning: RADVD received ICMPv6 RS/RA packet with invalid hoplimit

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20067 - LOG_ID_RAD_MISMATCH_HOP

Message ID: 20067

Message Description: LOG_ID_RAD_MISMATCH_HOP

Message Meaning: RADVD local AdvCurHopLimit disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG

Message ID: 20068

Message Description: LOG_ID_RAD_MISMATCH_MGR_FLAG

Message Meaning: RADVD local AdvManagedFlag disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG

Message ID: 20069

Message Description: LOG_ID_RAD_MISMATCH_OTH_FLAG

Message Meaning: RADVD local AdvOtherConfigFlag disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20070 - LOG_ID_RAD_MISMATCH_TIME

Message ID: 20070

Message Description: LOG_ID_RAD_MISMATCH_TIME

Message Meaning: RADVD local AdvReachableTime disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20071 - LOG_ID_RAD_MISMATCH_TIMER

Message ID: 20071

Message Description: LOG_ID_RAD_MISMATCH_TIMER

Message Meaning: RADVD local AdvRetransTimer disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20072 - LOG_ID_RAD_EXTRA_DATA

Message ID: 20072

Message Description: LOG_ID_RAD_EXTRA_DATA

Message Meaning: RADVD extra data in RA packet found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20073 - LOG_ID_RAD_NO_OPT_DATA

Message ID: 20073

Message Description: LOG_ID_RAD_NO_OPT_DATA

Message Meaning: RADVD RA packet option length zero

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20074 - LOG_ID_RAD_INV_OPT_LEN

Message ID: 20074

Message Description: LOG_ID_RAD_INV_OPT_LEN

Message Meaning: RADVD RA packet option length greater than total length

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20075 - LOG_ID_RAD_MISMATCH_MTU

Message ID: 20075

Message Description: LOG_ID_RAD_MISMATCH_MTU

Message Meaning: RADVD local AdvLinkMTU disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20077 - LOG_ID_RAD_MISMATCH_PREF_TIME

Message ID: 20077

Message Description: LOG_ID_RAD_MISMATCH_PREF_TIME

Message Meaning: Interface AdvPreferredLifetime on our interface does not agree with a remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20078 - LOG_ID_RAD_INV_OPT

Message ID: 20078

Message Description: LOG_ID_RAD_INV_OPT

Message Meaning: RADVD found invalid option in RA packet from remote site

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20079 - LOG_ID_RAD_READY

Message ID: 20079

Message Description: LOG_ID_RAD_READY

Message Meaning: RADVD daemon started

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20080 - LOG_ID_RAD_FAIL_TO_RCV

Message ID: 20080

Message Description: LOG_ID_RAD_FAIL_TO_RCV

Message Meaning: RADVD rcvmsg failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20081 - LOG_ID_RAD_INV_HOP

Message ID: 20081

Message Description: LOG_ID_RAD_INV_HOP

Message Meaning: RADVD received invalid IPV6_HOPLIMIT

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20082 - LOG_ID_RAD_INV_PKTINFO

Message ID: 20082

Message Description: LOG_ID_RAD_INV_PKTINFO

Message Meaning: RADVD received invalid IPV6_PKTINFO

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20083 - LOG_ID_RAD_FAIL_TO_CHECK

Message ID: 20083

Message Description: LOG_ID_RAD_FAIL_TO_CHECK

Message Meaning: RADVD all-routers membership check failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20084 - LOG_ID_RAD_FAIL_TO_SEND

Message ID: 20084

Message Description: LOG_ID_RAD_FAIL_TO_SEND

Message Meaning: RADVD sendmsg failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20085 - LOG_ID_SESSION_CLASH

Message ID: 20085

Message Description: LOG_ID_SESSION_CLASH

Message Meaning: Session clashed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
proto	Protocol Number	uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
trace_id		string	32
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20086 - LOG_ID_XH0_EVENT

Message ID: 20086

Message Description: LOG_ID_XH0_EVENT

Message Meaning: xh0 crashed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20090 - LOG_ID_INTF_LINK_STA_CHG

Message ID: 20090

Message Description: LOG_ID_INTF_LINK_STA_CHG

Message Meaning: Interface link status changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20099 - LOG_ID_INTF_STA_CHG

Message ID: 20099

Message Description: LOG_ID_INTF_STA_CHG

Message Meaning: Interface status changed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20100 - LOG_ID_WEB_CAT_UPDATED

Message ID: 20100

Message Description: LOG_ID_WEB_CAT_UPDATED

Message Meaning: FortiGuard web filter category list updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20101 - LOG_ID_WEB_LIC_EXPIRE

Message ID: 20101

Message Description: LOG_ID_WEB_LIC_EXPIRE

Message Meaning: FortiGuard web filter license expiring

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20102 - LOG_ID_SPAM_LIC_EXPIRE

Message ID: 20102**Message Description:** LOG_ID_SPAM_LIC_EXPIRE**Message Meaning:** FortiGuard antispam license expiring**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20103 - LOG_ID_AV_LIC_EXPIRE

Message ID: 20103

Message Description: LOG_ID_AV_LIC_EXPIRE

Message Meaning: FortiGuard antivirus license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20104 - LOG_ID_IPS_LIC_EXPIRE

Message ID: 20104

Message Description: LOG_ID_IPS_LIC_EXPIRE

Message Meaning: FortiGuard IPS license expiring

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20105 - LOG_ID_LOG_UPLOAD_SKIP

Message ID: 20105**Message Description:** LOG_ID_LOG_UPLOAD_SKIP**Message Meaning:** Log upload to FortiCloud skipped**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

20107 - LOG_ID_LOG_UPLOAD_ERR

Message ID: 20107

Message Description: LOG_ID_LOG_UPLOAD_ERR

Message Meaning: Log upload error

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
error	Error Reason for Log Upload to Forticloud	string	256
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

20108 - LOG_ID_LOG_UPLOAD_DONE

Message ID: 20108

Message Description: LOG_ID_LOG_UPLOAD_DONE

Message Meaning: Log upload completed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

20109 - LOG_ID_WEB_LIC_EXPIRED

Message ID: 20109

Message Description: LOG_ID_WEB_LIC_EXPIRED

Message Meaning: FortiGuard web filter license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20113 - LOG_ID_IPSA_DOWNLOAD_FAIL

Message ID: 20113

Message Description: LOG_ID_IPSA_DOWNLOAD_FAIL

Message Meaning: IPSA database download failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20115 - LOG_ID_IPSA_STATUSUPD_FAIL

Message ID: 20115

Message Description: LOG_ID_IPSA_STATUSUPD_FAIL

Message Meaning: IPSA driver update failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20116 - LOG_ID_SPAM_LIC_EXPIRED

Message ID: 20116

Message Description: LOG_ID_SPAM_LIC_EXPIRED

Message Meaning: FortiGuard antispam license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20118 - LOG_ID_WEBF_STATUS_REACH

Message ID: 20118

Message Description: LOG_ID_WEBF_STATUS_REACH

Message Meaning: FortiGuard webfilter reachable

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20119 - LOG_ID_WEBF_STATUS_UNREACH

Message ID: 20119

Message Description: LOG_ID_WEBF_STATUS_UNREACH

Message Meaning: FortiGuard webfilter unreachable

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20200 - LOG_ID_FIPS_SELF_TEST

Message ID: 20200

Message Description: LOG_ID_FIPS_SELF_TEST

Message Meaning: FIPS CC self-test initiated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20201 - LOG_ID_FIPS_SELF_ALL_TEST

Message ID: 20201

Message Description: LOG_ID_FIPS_SELF_ALL_TEST

Message Meaning: FIPS ALL CC self-tests initiated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20202 - LOG_ID_DISK_FORMAT_ERROR

Message ID: 20202

Message Description: LOG_ID_DISK_FORMAT_ERROR

Message Meaning: Disk partitioning or formatting Error

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20203 - LOG_ID_DAEMON_SHUTDOWN

Message ID: 20203

Message Description: LOG_ID_DAEMON_SHUTDOWN

Message Meaning: Daemon shutdown

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20204 - LOG_ID_DAEMON_START

Message ID: 20204

Message Description: LOG_ID_DAEMON_START

Message Meaning: Daemon started

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20205 - LOG_ID_DISK_FORMAT_REQ

Message ID: 20205

Message Description: LOG_ID_DISK_FORMAT_REQ

Message Meaning: Format disk requested

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20206 - LOG_ID_DISK_SCAN_REQ

Message ID: 20206

Message Description: LOG_ID_DISK_SCAN_REQ

Message Meaning: Scan disk requested

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20207 - LOG_ID_RAD_MISMATCH_VALID_TIME

Message ID: 20207

Message Description: LOG_ID_RAD_MISMATCH_VALID_TIME

Message Meaning: RADVD local AdvValidLifeTime disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP

Message ID: 20208

Message Description: LOG_ID_ZOMBIE_DAEMON_CLEANUP

Message Meaning: Zombie daemon cleanup

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
pid	Process ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20209 - LOG_ID_DISK_UNAVAIL

Message ID: 20209

Message Description: LOG_ID_DISK_UNAVAIL

Message Meaning: Disk unavailable

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20210 - LOG_ID_DISK_TRIM_START

Message ID: 20210

Message Description: LOG_ID_DISK_TRIM_START

Message Meaning: SSD Trim Started

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20211 - LOG_ID_DISK_TRIM_END

Message ID: 20211

Message Description: LOG_ID_DISK_TRIM_END

Message Meaning: SSD Trim Finished

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

20212 - LOG_ID_DISK_SCAN_NEEDED

Message ID: 20212

Message Description: LOG_ID_DISK_SCAN_NEEDED

Message Meaning: Scan disk is needed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20220 - LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT

Message ID: 20220

Message Description: LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT

Message Meaning: Outbound bandwidth rate exceeded

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20221 - LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT

Message ID: 20221

Message Description: LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT

Message Meaning: Inbound bandwidth rate exceeded

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
intf	Interface	string	16
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20300 - LOG_ID_BGP_NB_STAT_CHG

Message ID: 20300

Message Description: LOG_ID_BGP_NB_STAT_CHG

Message Meaning: BGP neighbor status changed

Type: Event

Category: ROUTER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20301 - LOG_ID_VZ_LOG

Message ID: 20301

Message Description: LOG_ID_VZ_LOG

Message Meaning: Routing log

Type: Event

Category: ROUTER**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20302 - LOG_ID_OSPF_NB_STAT_CHG

Message ID: 20302**Message Description:** LOG_ID_OSPF_NB_STAT_CHG**Message Meaning:** OSPF neighbor status changed**Type:** Event**Category:** ROUTER**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20303 - LOG_ID_OSPF6_NB_STAT_CHG

Message ID: 20303

Message Description: LOG_ID_OSPF6_NB_STAT_CHG

Message Meaning: OSPFv3 neighbor status changed

Type: Event

Category: ROUTER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

20401 - LOG_ID_ROUTER_CLEAR

Message ID: 20401

Message Description: LOG_ID_ROUTER_CLEAR

Message Meaning: Router cleared

Type: Event

Category: ROUTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui		string	64
user		string	256
vd	Virtual Domain Name	string	32

22000 - LOG_ID_INV_PKT_LEN

Message ID: 22000**Message Description:** LOG_ID_INV_PKT_LEN**Message Meaning:** Packet length mismatch**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22001 - LOG_ID_UNSUPPORTED_PROT_VER

Message ID: 22001

Message Description: LOG_ID_UNSUPPORTED_PROT_VER

Message Meaning: Protocol version unsupported

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22002 - LOG_ID_INV_REQ_TYPE

Message ID: 22002

Message Description: LOG_ID_INV_REQ_TYPE

Message Meaning: Request type not supported

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22003 - LOG_ID_FAIL_SET_SIG_HANDLER

Message ID: 22003

Message Description: LOG_ID_FAIL_SET_SIG_HANDLER

Message Meaning: Signal handler setup failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22004 - LOG_ID_FAIL_CREATE_SOCKET

Message ID: 22004

Message Description: LOG_ID_FAIL_CREATE_SOCKET

Message Meaning: Socket creation failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY

Message ID: 22005

Message Description: LOG_ID_FAIL_CREATE_SOCKET_RETRY

Message Meaning: Socket creation retry failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22006 - LOG_ID_FAIL_REG_CMDB_EVENT

Message ID: 22006

Message Description: LOG_ID_FAIL_REG_CMDB_EVENT

Message Meaning: Registration for CMDB events failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22009 - LOG_ID_FAIL_FIND_AV_PROFILE

Message ID: 22009

Message Description: LOG_ID_FAIL_FIND_AV_PROFILE

Message Meaning: AntiVirus profile not found

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22010 - LOG_ID_SENDTO_FAIL

Message ID: 22010

Message Description: LOG_ID_SENDTO_FAIL

Message Meaning: URL filter packet send failure

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
process	Process	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE

Message ID: 22011

Message Description: LOG_ID_ENTER_MEM_CONSERVE_MODE

Message Meaning: Memory conserve mode entered

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE

Message ID: 22012

Message Description: LOG_ID_LEAVE_MEM_CONSERVE_MODE

Message Meaning: Memory conserve mode exited

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22013 - LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED

Message ID: 22013

Message Description: LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED

Message Meaning: IP pool PBA block exhausted

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22014 - LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED

Message ID: 22014

Message Description: LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED

Message Meaning: IP pool PBA NATIP exhausted

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
poolname	IP Pool Name	string	36
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22015 - LOG_ID_IPPOOLPBA_CREATE

Message ID: 22015

Message Description: LOG_ID_IPPOOLPBA_CREATE

Message Meaning: IP pool PBA created

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22016 - LOG_ID_IPPOOLPBA_DEALLOCATE

Message ID: 22016

Message Description: LOG_ID_IPPOOLPBA_DEALLOCATE

Message Meaning: Deallocate IP pool PBA

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
nat	NAT IP Address	ip	39
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
saddr	Source Address IP	string	80
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT

Message ID: 22017

Message Description: LOG_ID_EXCEED_GLOB_RES_LIMIT

Message Meaning: Global resource limit exceeded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22018 - LOG_ID_EXCEED_VD_RES_LIMIT

Message ID: 22018

Message Description: LOG_ID_EXCEED_VD_RES_LIMIT

Message Meaning: VDOM resource limit exceeded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22020 - LOG_ID_FAIL_CREATE_HA_SOCKET

Message ID: 22020

Message Description: LOG_ID_FAIL_CREATE_HA_SOCKET

Message Meaning: HA socket creation failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY

Message ID: 22021

Message Description: LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY

Message Meaning: UDP socket creation to relay URL request failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22030 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FAZ

Message ID: 22030

Message Description: LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FAZ

Message Meaning: FAZ is not configured for Security Fabric Service

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
server	Server IP Address	string	64
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22031 - LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED

Message ID: 22031

Message Description: LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED

Message Meaning: Settings modified by Security Fabric service

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22032 - LOG_ID_CSF_LOOP_FOUND

Message ID: 22032

Message Description: LOG_ID_CSF_LOOP_FOUND

Message Meaning: Looped configuration in Security Fabric service

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
path		string	512
reason	Reason	string	256
sn	Serial Number	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22100 - LOG_ID_QUAR_DROP_TRAN_JOB

Message ID: 22100

Message Description: LOG_ID_QUAR_DROP_TRAN_JOB

Message Meaning: Files dropped by quarantine daemon

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
fams_pause	Fortinet Analysis and Management Service Pause	uint32	10
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22101 - LOG_ID_QUAR_DROP_TLL_JOB

Message ID: 22101

Message Description: LOG_ID_QUAR_DROP_TLL_JOB

Message Meaning: Files dropped due to poor network connection

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22102 - LOG_ID_LOG_DISK_FAILURE

Message ID: 22102

Message Description: LOG_ID_LOG_DISK_FAILURE

Message Meaning: Log disk failure imminent

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22103 - LOG_ID_QUAR_LIMIT_REACHED

Message ID: 22103

Message Description: LOG_ID_QUAR_LIMIT_REACHED

Message Meaning: Sandbox limit reached

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
limit	Virtual Domain Resource Limit	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22104 - LOG_ID_POWER_RESTORE

Message ID: 22104

Message Description: LOG_ID_POWER_RESTORE

Message Meaning: Power supply restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

22105 - LOG_ID_POWER_FAILURE

Message ID: 22105

Message Description: LOG_ID_POWER_FAILURE

Message Meaning: Power supply failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unit	Unit	uint32	10
vd	Virtual Domain Name	string	32

22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED

Message ID: 22106

Message Description: LOG_ID_POWER_OPTIONAL_NOT_DETECTED

Message Meaning: Optional power supply not detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22107 - LOG_ID_VOLT_ANOM

Message ID: 22107

Message Description: LOG_ID_VOLT_ANOM

Message Meaning: Voltage anomaly

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22108 - LOG_ID_FAN_ANOM

Message ID: 22108

Message Description: LOG_ID_FAN_ANOM

Message Meaning: Fan anomaly

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22109 - LOG_ID_TEMP_TOO_HIGH

Message ID: 22109

Message Description: LOG_ID_TEMP_TOO_HIGH

Message Meaning: Temperature too high

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22110 - LOG_ID_SPARE_BLOCK_LOW

Message ID: 22110

Message Description: LOG_ID_SPARE_BLOCK_LOW

Message Meaning: Spare blocks availability low

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22111 - LOG_ID_POWER_RESTORE_NOTIF

Message ID: 22111

Message Description: LOG_ID_POWER_RESTORE_NOTIF

Message Meaning: Power supply restored

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22112 - LOG_ID_POWER_FAILURE_WARNING

Message ID: 22112

Message Description: LOG_ID_POWER_FAILURE_WARNING

Message Meaning: Power supply failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22113 - LOG_ID_FNBAM_FAILURE

Message ID: 22113

Message Description: LOG_ID_FNBAM_FAILURE

Message Meaning: Authentication error

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

22150 - LOG_ID_VOLT_NOM

Message ID: 22150

Message Description: LOG_ID_VOLT_NOM

Message Meaning: Voltage normal

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22151 - LOG_ID_FAN_NOM

Message ID: 22151

Message Description: LOG_ID_FAN_NOM

Message Meaning: Fan normal

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22152 - LOG_ID_TEMP_TOO_LOW

Message ID: 22152

Message Description: LOG_ID_TEMP_TOO_LOW

Message Meaning: Temperature too low

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22153 - LOG_ID_TEMP_NORM

Message ID: 22153

Message Description: LOG_ID_TEMP_NORM

Message Meaning: Temperature normal

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22200 - LOG_ID_AUTO_UPT_CERT

Message ID: 22200

Message Description: LOG_ID_AUTO_UPT_CERT

Message Meaning: Certificate will be auto-updated

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22201 - LOG_ID_AUTO_GEN_CERT

Message ID: 22201

Message Description: LOG_ID_AUTO_GEN_CERT

Message Meaning: Certificate will be auto-regenerated

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert	Certificate	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22203 - LOG_ID_AUTO_GEN_CERT_FAIL

Message ID: 22203

Message Description: LOG_ID_AUTO_GEN_CERT_FAIL

Message Meaning: Certificate failed to auto-generate

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22204 - LOG_ID_AUTO_GEN_CERT_PENDING

Message ID: 22204

Message Description: LOG_ID_AUTO_GEN_CERT_PENDING

Message Meaning: Certificate pending to auto-generate

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22205 - LOG_ID_AUTO_GEN_CERT_SUCC

Message ID: 22205

Message Description: LOG_ID_AUTO_GEN_CERT_SUCC

Message Meaning: Certificate succeed to auto-generate

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22206 - LOG_ID_CRL_EXPIRED

Message ID: 22206

Message Description: LOG_ID_CRL_EXPIRED

Message Meaning: CRL is expired

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22700 - LOG_ID_IPS_FAIL_OPEN

Message ID: 22700

Message Description: LOG_ID_IPS_FAIL_OPEN

Message Meaning: IPS session scan paused

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22701 - LOG_ID_IPS_FAIL_OPEN_END

Message ID: 22701

Message Description: LOG_ID_IPS_FAIL_OPEN_END

Message Meaning: IPS session scan resumed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22800 - LOG_ID_SCAN_SERV_FAIL

Message ID: 22800

Message Description: LOG_ID_SCAN_SERV_FAIL

Message Meaning: Scan services session failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message Text	string	
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22802 - LOG_ID_ENTER_FD_CONSERVE_MODE

Message ID: 22802

Message Description: LOG_ID_ENTER_FD_CONSERVE_MODE

Message Meaning: File descriptor conserve mode entered

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
red		string	32
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE

Message ID: 22803

Message Description: LOG_ID_LEAVE_FD_CONSERVE_MODE

Message Meaning: File descriptor conserve mode exited

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22804 - LOG_ID_LIC_STATUS_CHG

Message ID: 22804

Message Description: LOG_ID_LIC_STATUS_CHG

Message Meaning: License status changed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22805 - LOG_ID_FAIL_TO_VALIDATE_LIC

Message ID: 22805

Message Description: LOG_ID_FAIL_TO_VALIDATE_LIC

Message Meaning: License validation failure

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22806 - LOG_ID_DUP_LIC

Message ID: 22806

Message Description: LOG_ID_DUP_LIC

Message Meaning: Duplicate license detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22807 - LOG_ID_LEAVE_FD_CONSERVE_MODE_NOTIF

Message ID: 22807

Message Description: LOG_ID_LEAVE_FD_CONSERVE_MODE_NOTIF

Message Meaning: File descriptor conserve mode exited

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
conserve	Flag for Conserve Mode	string	32
daemon	Daemon Name	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
green		string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
red		string	32
subtype	Log Subtype	string	20
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

22808 - LOG_ID_LIC_EXPIRE

Message ID: 22808

Message Description: LOG_ID_LIC_EXPIRE

Message Meaning: VM license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22809 - LOG_ID_LIC_WILL_EXPIRE

Message ID: 22809

Message Description: LOG_ID_LIC_WILL_EXPIRE

Message Meaning: VM license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
service	Name of Service	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22891 - LOG_ID_FLCFGD

Message ID: 22891

Message Description: LOG_ID_FLCFGD

Message Meaning: Switch-Controller Config Daemon Log

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

22892 - LOG_ID_FLCFGD_INFO

Message ID: 22892

Message Description: LOG_ID_FLCFGD_INFO

Message Meaning: Switch-Controller Config Daemon Log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

22893 - LOG_ID_FLCFGD_WARNING

Message ID: 22893

Message Description: LOG_ID_FLCFGD_WARNING

Message Meaning: Switch-Controller Config Daemon Log

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

22900 - LOG_ID_CAPUTP_SESSION

Message ID: 22900

Message Description: LOG_ID_CAPUTP_SESSION

Message Meaning: CAPUTP session status

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22901 - LOG_ID_FAZ_CON

Message ID: 22901

Message Description: LOG_ID_FAZ_CON

Message Meaning: FortiAnalyzer connection up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22902 - LOG_ID_FAZ_DISCON

Message ID: 22902

Message Description: LOG_ID_FAZ_DISCON

Message Meaning: FortiAnalyzer connection down

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22903 - LOG_ID_FAZ_CON_ERR

Message ID: 22903

Message Description: LOG_ID_FAZ_CON_ERR

Message Meaning: FortiAnalyzer connection failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22904 - LOG_ID_CAPUTP_SESSION_NOTIF

Message ID: 22904

Message Description: LOG_ID_CAPUTP_SESSION_NOTIF

Message Meaning: CAPUTP session status notification

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

22912 - LOG_ID_FDS_SRV_ERRCON

Message ID: 22912

Message Description: LOG_ID_FDS_SRV_ERRCON

Message Meaning: FortiCloud server connection failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22913 - LOG_ID_FDS_SRV_DISCON

Message ID: 22913

Message Description: LOG_ID_FDS_SRV_DISCON

Message Meaning: FortiCloud server disconnected

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22914 - LOG_ID_FDS_SRV_CHG

Message ID: 22914

Message Description: LOG_ID_FDS_SRV_CHG

Message Meaning: FortiCloud server changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22915 - LOG_ID_FDS_SRV_CON

Message ID: 22915

Message Description: LOG_ID_FDS_SRV_CON

Message Meaning: FortiCloud server connected

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
server	Server IP Address	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22916 - LOG_ID_FDS_STATUS

Message ID: 22916

Message Description: LOG_ID_FDS_STATUS

Message Meaning: FortiGuard Message Service status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22917 - LOG_ID_FDS_SMS_QUOTA

Message ID: 22917

Message Description: LOG_ID_FDS_SMS_QUOTA

Message Meaning: SMS quota reached

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22918 - LOG_ID_FDS_CTRL_STATUS

Message ID: 22918

Message Description: LOG_ID_FDS_CTRL_STATUS

Message Meaning: FortiGuard Message Service controller status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED

Message ID: 22921

Message Description: LOG_ID_EVENT_ROUTE_INFO_CHANGED

Message Meaning: Routing information changed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS

Message ID: 22922

Message Description: LOG_ID_EVENT_LINK_MONITOR_STATUS

Message Meaning: Link monitor status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
probeproto	Link Monitor Probe Protocol	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22923 - LOG_ID_EVENT_VWL_LQTY_STATUS

Message ID: 22923

Message Description: LOG_ID_EVENT_VWL_LQTY_STATUS

Message Meaning: Virtual WAN Link status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS

Message ID: 22924

Message Description: LOG_ID_EVENT_VWL_VOLUME_STATUS

Message Meaning: Virtual WAN Link volume status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

22950 - LOG_ID_FDS_LOGIN_SUCC

Message ID: 22950

Message Description: LOG_ID_FDS_LOGIN_SUCC

Message Meaning: FortiCloud login

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22951 - LOG_ID_FDS_LOGOUT

Message ID: 22951**Message Description:** LOG_ID_FDS_LOGOUT**Message Meaning:** FortiCloud logout**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

22952 - LOG_ID_FDS_LOGIN_FAIL

Message ID: 22952

Message Description: LOG_ID_FDS_LOGIN_FAIL

Message Meaning: FortiCloud activation failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

23101 - LOG_ID_IPSEC_TUNNEL_UP

Message ID: 23101

Message Description: LOG_ID_IPSEC_TUNNEL_UP

Message Meaning: IPsec VPN tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

23102 - LOG_ID_IPSEC_TUNNEL_DOWN

Message ID: 23102

Message Description: LOG_ID_IPSEC_TUNNEL_DOWN

Message Meaning: IPsec VPN tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

23103 - LOG_ID_IPSEC_TUNNEL_STAT

Message ID: 23103

Message Description: LOG_ID_IPSEC_TUNNEL_STAT

Message Meaning: IPsec VPN tunnel statistics

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

26001 - LOG_ID_DHCP_ACK

Message ID: 26001

Message Description: LOG_ID_DHCP_ACK

Message Meaning: DHCP Ack log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
hostname	Hostname	string	128
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26002 - LOG_ID_DHCP_RELEASE

Message ID: 26002

Message Description: LOG_ID_DHCP_RELEASE

Message Meaning: DHCP Release log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
hostname	Hostname	string	128

Log Field Name	Description	Data Type	Length
interface	Interface	string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26003 - LOG_ID_DHCP_STAT

Message ID: 26003

Message Description: LOG_ID_DHCP_STAT

Message Meaning: DHCP statistics

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
total	Total	uint32	10
type	Log Type	string	16
used	Number of Used IPs	uint32	10
vd	Virtual Domain Name	string	32

26004 - LOG_ID_DHCP_CLIENT_LEASE

Message ID: 26004

Message Description: LOG_ID_DHCP_CLIENT_LEASE

Message Meaning: DHCP client lease granted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH

Message ID: 26005

Message Description: LOG_ID_DHCP_LEASE_USAGE_HIGH

Message Meaning: DHCP lease usage high

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26006 - LOG_ID_DHCP_LEASE_USAGE_FULL

Message ID: 26006

Message Description: LOG_ID_DHCP_LEASE_USAGE_FULL

Message Meaning: DHCP lease usage full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26007 - LOG_ID_DHCP_BLOCKED_MAC

Message ID: 26007

Message Description: LOG_ID_DHCP_BLOCKED_MAC

Message Meaning: DHCP client blocked log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface	Interface	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26008 - LOG_ID_DHCP_DDNS_ADD

Message ID: 26008

Message Description: LOG_ID_DHCP_DDNS_ADD

Message Meaning: DHCP DDNS add query

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26009 - LOG_ID_DHCP_DDNS_DELETE

Message ID: 26009

Message Description: LOG_ID_DHCP_DDNS_DELETE

Message Meaning: DHCP DDNS delete query

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26010 - LOG_ID_DHCP_DDNS_COMPLETED

Message ID: 26010

Message Description: LOG_ID_DHCP_DDNS_COMPLETED

Message Meaning: DHCP DDNS query completed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
ddnsserver	DDNS Server	ip	39
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fqdn		string	256
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26011 - LOG_ID_DHCPV6_REPLY

Message ID: 26011

Message Description: LOG_ID_DHCPV6_REPLY

Message Meaning: DHCPv6 Ack log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
duid		string	128
eventtime		uint64	20
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

26012 - LOG_ID_DHCPV6_RELEASE

Message ID: 26012

Message Description: LOG_ID_DHCPV6_RELEASE

Message Meaning: DHCPv6 Release log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dhcp_msg	DHCP Message	string	
duid		string	128
eventtime		uint64	20
iaid		uint32	10
interface	Interface	string	32
ip		ip	39
lease	DHCP Lease	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

27001 - LOG_ID_VRRP_STATE_CHG

Message ID: 27001

Message Description: LOG_ID_VRRP_STATE_CHG

Message Meaning: VRRP state changed

Type: Event

Category: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29001 - LOG_ID_PPPD_MSG

Message ID: 29001

Message Description: LOG_ID_PPPD_MSG

Message Meaning: PPPD status

Type: Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

29002 - LOG_ID_PPPD_AUTH_SUC

Message ID: 29002**Message Description:** LOG_ID_PPPD_AUTH_SUC**Message Meaning:** PPPD authentication successful**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

29003 - LOG_ID_PPPD_AUTH_FAIL

Message ID: 29003

Message Description: LOG_ID_PPPD_AUTH_FAIL

Message Meaning: PPPD authentication failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
remote	Remote IP Address	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29010 - LOG_ID_PPPOE_STATUS_REPORT_NOTIF

Message ID: 29010

Message Description: LOG_ID_PPPOE_STATUS_REPORT_NOTIF

Message Meaning: PPPoE status report

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
assigned	Assigned IP Address	ip	39
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
gateway	gateway ip address for PPPoE status report	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
mtu	Max Transmission Unit Value	uint32	10

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29011 - LOG_ID_PPPD_FAIL_TO_EXEC

Message ID: 29011

Message Description: LOG_ID_PPPD_FAIL_TO_EXEC

Message Meaning: PPPD execution failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29012 - LOG_ID_PPP_OPT_ERR

Message ID: 29012

Message Description: LOG_ID_PPP_OPT_ERR

Message Meaning: PPP received incorrect options

Type: Event

Category: SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29013 - LOG_ID_PPPD_START

Message ID: 29013**Message Description:** LOG_ID_PPPD_START**Message Meaning:** PPPD started**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29014 - LOG_ID_PPPD_EXIT

Message ID: 29014

Message Description: LOG_ID_PPPD_EXIT

Message Meaning: PPPD exiting

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29015 - LOG_ID_PPP_RCV_BAD_PEER_IP

Message ID: 29015

Message Description: LOG_ID_PPP_RCV_BAD_PEER_IP

Message Meaning: PPP received invalid peer IP

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP

Message ID: 29016**Message Description:** LOG_ID_PPP_RCV_BAD_LOCAL_IP**Message Meaning:** PPP received invalid local IP**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29017 - LOG_ID_PPP_OPT_NOTIF

Message ID: 29017

Message Description: LOG_ID_PPP_OPT_NOTIF

Message Meaning: PPP received incorrect notifications

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED

Message ID: 29021

Message Description: LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED

Message Meaning: SNMP query failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
community	Community	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version	Version	string	64

29022 - LOG_ID_DDNS_UPDATE_FAIL

Message ID: 29022

Message Description: LOG_ID_DDNS_UPDATE_FAIL

Message Meaning: DDNS update failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32001 - LOG_ID_ADMIN_LOGIN_SUCC

Message ID: 32001

Message Description: LOG_ID_ADMIN_LOGIN_SUCC

Message Meaning: Admin login successful

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
profile	Profile Name	string	64

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32002 - LOG_ID_ADMIN_LOGIN_FAIL

Message ID: 32002

Message Description: LOG_ID_ADMIN_LOGIN_FAIL

Message Meaning: Admin login failed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32003 - LOG_ID_ADMIN_LOGOUT

Message ID: 32003

Message Description: LOG_ID_ADMIN_LOGOUT

Message Meaning: Admin logout successful

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32005 - LOG_ID_ADMIN_OVERRIDE_VDOM

Message ID: 32005

Message Description: LOG_ID_ADMIN_OVERRIDE_VDOM

Message Meaning: Admin overrode VDOM

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32006 - LOG_ID_ADMIN_ENTER_VDOM

Message ID: 32006

Message Description: LOG_ID_ADMIN_ENTER_VDOM

Message Meaning: Super admin entered VDOM

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32007 - LOG_ID_ADMIN_LEFT_VDOM

Message ID: 32007

Message Description: LOG_ID_ADMIN_LEFT_VDOM

Message Meaning: Super admin left VDOM

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32008 - LOG_ID_VIEW_DISK_LOG_FAIL

Message ID: 32008

Message Description: LOG_ID_VIEW_DISK_LOG_FAIL

Message Meaning: Disk log access failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32009 - LOG_ID_SYSTEM_START

Message ID: 32009

Message Description: LOG_ID_SYSTEM_START

Message Meaning: FortiGate started

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32010 - LOG_ID_DISK_LOG_FULL

Message ID: 32010

Message Description: LOG_ID_DISK_LOG_FULL

Message Meaning: Disk full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32011 - LOG_ID_LOG_ROLL

Message ID: 32011

Message Description: LOG_ID_LOG_ROLL

Message Meaning: Disk log rolled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32014 - LOG_ID_CS_LIC_EXPIRE

Message ID: 32014

Message Description: LOG_ID_CS_LIC_EXPIRE

Message Meaning: Support license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32015 - LOG_ID_DISK_LOG_USAGE

Message ID: 32015

Message Description: LOG_ID_DISK_LOG_USAGE

Message Meaning: Log disk full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32016 - LOG_ID_FDS_QUOTA_WARN

Message ID: 32016

Message Description: LOG_ID_FDS_QUOTA_WARN

Message Meaning: FortiCloud quota full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32017 - LOG_ID_FDS_DAILY_QUOTA_FULL

Message ID: 32017

Message Description: LOG_ID_FDS_DAILY_QUOTA_FULL

Message Meaning: FortiCloud daily quota full

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32018 - LOG_ID_FIPS_ENTER_ERR_MOD

Message ID: 32018

Message Description: LOG_ID_FIPS_ENTER_ERR_MOD

Message Meaning: FIPS CC entered error mode

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32019 - LOG_ID_CC_ENTER_ERR_MOD

Message ID: 32019

Message Description: LOG_ID_CC_ENTER_ERR_MOD

Message Meaning: CC entered error mode

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32020 - LOG_ID_SSH_CORRPUT_MAC

Message ID: 32020

Message Description: LOG_ID_SSH_CORRPUT_MAC

Message Meaning: Message Authentication Code corrupted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32021 - LOG_ID_ADMIN_LOGIN_DISABLE

Message ID: 32021

Message Description: LOG_ID_ADMIN_LOGIN_DISABLE

Message Meaning: Admin login disabled

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32022 - LOG_ID_VDOM_ENABLED

Message ID: 32022

Message Description: LOG_ID_VDOM_ENABLED

Message Meaning: VDOM enabled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32023 - LOG_ID_MEM_LOG_FIRST_FULL

Message ID: 32023

Message Description: LOG_ID_MEM_LOG_FIRST_FULL

Message Meaning: Memory log full over first warning level

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32024 - LOG_ID_ADMIN_PASSWD_EXPIRE

Message ID: 32024

Message Description: LOG_ID_ADMIN_PASSWD_EXPIRE

Message Meaning: Admin password expired

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32025 - LOG_ID_SSH_REKEY

Message ID: 32025**Message Description:** LOG_ID_SSH_REKEY**Message Meaning:** SSH server rekey**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32026 - LOG_ID_SSH_BAD_PACKET_LENGTH

Message ID: 32026

Message Description: LOG_ID_SSH_BAD_PACKET_LENGTH

Message Meaning: SSH server received bad length packet

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32027 - LOG_ID_VIEW_DISK_LOG_SUCC

Message ID: 32027

Message Description: LOG_ID_VIEW_DISK_LOG_SUCC

Message Meaning: Disk logs viewed successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32028 - LOG_ID_LOG_DEL_DIR

Message ID: 32028

Message Description: LOG_ID_LOG_DEL_DIR

Message Meaning: Disk log directory deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32029 - LOG_ID_LOG_DEL_FILE

Message ID: 32029

Message Description: LOG_ID_LOG_DEL_FILE

Message Meaning: Disk log file deleted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
filesize	Report File Size in Bytes	uint32	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32030 - LOG_ID_SEND_FDS_STAT

Message ID: 32030

Message Description: LOG_ID_SEND_FDS_STAT

Message Meaning: FDS statistics sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32031 - LOG_ID_VIEW_MEM_LOG_FAIL

Message ID: 32031

Message Description: LOG_ID_VIEW_MEM_LOG_FAIL

Message Meaning: Memory log access failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32032 - LOG_ID_DISK_DLP_ARCH_FULL

Message ID: 32032

Message Description: LOG_ID_DISK_DLP_ARCH_FULL

Message Meaning: DLP archive full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32033 - LOG_ID_DISK_QUAR_FULL

Message ID: 32033

Message Description: LOG_ID_DISK_QUAR_FULL

Message Meaning: Quarantine full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32034 - LOG_ID_DISK_REPORT_FULL

Message ID: 32034

Message Description: LOG_ID_DISK_REPORT_FULL

Message Meaning: Report full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32035 - LOG_ID_VDOM_DISABLED

Message ID: 32035

Message Description: LOG_ID_VDOM_DISABLED

Message Meaning: VDOM disabled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32036 - LOG_ID_DISK_IPS_ARCH_FULL

Message ID: 32036

Message Description: LOG_ID_DISK_IPS_ARCH_FULL

Message Meaning: IPS archive full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32037 - LOG_ID_DISK_LOG_FIRST_FULL

Message ID: 32037

Message Description: LOG_ID_DISK_LOG_FIRST_FULL

Message Meaning: Disk log full over first warning

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32038 - LOG_ID_LOG_ROLL_FORTICRON

Message ID: 32038

Message Description: LOG_ID_LOG_ROLL_FORTICRON

Message Meaning: Log rotation requested by forticron

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32039 - LOG_ID_VIEW_MEM_LOG_SUCC

Message ID: 32039**Message Description:** LOG_ID_VIEW_MEM_LOG_SUCC**Message Meaning:** Memory logs viewed successfully**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32040 - LOG_ID_REPORT_DELETED

Message ID: 32040

Message Description: LOG_ID_REPORT_DELETED

Message Meaning: Report deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32041 - LOG_ID_REPORT_DELETED_GUI

Message ID: 32041

Message Description: LOG_ID_REPORT_DELETED_GUI

Message Meaning: Report deleted from GUI

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32042 - LOG_ID_MEM_LOG_SECOND_FULL

Message ID: 32042

Message Description: LOG_ID_MEM_LOG_SECOND_FULL

Message Meaning: Memory log full over second warning level

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32043 - LOG_ID_MEM_LOG_FINAL_FULL

Message ID: 32043**Message Description:** LOG_ID_MEM_LOG_FINAL_FULL**Message Meaning:** Memory log full over final warning level**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32044 - LOG_ID_LOG_DELETE

Message ID: 32044

Message Description: LOG_ID_LOG_DELETE

Message Meaning: Log deleted by user

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
log	Log Name for Log Rotation	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32045 - LOG_ID_MGR_LIC_EXPIRE

Message ID: 32045

Message Description: LOG_ID_MGR_LIC_EXPIRE

Message Meaning: FortiGuard management service license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32046 - LOG_ID_SSL_CORRPUT_MAC

Message ID: 32046

Message Description: LOG_ID_SSL_CORRPUT_MAC

Message Meaning: SSL Message Authentication Code corrupted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32048 - LOG_ID_SCHEDULE_EXPIRE

Message ID: 32048

Message Description: LOG_ID_SCHEDULE_EXPIRE

Message Meaning: One time schedule expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32049 - LOG_ID_FC_EXPIRE

Message ID: 32049

Message Description: LOG_ID_FC_EXPIRE

Message Meaning: FortiCloud license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32050 - LOG_ID_POL_PKT_CAPTURE_FULL

Message ID: 32050

Message Description: LOG_ID_POL_PKT_CAPTURE_FULL

Message Meaning: Policy packet capture full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32051 - LOG_ID_LOG_UPLOAD

Message ID: 32051

Message Description: LOG_ID_LOG_UPLOAD

Message Meaning: Disk logs upload started

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
vd	Virtual Domain Name	string	32

32052 - LOG_ID_UPLOAD_RUN_SCRIPT

Message ID: 32052

Message Description: LOG_ID_UPLOAD_RUN_SCRIPT

Message Meaning: Upload and run a script

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32053 - LOG_ID_ADMIN_MTNER_LOGIN_SUCC

Message ID: 32053

Message Description: LOG_ID_ADMIN_MTNER_LOGIN_SUCC

Message Meaning: Admin monitor login successful

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32054 - LOG_ID_ADMIN_MTNER_LOGOUT

Message ID: 32054

Message Description: LOG_ID_ADMIN_MTNER_LOGOUT

Message Meaning: Admin monitor logout successful

Type: Event

Category: SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32055 - LOG_ID_FDS_QUOTA_WARN_WARNING

Message ID: 32055**Message Description:** LOG_ID_FDS_QUOTA_WARN_WARNING**Message Meaning:** FortiCloud quota full**Type:** Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32056 - LOG_ID_FDS_QUOTA_WARN_INFO

Message ID: 32056**Message Description:** LOG_ID_FDS_QUOTA_WARN_INFO**Message Meaning:** FortiCloud quota full**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32057 - LOG_ID_VIEW_FAZ_LOG_FAIL

Message ID: 32057

Message Description: LOG_ID_VIEW_FAZ_LOG_FAIL

Message Meaning: FortiAnalyzer log access failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32058 - LOG_ID_VIEW_FAZ_LOG_SUCC

Message ID: 32058

Message Description: LOG_ID_VIEW_FAZ_LOG_SUCC

Message Meaning: FortiAnalyzer logs viewed successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32095 - LOG_ID_GUI_CHG_SUB_MODULE

Message ID: 32095

Message Description: LOG_ID_GUI_CHG_SUB_MODULE

Message Meaning: Admin performed an action from GUI

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32097 - LOG_ID_DELETE_CAPTURE_PKT

Message ID: 32097

Message Description: LOG_ID_DELETE_CAPTURE_PKT

Message Meaning: Policy packet capture file deleted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32100 - LOG_ID_FORTI_TOKEN_SYNC

Message ID: 32100

Message Description: LOG_ID_FORTI_TOKEN_SYNC

Message Meaning: FortiToken synchronized

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32102 - LOG_ID_CHG_CONFIG

Message ID: 32102

Message Description: LOG_ID_CHG_CONFIG

Message Meaning: Configuration changed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Configuration Module Name	string	32
msg	Message Text	string	
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32103 - LOG_ID_NEW_FIRMWARE

Message ID: 32103

Message Description: LOG_ID_NEW_FIRMWARE

Message Meaning: New firmware available on FortiGuard

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32104 - LOG_ID_CHG_CONFIG_GUI

Message ID: 32104

Message Description: LOG_ID_CHG_CONFIG_GUI

Message Meaning: Configuration changed via GUI

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
module	Configuration Module Name	string	32
msg	Message Text	string	
submodule	Configuration Sub-Module Name	string	32
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE

Message ID: 32105

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE

Message Meaning: NTP server status changes to reachable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE

Message ID: 32106

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE

Message Meaning: NTP server status changes to resolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE

Message ID: 32107

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE

Message Meaning: NTP server status changes to unresolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE

Message ID: 32108

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE

Message Meaning: NTP server status changes to unreachable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32109 - LOG_ID_UPD_SIGN_AV_DB

Message ID: 32109

Message Description: LOG_ID_UPD_SIGN_AV_DB

Message Meaning: Updating virus database

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32110 - LOG_ID_UPD_SIGN_IPS_DB

Message ID: 32110

Message Description: LOG_ID_UPD_SIGN_IPS_DB

Message Meaning: IPS database updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32111 - LOG_ID_UPD_SIGN_AVIPS_DB

Message ID: 32111

Message Description: LOG_ID_UPD_SIGN_AVIPS_DB

Message Meaning: Virus and IPS database updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32113 - LOG_ID_UPD_SIGN_SRCVIS_DB

Message ID: 32113

Message Description: LOG_ID_UPD_SIGN_SRCVIS_DB

Message Meaning: SRC-VIS object updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32114 - LOG_ID_UPD_SIGN_GEOIP_DB

Message ID: 32114

Message Description: LOG_ID_UPD_SIGN_GEOIP_DB

Message Meaning: Geoip object updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32115 - LOG_ID_UPD_SIGN_SERVER_LIST

Message ID: 32115

Message Description: LOG_ID_UPD_SIGN_SERVER_LIST

Message Meaning: Server list updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE

Message ID: 32116

Message Description: LOG_ID_UPD_SIGN_AVPKG_FAILURE

Message Meaning: AV package update by SCP failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS

Message ID: 32117

Message Description: LOG_ID_UPD_SIGN_AVPKG_SUCCESS

Message Meaning: AV package update by SCP successful

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32118 - LOG_ID_UPD_ADMIN_AV_DB

Message ID: 32118

Message Description: LOG_ID_UPD_ADMIN_AV_DB

Message Meaning: AV updated by admin

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32119 - LOG_ID_UPD_SCANUNIT_AV_DB

Message ID: 32119

Message Description: LOG_ID_UPD_SCANUNIT_AV_DB

Message Meaning: AV database updated by scanunit

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32120 - LOG_ID_RPT_ADD_DATASET

Message ID: 32120

Message Description: LOG_ID_RPT_ADD_DATASET

Message Meaning: Report dataset added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32122 - LOG_ID_RPT_DEL_DATASET

Message ID: 32122

Message Description: LOG_ID_RPT_DEL_DATASET

Message Meaning: Report dataset deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32125 - LOG_ID_RPT_ADD_CHART

Message ID: 32125

Message Description: LOG_ID_RPT_ADD_CHART

Message Meaning: Report chart widget added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32126 - LOG_ID_RPT_DEL_CHART

Message ID: 32126

Message Description: LOG_ID_RPT_DEL_CHART

Message Meaning: Report chart widget deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32129 - LOG_ID_ADD_GUEST

Message ID: 32129

Message Description: LOG_ID_ADD_GUEST

Message Meaning: Guest user added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32130 - LOG_ID_CHG_USER

Message ID: 32130

Message Description: LOG_ID_CHG_USER

Message Meaning: User changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
new_status	New Status	string	512
old_status	Original Status	string	512
passwd	Password	string	20
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32131 - LOG_ID_DEL_GUEST

Message ID: 32131

Message Description: LOG_ID_DEL_GUEST

Message Meaning: Guest user deleted

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32132 - LOG_ID_ADD_USER

Message ID: 32132**Message Description:** LOG_ID_ADD_USER**Message Meaning:** Local user added**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32138 - LOG_ID_REBOOT

Message ID: 32138

Message Description: LOG_ID_REBOOT

Message Meaning: Device rebooted

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32140 - LOG_ID_TIME_USER_SETTING_CHG

Message ID: 32140

Message Description: LOG_ID_TIME_USER_SETTING_CHG

Message Meaning: Global time setting changed by user

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32141 - LOG_ID_TIME_NTP_SETTING_CHG

Message ID: 32141

Message Description: LOG_ID_TIME_NTP_SETTING_CHG

Message Meaning: Global time setting changed by NTP

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32142 - LOG_ID_BACKUP_CONF

Message ID: 32142

Message Description: LOG_ID_BACKUP_CONF

Message Meaning: System configuration backed up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32143 - LOG_ID_BACKUP_CONF_BY_SCP

Message ID: 32143

Message Description: LOG_ID_BACKUP_CONF_BY_SCP

Message Meaning: System configuration backed up by SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32144 - LOG_ID_BACKUP_CONF_ERROR

Message ID: 32144

Message Description: LOG_ID_BACKUP_CONF_ERROR

Message Meaning: System configuration backed up error

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32145 - LOG_ID_BACKUP_CONF_ALERT

Message ID: 32145

Message Description: LOG_ID_BACKUP_CONF_ALERT

Message Meaning: System configuration backed up alert

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32148 - LOG_ID_GET_CRL

Message ID: 32148

Message Description: LOG_ID_GET_CRL

Message Meaning: CRL update requested

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
crl		string	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32149 - LOG_ID_COMMAND_FAIL

Message ID: 32149

Message Description: LOG_ID_COMMAND_FAIL

Message Meaning: Command failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32151 - LOG_ID_ADD_IP6_LOCAL_POL

Message ID: 32151

Message Description: LOG_ID_ADD_IP6_LOCAL_POL

Message Meaning: IPv6 firewall local in policy added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32152 - LOG_ID_CHG_IP6_LOCAL_POL

Message ID: 32152

Message Description: LOG_ID_CHG_IP6_LOCAL_POL

Message Meaning: IPv6 firewall local in policy setting changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32153 - LOG_ID_DEL_IP6_LOCAL_POL

Message ID: 32153

Message Description: LOG_ID_DEL_IP6_LOCAL_POL

Message Meaning: IPv6 firewall local in policy deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32155 - LOG_ID_ACT_FTOKEN_REQ

Message ID: 32155

Message Description: LOG_ID_ACT_FTOKEN_REQ

Message Meaning: FortiToken activation requested

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32156 - LOG_ID_ACT_FTOKEN_SUCC

Message ID: 32156

Message Description: LOG_ID_ACT_FTOKEN_SUCC

Message Meaning: FortiToken activation successful

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32157 - LOG_ID_SYNC_FTOKEN_SUCC

Message ID: 32157

Message Description: LOG_ID_SYNC_FTOKEN_SUCC

Message Meaning: FortiToken resynchronized

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32158 - LOG_ID_SYNC_FTOKEN_FAIL

Message ID: 32158

Message Description: LOG_ID_SYNC_FTOKEN_FAIL

Message Meaning: FortiToken resynchronization failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32159 - LOG_ID_ACT_FTOKEN_FAIL

Message ID: 32159

Message Description: LOG_ID_ACT_FTOKEN_FAIL

Message Meaning: FortiToken activation failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
serialno	Serial Number	string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32160 - LOG_ID_FTM_PUSH_SUCC

Message ID: 32160

Message Description: LOG_ID_FTM_PUSH_SUCC

Message Meaning: FTM Push message sent success

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32161 - LOG_ID_FTM_PUSH_FAIL

Message ID: 32161

Message Description: LOG_ID_FTM_PUSH_FAIL

Message Meaning: FTM Push message sent failed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32168 - LOG_ID_REACH_VDOM_LIMIT

Message ID: 32168

Message Description: LOG_ID_REACH_VDOM_LIMIT

Message Meaning: Failed to add a new entry - VDOM limit reached

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32169 - LOG_ID_ALARM_DLP_DB

Message ID: 32169

Message Description: LOG_ID_ALARM_DLP_DB

Message Meaning: DLP database space alarm

Type: Event

Category: SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32170 - LOG_ID_ALARM_MSG

Message ID: 32170**Message Description:** LOG_ID_ALARM_MSG**Message Meaning:** Alarm created**Type:** Event**Category:** SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
groupid	User Group ID	uint32	10

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32171 - LOG_ID_ALARM_ACK

Message ID: 32171

Message Description: LOG_ID_ALARM_ACK

Message Meaning: Alarm acknowledged

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
acktime	Alarm Acknowledge Time	string	24
action	Action	string	32
alarmid	Alarm ID	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32172 - LOG_ID_ADD_IP4_LOCAL_POL

Message ID: 32172

Message Description: LOG_ID_ADD_IP4_LOCAL_POL

Message Meaning: IPv4 firewall local in policy added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32173 - LOG_ID_CHG_IP4_LOCAL_POL

Message ID: 32173

Message Description: LOG_ID_CHG_IP4_LOCAL_POL

Message Meaning: IPv4 firewall local in policy's setting changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32174 - LOG_ID_DEL_IP4_LOCAL_POL

Message ID: 32174

Message Description: LOG_ID_DEL_IP4_LOCAL_POL

Message Meaning: IPv4 firewall local in policy deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
act		string	16
daddr		string	80
date	Date	string	10
devid	Device ID	string	16
dintf		string	36
eventtime		uint64	20
iptype		string	16
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32190 - LOG_ID_UPT_INVALID_IMG

Message ID: 32190

Message Description: LOG_ID_UPT_INVALID_IMG

Message Meaning: Invalid image loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32191 - LOG_ID_UPT_INVALID_IMG_CC

Message ID: 32191

Message Description: LOG_ID_UPT_INVALID_IMG_CC

Message Meaning: Image with invalid CC signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32192 - LOG_ID_UPT_INVALID_IMG_RSA

Message ID: 32192

Message Description: LOG_ID_UPT_INVALID_IMG_RSA

Message Meaning: Image with invalid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32193 - LOG_ID_UPT_IMG_RSA

Message ID: 32193

Message Description: LOG_ID_UPT_IMG_RSA

Message Meaning: Image with valid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32194 - LOG_ID_UPT_IMG_FAIL

Message ID: 32194

Message Description: LOG_ID_UPT_IMG_FAIL

Message Meaning: System upgrade failed due to file operation failure

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32199 - LOG_ID_RESTORE_IMG_USB

Message ID: 32199

Message Description: LOG_ID_RESTORE_IMG_USB

Message Meaning: Image restored from USB

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32200 - LOG_ID_SHUTDOWN

Message ID: 32200

Message Description: LOG_ID_SHUTDOWN

Message Meaning: Device shutdown

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32201 - LOG_ID_LOAD_IMG_SUCC

Message ID: 32201

Message Description: LOG_ID_LOAD_IMG_SUCC

Message Meaning: Image loaded successfully

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32202 - LOG_ID_RESTORE_IMG

Message ID: 32202

Message Description: LOG_ID_RESTORE_IMG

Message Meaning: Image restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32203 - LOG_ID_RESTORE_CONF

Message ID: 32203

Message Description: LOG_ID_RESTORE_CONF

Message Meaning: Configuration restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32204 - LOG_ID_RESTORE_FGD_SVR

Message ID: 32204

Message Description: LOG_ID_RESTORE_FGD_SVR

Message Meaning: FortiGuard service restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32205 - LOG_ID_RESTORE_VDOM_LIC

Message ID: 32205

Message Description: LOG_ID_RESTORE_VDOM_LIC

Message Meaning: VM license restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32206 - LOG_ID_RESTORE_SCRIPT

Message ID: 32206

Message Description: LOG_ID_RESTORE_SCRIPT

Message Meaning: Script restored from management station

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32207 - LOG_ID_RETRIEVE_CONF_LIST

Message ID: 32207

Message Description: LOG_ID_RETRIEVE_CONF_LIST

Message Meaning: Configuration list retrieval failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32208 - LOG_ID_IMP_PKCS12_CERT

Message ID: 32208

Message Description: LOG_ID_IMP_PKCS12_CERT

Message Meaning: PKCS12 certificate imported

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32209 - LOG_ID_RESTORE_USR_DEF_IPS

Message ID: 32209

Message Description: LOG_ID_RESTORE_USR_DEF_IPS

Message Meaning: IPS custom signatures restored

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32210 - LOG_ID_BACKUP_IMG_SUCC

Message ID: 32210

Message Description: LOG_ID_BACKUP_IMG_SUCC

Message Meaning: Firmware image backed up successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32211 - LOG_ID_UPLOAD_REVISION

Message ID: 32211

Message Description: LOG_ID_UPLOAD_REVISION

Message Meaning: Revision uploaded to flash disk

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32212 - LOG_ID_DEL_REVISION

Message ID: 32212

Message Description: LOG_ID_DEL_REVISION

Message Meaning: Revision database deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32213 - LOG_ID_RESTORE_TEMPLATE

Message ID: 32213

Message Description: LOG_ID_RESTORE_TEMPLATE

Message Meaning: Template restored

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32214 - LOG_ID_RESTORE_FILE

Message ID: 32214

Message Description: LOG_ID_RESTORE_FILE

Message Meaning: File restore failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32215 - LOG_ID_UPT_IMG

Message ID: 32215

Message Description: LOG_ID_UPT_IMG

Message Meaning: Image updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32217 - LOG_ID_UPD_IPS

Message ID: 32217

Message Description: LOG_ID_UPD_IPS

Message Meaning: IPS database - Admin update successful

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32218 - LOG_ID_UPD_DLP

Message ID: 32218

Message Description: LOG_ID_UPD_DLP

Message Meaning: DLP fingerprint database update via SCP failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32219 - LOG_ID_BACKUP_OUTPUT

Message ID: 32219

Message Description: LOG_ID_BACKUP_OUTPUT

Message Meaning: Error output backup via SCP successful

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32220 - LOG_ID_BACKUP_COMMAND

Message ID: 32220

Message Description: LOG_ID_BACKUP_COMMAND

Message Meaning: Batch mode command output backup via SCP successful

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32221 - LOG_ID_UPD_VDOM_LIC

Message ID: 32221

Message Description: LOG_ID_UPD_VDOM_LIC

Message Meaning: VM license installed via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32222 - LOG_ID_GLB_SETTING_CHG

Message ID: 32222

Message Description: LOG_ID_GLB_SETTING_CHG

Message Meaning: Global setting changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
field		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
new_value	New Virtual Domain Name	string	128
old_value	Original Virtual Domain name	string	128
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32223 - LOG_ID_BACKUP_USER_DEF_IPS

Message ID: 32223

Message Description: LOG_ID_BACKUP_USER_DEF_IPS

Message Meaning: IPS custom signatures backup success

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32224 - LOG_ID_BACKUP_DISK_LOG

Message ID: 32224

Message Description: LOG_ID_BACKUP_DISK_LOG

Message Meaning: Disk logs backed up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
file	File Name for Generated Report?	string	256
hash	Hash Value of Downloaded File	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32225 - LOG_ID_DEL_ALL_REVISION

Message ID: 32225

Message Description: LOG_ID_DEL_ALL_REVISION

Message Meaning: Revision database reset due to data corruption

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32226 - LOG_ID_LOAD_IMG_FAIL

Message ID: 32226

Message Description: LOG_ID_LOAD_IMG_FAIL

Message Meaning: Image failed to load

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32227 - LOG_ID_UPD_DLP_FAIL

Message ID: 32227

Message Description: LOG_ID_UPD_DLP_FAIL

Message Meaning: DLP fingerprint database failed to update by SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG

Message ID: 32228

Message Description: LOG_ID_LOAD_IMG_FAIL_WRONG_IMG

Message Meaning: Firmware image loaded incorrect

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA

Message ID: 32229

Message Description: LOG_ID_LOAD_IMG_FAIL_NO_RSA

Message Meaning: Firmware image without valid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA

Message ID: 32230

Message Description: LOG_ID_LOAD_IMG_FAIL_INVALID_RSA

Message Meaning: Firmware image with invalid RSA signature loaded

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32231 - LOG_ID_RESTORE_FGD_SVR_FAIL

Message ID: 32231**Message Description:** LOG_ID_RESTORE_FGD_SVR_FAIL**Message Meaning:** FortiGuard service failed to restore**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL

Message ID: 32232

Message Description: LOG_ID_RESTORE_VDOM_LIC_FAIL

Message Meaning: VM license failed to restore

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32233 - LOG_ID_BACKUP_IMG_FAIL

Message ID: 32233

Message Description: LOG_ID_BACKUP_IMG_FAIL

Message Meaning: Firmware image backup failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32234 - LOG_ID_RESTORE_IMG_INVALID_CC

Message ID: 32234

Message Description: LOG_ID_RESTORE_IMG_INVALID_CC

Message Meaning: Image with invalid CC signature restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32235 - LOG_ID_RESTORE_IMG_FORTIGUARD

Message ID: 32235

Message Description: LOG_ID_RESTORE_IMG_FORTIGUARD

Message Meaning: Image restored from FortiGuard Management

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

32236 - LOG_ID_BACKUP_MEM_LOG

Message ID: 32236

Message Description: LOG_ID_BACKUP_MEM_LOG

Message Meaning: Memory logs backed up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32237 - LOG_ID_BACKUP_MEM_LOG_FAIL

Message ID: 32237

Message Description: LOG_ID_BACKUP_MEM_LOG_FAIL

Message Meaning: Memory logs failed to back up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32238 - LOG_ID_BACKUP_DISK_LOG_FAIL

Message ID: 32238

Message Description: LOG_ID_BACKUP_DISK_LOG_FAIL

Message Meaning: Disk logs failed to back up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32239 - LOG_ID_BACKUP_DISK_LOG_USB

Message ID: 32239

Message Description: LOG_ID_BACKUP_DISK_LOG_USB

Message Meaning: Disk logs backed up to USB

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32240 - LOG_ID_SYS_USB_MODE

Message ID: 32240

Message Description: LOG_ID_SYS_USB_MODE

Message Meaning: System operating in USB mode

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL

Message ID: 32241

Message Description: LOG_ID_BACKUP_DISK_LOG_USB_FAIL

Message Meaning: Disk logs failed to back up to USB

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32242 - LOG_ID_UPD_VDOM_LIC_FAIL

Message ID: 32242

Message Description: LOG_ID_UPD_VDOM_LIC_FAIL

Message Meaning: VM license failed to install via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32243 - LOG_ID_UPD_IPS_SCP

Message ID: 32243

Message Description: LOG_ID_UPD_IPS_SCP

Message Meaning: IPS package updated via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32244 - LOG_ID_UPD_IPS_SCP_FAIL

Message ID: 32244

Message Description: LOG_ID_UPD_IPS_SCP_FAIL

Message Meaning: IPS package failed to update via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL

Message ID: 32245

Message Description: LOG_ID_BACKUP_USER_DEF_IPS_FAIL

Message Meaning: IPS custom signatures backup failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32246 - LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL

Message ID: 32246

Message Description: LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL

Message Meaning: IPS custom signatures restored critical

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32247 - LOG_ID_SSH_NEGOTIATION_FAILURE

Message ID: 32247

Message Description: LOG_ID_SSH_NEGOTIATION_FAILURE

Message Meaning: SSH protocol cannot be negotiated

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
addr	IP Address	string	80
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32252 - LOG_ID_FACTORY_RESET

Message ID: 32252

Message Description: LOG_ID_FACTORY_RESET

Message Meaning: Factory settings reset

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32253 - LOG_ID_FORMAT_RAID

Message ID: 32253

Message Description: LOG_ID_FORMAT_RAID

Message Meaning: RAID disk formatted

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32254 - LOG_ID_ENABLE_RAID

Message ID: 32254

Message Description: LOG_ID_ENABLE_RAID

Message Meaning: RAID enabled

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

32255 - LOG_ID_DISABLE_RAID

Message ID: 32255

Message Description: LOG_ID_DISABLE_RAID

Message Meaning: RAID disabled

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32300 - LOG_ID_UPLOAD_RPT_IMG

Message ID: 32300

Message Description: LOG_ID_UPLOAD_RPT_IMG

Message Meaning: Report image file uploaded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32301 - LOG_ID_ADD_VDOM

Message ID: 32301

Message Description: LOG_ID_ADD_VDOM

Message Meaning: VDOM added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32302 - LOG_ID_DEL_VDOM

Message ID: 32302

Message Description: LOG_ID_DEL_VDOM

Message Meaning: VDOM deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32400 - LOG_ID_CONF_CHG

Message ID: 32400

Message Description: LOG_ID_CONF_CHG

Message Meaning: Configuration changed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32545 - LOG_ID_SYS_RESTART

Message ID: 32545

Message Description: LOG_ID_SYS_RESTART

Message Meaning: Scheduled daily reboot started

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32546 - LOG_ID_APPLICATION_CRASH

Message ID: 32546

Message Description: LOG_ID_APPLICATION_CRASH

Message Meaning: Application crashed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32547 - LOG_ID_AUTOSCRIPT_START

Message ID: 32547

Message Description: LOG_ID_AUTOSCRIPT_START

Message Meaning: Autoscript start

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32548 - LOG_ID_AUTOSCRIPT_STOP

Message ID: 32548

Message Description: LOG_ID_AUTOSCRIPT_STOP

Message Meaning: Autoscript stop

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32549 - LOG_ID_AUTOSCRIPT_STOP_AUTO

Message ID: 32549

Message Description: LOG_ID_AUTOSCRIPT_STOP_AUTO

Message Meaning: Autoscript stop automatically

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32550 - LOG_ID_AUTOSCRIPT_DELETE_RSLT

Message ID: 32550

Message Description: LOG_ID_AUTOSCRIPT_DELETE_RSLT

Message Meaning: Autoscript delete result

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32551 - LOG_ID_AUTOSCRIPT_BACKUP_RSLT

Message ID: 32551

Message Description: LOG_ID_AUTOSCRIPT_BACKUP_RSLT

Message Meaning: Autoscript backup result

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32552 - LOG_ID_AUTOSCRIPT_CHECK_STATUS

Message ID: 32552

Message Description: LOG_ID_AUTOSCRIPT_CHECK_STATUS

Message Meaning: Autoscrypt check status

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32553 - LOG_ID_AUTOSCRIPT_STOP_REACH_LIMIT

Message ID: 32553

Message Description: LOG_ID_AUTOSCRIPT_STOP_REACH_LIMIT

Message Meaning: Autoscript stop due to limit reached

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT

Message ID: 32561

Message Description: LOG_ID_ADMIN_LOGOUT_DISCONNECT

Message Meaning: Admin disconnected

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32562 - LOG_ID_STORE_CONF_FAIL_SPACE

Message ID: 32562

Message Description: LOG_ID_STORE_CONF_FAIL_SPACE

Message Meaning: Store config failed - not enough flash space

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32564 - LOG_ID_RESTORE_CONF_FAIL

Message ID: 32564

Message Description: LOG_ID_RESTORE_CONF_FAIL

Message Meaning: Configuration failed to restore

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32565 - LOG_ID_RESTORE_CONF_BY_MGMT

Message ID: 32565

Message Description: LOG_ID_RESTORE_CONF_BY_MGMT

Message Meaning: Configuration restored from management station

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32566 - LOG_ID_RESTORE_CONF_BY_SCP

Message ID: 32566

Message Description: LOG_ID_RESTORE_CONF_BY_SCP

Message Meaning: Configuration restored by SCP

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32567 - LOG_ID_RESTORE_CONF_BY_USB

Message ID: 32567

Message Description: LOG_ID_RESTORE_CONF_BY_USB

Message Meaning: Configuration restored by USB

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32568 - LOG_ID_DEL_REVISION_DB

Message ID: 32568

Message Description: LOG_ID_DEL_REVISION_DB

Message Meaning: Revision Database deletion

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

32569 - LOG_ID_FSW_SWITCH_LOG_EVENT

Message ID: 32569

Message Description: LOG_ID_FSW_SWITCH_LOG_EVENT

Message Meaning: Switch-Controller

Type: Event

Category: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32570 - LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT

Message ID: 32570

Message Description: LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT

Message Meaning: Admin monitor disconnected

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method		string	64
msg	Message Text	string	
reason	Reason	string	256
sn	Serial Number	string	64
srcip	Source IP	ip	39
state		string	64
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32571 - LOG_ID_RESTORE_CONF_FAIL_WARNING

Message ID: 32571

Message Description: LOG_ID_RESTORE_CONF_FAIL_WARNING

Message Meaning: Configuration failed to restore

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32601 - LOG_ID_FGT_SWITCH_LOG_DISCOVER

Message ID: 32601

Message Description: LOG_ID_FGT_SWITCH_LOG_DISCOVER

Message Meaning: Switch-Controller Discover

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32602 - LOG_ID_FGT_SWITCH_LOG_AUTH

Message ID: 32602

Message Description: LOG_ID_FGT_SWITCH_LOG_AUTH

Message Meaning: Switch-Controller Authorize

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32603 - LOG_ID_FGT_SWITCH_LOG_DEAUTH

Message ID: 32603

Message Description: LOG_ID_FGT_SWITCH_LOG_DEAUTH

Message Meaning: Switch-Controller De-Authorize

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32604 - LOG_ID_FGT_SWITCH_LOG_DELETE

Message ID: 32604

Message Description: LOG_ID_FGT_SWITCH_LOG_DELETE

Message Meaning: Switch-Controller Delete

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32605 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP

Message ID: 32605

Message Description: LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP

Message Meaning: Switch-Controller Tunnel Up

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32606 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN

Message ID: 32606

Message Description: LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN

Message Meaning: Switch-Controller Tunnel Down

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32607 - LOG_ID_FGT_SWITCH_PUSH_IMAGE

Message ID: 32607

Message Description: LOG_ID_FGT_SWITCH_PUSH_IMAGE

Message Meaning: Image push to FortiSwitch

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32608 - LOG_ID_FGT_SWITCH_STAGE_IMAGE

Message ID: 32608

Message Description: LOG_ID_FGT_SWITCH_STAGE_IMAGE

Message Meaning: Image stage to FortiSwitch

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32693 - LOG_ID_FGT_SWITCH_GROUP_SWC

Message ID: 32693

Message Description: LOG_ID_FGT_SWITCH_GROUP_SWC

Message Meaning: FortiSwitch switch controller

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32694 - LOG_ID_FGT_SWITCH_GROUP_POE

Message ID: 32694

Message Description: LOG_ID_FGT_SWITCH_GROUP_POE

Message Meaning: FortiSwitch POE

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32695 - LOG_ID_FGT_SWITCH_GROUP_LINK

Message ID: 32695**Message Description:** LOG_ID_FGT_SWITCH_GROUP_LINK**Message Meaning:** FortiSwitch link**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	

Log Field Name	Description	Data Type	Length
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32696 - LOG_ID_FGT_SWITCH_GROUP_STP

Message ID: 32696

Message Description: LOG_ID_FGT_SWITCH_GROUP_STP

Message Meaning: FortiSwitch spanning Tree

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32697 - LOG_ID_FGT_SWITCH_GROUP_SWITCH

Message ID: 32697

Message Description: LOG_ID_FGT_SWITCH_GROUP_SWITCH

Message Meaning: FortiSwitch switch

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32698 - LOG_ID_FGT_SWITCH_GROUP_ROUTER

Message ID: 32698

Message Description: LOG_ID_FGT_SWITCH_GROUP_ROUTER

Message Meaning: FortiSwitch router

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

32699 - LOG_ID_FGT_SWITCH_GROUP_SYSTEM

Message ID: 32699

Message Description: LOG_ID_FGT_SWITCH_GROUP_SYSTEM

Message Meaning: FortiSwitch system

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

35001 - LOG_ID_HA_SYNC_VIRDB

Message ID: 35001

Message Description: LOG_ID_HA_SYNC_VIRDB

Message Meaning: HA slave synchronized Virus database

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35002 - LOG_ID_HA_SYNC_ETDB

Message ID: 35002

Message Description: LOG_ID_HA_SYNC_ETDB

Message Meaning: HA slave synchronized Extended database

Type: Event

Category: HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35003 - LOG_ID_HA_SYNC_EXDB

Message ID: 35003**Message Description:** LOG_ID_HA_SYNC_EXDB**Message Meaning:** HA slave synchronized Extended database**Type:** Event**Category:** HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35004 - LOG_ID_HA_SYNC_FLDB

Message ID: 35004

Message Description: LOG_ID_HA_SYNC_FLDB

Message Meaning: HA slave synchronized flddb

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35005 - LOG_ID_HA_SYNC_IPS

Message ID: 35005

Message Description: LOG_ID_HA_SYNC_IPS

Message Meaning: HA slave synchronized IDS package

Type: Event

Category: HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35007 - LOG_ID_HA_SYNC_AV

Message ID: 35007**Message Description:** LOG_ID_HA_SYNC_AV**Message Meaning:** HA slave synchronized AntiVirus package**Type:** Event**Category:** HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35009 - LOG_ID_HA_SYNC_CID

Message ID: 35009

Message Description: LOG_ID_HA_SYNC_CID

Message Meaning: HA slave synchronized CID package

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35010 - LOG_ID_HA_SYNC_UWDB

Message ID: 35010

Message Description: LOG_ID_HA_SYNC_UWDB

Message Meaning: HA slave synchronization failed

Type: Event

Category: HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35011 - LOG_ID_HA_SYNC_FAIL

Message ID: 35011**Message Description:** LOG_ID_HA_SYNC_FAIL**Message Meaning:** HA slave synchronization failed**Type:** Event**Category:** HA**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

35012 - LOG_ID_CONF_SYNC_FAIL

Message ID: 35012

Message Description: LOG_ID_CONF_SYNC_FAIL

Message Meaning: CONFSYNC slave sync failed

Type: Event

Category: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

36880 - LOG_ID_EVENT_SYSTEM_MAC_HOST_STORE_LIMIT

Message ID: 36880

Message Description: LOG_ID_EVENT_SYSTEM_MAC_HOST_STORE_LIMIT

Message Meaning: Device detection storage limit reached

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

36881 - LOG_ID_EVENT_SYSTEM_CFG_REVERT

Message ID: 36881**Message Description:** LOG_ID_EVENT_SYSTEM_CFG_REVERT**Message Meaning:** Configuration reverted due to cfg-revert-timeout**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

36882 - LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED

Message ID: 36882

Message Description: LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED

Message Meaning: Configuration manually saved

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

37120 - MESGID_NEG_GENERIC_P1_NOTIF

Message ID: 37120

Message Description: MESGID_NEG_GENERIC_P1_NOTIF

Message Meaning: Negotiate IPsec phase 1

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37121 - MSGID_NEG_GENERIC_P1_ERROR

Message ID: 37121

Message Description: MSGID_NEG_GENERIC_P1_ERROR

Message Meaning: Negotiate IPsec phase 1

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37122 - MESGID_NEG_GENERIC_P2_NOTIF

Message ID: 37122

Message Description: MESGID_NEG_GENERIC_P2_NOTIF

Message Meaning: Negotiate IPsec phase 2

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37123 - MESGID_NEG_GENERIC_P2_ERROR

Message ID: 37123

Message Description: MESGID_NEG_GENERIC_P2_ERROR

Message Meaning: Negotiate IPsec phase 2

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37124 - MESGID_NEG_I_P1_ERROR

Message ID: 37124

Message Description: MESGID_NEG_I_P1_ERROR

Message Meaning: IPsec phase 1 error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37125 - MESSGID_NEG_I_P2_ERROR

Message ID: 37125

Message Description: MESSGID_NEG_I_P2_ERROR

Message Meaning: IPsec phase 2 error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37126 - MESGID_NEG_NO_STATE_ERROR

Message ID: 37126

Message Description: MESGID_NEG_NO_STATE_ERROR

Message Meaning: IPsec no state error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37127 - MESGID_NEG_PROGRESS_P1_NOTIF

Message ID: 37127

Message Description: MESGID_NEG_PROGRESS_P1_NOTIF

Message Meaning: Progress IPsec phase 1

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
group	User Name Group	string	64
init		string	6
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37128 - MESGID_NEG_PROGRESS_P1_ERROR

Message ID: 37128

Message Description: MESGID_NEG_PROGRESS_P1_ERROR

Message Meaning: Progress IPsec phase 1

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37129 - MESGID_NEG_PROGRESS_P2_NOTIF

Message ID: 37129

Message Description: MESGID_NEG_PROGRESS_P2_NOTIF

Message Meaning: Progress IPsec phase 2

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37130 - MESGID_NEG_PROGRESS_P2_ERROR

Message ID: 37130

Message Description: MESGID_NEG_PROGRESS_P2_ERROR

Message Meaning: Progress IPsec phase 2

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
mode	Mode	string	12
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
stage		uint8	3
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37131 - MESGID_ESP_ERROR

Message ID: 37131

Message Description: MESGID_ESP_ERROR

Message Meaning: IPsec ESP

Type: Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37132 - MESGID_ESP_CRITICAL

Message ID: 37132

Message Description: MESGID_ESP_CRITICAL

Message Meaning: IPsec ESP

Type: Event

Category: VPN

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16

Log Field Name	Description	Data Type	Length
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37133 - MESGID_INSTALL_SA

Message ID: 37133

Message Description: MESGID_INSTALL_SA

Message Meaning: IPsec SA installed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39

Log Field Name	Description	Data Type	Length
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37134 - MESGID_DELETE_P1_SA

Message ID: 37134

Message Description: MESGID_DELETE_P1_SA

Message Meaning: IPsec phase 1 SA deleted

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37135 - MESGID_DELETE_P2_SA

Message ID: 37135

Message Description: MESGID_DELETE_P2_SA

Message Meaning: IPsec phase 2 SA deleted

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37136 - MESGID_DPD_FAILURE

Message ID: 37136

Message Description: MESGID_DPD_FAILURE**Message Meaning:** IPsec DPD failed**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37137 - MESGID_CONN_FAILURE

Message ID: 37137

Message Description: MESGID_CONN_FAILURE

Message Meaning: IPsec connection failed

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37138 - MESGID_CONN_UPDOWN

Message ID: 37138

Message Description: MESGID_CONN_UPDOWN

Message Meaning: IPsec connection status changed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37139 - MESGID_P2_UPDOWN

Message ID: 37139

Message Description: MESGID_P2_UPDOWN

Message Meaning: IPsec phase 2 status changed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
phase2_name	Phase 2 Name	string	128
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37141 - MESGID_CONN_STATS

Message ID: 37141

Message Description: MESGID_CONN_STATS

Message Meaning: IPsec tunnel statistics

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37184 - MESGID_NEG_GENERIC_P1_NOTIF_IKEV2

Message ID: 37184

Message Description: MESGID_NEG_GENERIC_P1_NOTIF_IKEV2

Message Meaning: Negotiate IPsec phase 1

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37185 - MESGID_NEG_GENERIC_P1_ERROR_IKEV2

Message ID: 37185

Message Description: MESGID_NEG_GENERIC_P1_ERROR_IKEV2

Message Meaning: Negotiate IPsec phase 1

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
peer_notif	Peer Notification	string	25
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37186 - MESGID_NEG_GENERIC_P2_NOTIF_IKEV2

Message ID: 37186

Message Description: MESGID_NEG_GENERIC_P2_NOTIF_IKEV2

Message Meaning: Negotiate IPsec phase 2

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37187 - MESGID_NEG_GENERIC_P2_ERROR_IKEV2

Message ID: 37187

Message Description: MESGID_NEG_GENERIC_P2_ERROR_IKEV2

Message Meaning: Negotiate IPsec phase 2

Type: Event

Category: VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
espauth	ESP Authentication	string	17
esptransform	ESP Transform	string	11
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37188 - MSGID_NEG_I_P1_ERROR_IKEV2

Message ID: 37188

Message Description: MSGID_NEG_I_P1_ERROR_IKEV2

Message Meaning: IPsec phase 1 error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37189 - MESGID_NEG_I_P2_ERROR_IKEV2

Message ID: 37189

Message Description: MESGID_NEG_I_P2_ERROR_IKEV2

Message Meaning: IPsec phase 2 error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37190 - MESGID_NEG_NO_STATE_ERROR_IKEV2

Message ID: 37190

Message Description: MESGID_NEG_NO_STATE_ERROR_IKEV2

Message Meaning: IPsec no state error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
reason	Reason	string	256
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37191 - MESGID_NEG_PROGRESS_P1_NOTIF_IKEV2

Message ID: 37191

Message Description: MESGID_NEG_PROGRESS_P1_NOTIF_IKEV2

Message Meaning: Progress IPsec phase 1

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37192 - MESGID_NEG_PROGRESS_P1_ERROR_IKEV2

Message ID: 37192

Message Description: MESGID_NEG_PROGRESS_P1_ERROR_IKEV2

Message Meaning: Progress IPsec phase 1

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37193 - MESGID_NEG_PROGRESS_P2_NOTIF_IKEV2

Message ID: 37193

Message Description: MESGID_NEG_PROGRESS_P2_NOTIF_IKEV2

Message Meaning: Progress IPsec phase 2

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37194 - MESGID_NEG_PROGRESS_P2_ERROR_IKEV2

Message ID: 37194

Message Description: MESGID_NEG_PROGRESS_P2_ERROR_IKEV2

Message Meaning: Progress IPsec phase 2

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
dir	Direction	string	8
eventtime		uint64	20
exch	In SPI	string	14
group	User Name Group	string	64
init		string	6
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
result	Result	string	31
role	Role	string	9
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
version		string	64

Log Field Name	Description	Data Type	Length
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37195 - MESGID_ESP_ERROR_IKEV2

Message ID: 37195

Message Description: MESGID_ESP_ERROR_IKEV2

Message Meaning: IPsec ESP

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5

Log Field Name	Description	Data Type	Length
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37196 - MESGID_ESP_CRITICAL_IKEV2

Message ID: 37196

Message Description: MESGID_ESP_CRITICAL_IKEV2

Message Meaning: IPsec ESP

Type: Event

Category: VPN

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
error_num	Error Number	string	53
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
seq	Sequence	string	16
spi		string	16
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37197 - MESGID_INSTALL_SA_IKEV2

Message ID: 37197

Message Description: MESGID_INSTALL_SA_IKEV2

Message Meaning: IPsec SA installed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
role	Role	string	9
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37198 - MESGID_DELETE_P1_SA_IKEV2

Message ID: 37198

Message Description: MSGID_DELETE_P1_SA_IKEV2

Message Meaning: IPsec phase 1 SA deleted

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37199 - MESGID_DELETE_P2_SA_IKEV2

Message ID: 37199

Message Description: MESGID_DELETE_P2_SA_IKEV2

Message Meaning: IPsec phase 2 SA deleted

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
in_spi		string	16
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
out_spi	Out SPI	string	16
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37200 - MESGID_DPD_FAILURE_IKEV2

Message ID: 37200

Message Description: MESGID_DPD_FAILURE_IKEV2

Message Meaning: IPsec DPD failed

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37201 - MESGID_CONN_FAILURE_IKEV2

Message ID: 37201

Message Description: MESGID_CONN_FAILURE_IKEV2

Message Meaning: IPsec connection failed

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37202 - MESGID_CONN_UPDOWN_IKEV2

Message ID: 37202

Message Description: MESGID_CONN_UPDOWN_IKEV2

Message Meaning: IPsec connection status changed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37203 - MESGID_P2_UPDOWN_IKEV2

Message ID: 37203

Message Description: MESGID_P2_UPDOWN_IKEV2

Message Meaning: IPsec phase 2 status changed

Type: Event**Category:** VPN**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
outintf	Out interface	string	32
phase2_name	Phase 2 Name	string	128
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37204 - MESGID_CONN_STATS_IKEV2

Message ID: 37204

Message Description: MESGID_CONN_STATS_IKEV2

Message Meaning: IPsec tunnel statistics

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
assignip	Assigned IP Address	ip	39
cookies	Cookie	string	64
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
locip	Local IP	ip	39
locport	Local Port	uint16	5
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
outintf	Out interface	string	32
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
remport	Remote Port	uint16	5
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vpntunnel	IPsec Vpn Tunnel Name	string	128
xauthgroup	XAuth Group Name	string	128
xauthuser	XAuth User Name	string	256

37888 - MESGID_HA_GROUP_DELETE

Message ID: 37888

Message Description: MESGID_HA_GROUP_DELETE

Message Meaning: Specified HA group was deleted

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37889 - MESSAGES_VC_DELETE

Message ID: 37889

Message Description: MESSAGES_VC_DELETE

Message Meaning: Virtual cluster deleted

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37890 - MESSAGES_VC_MOVE_VDOM

Message ID: 37890

Message Description: MESSAGES_VC_MOVE_VDOM

Message Meaning: Virtual cluster VDOM moved

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
from_vcluster	source virtual cluster number	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vdname	vdom name	string	32

37891 - MESGID_VC_ADD_VDOM

Message ID: 37891

Message Description: MESGID_VC_ADD_VDOM

Message Meaning: Virtual cluster VDOM added

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
to_vcluster	destination virtual cluster number	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vdname	vdom name	string	32

37892 - MESGID_VC_MOVE_MEMB_STATE

Message ID: 37892

Message Description: MESGID_VC_MOVE_MEMB_STATE

Message Meaning: Virtual cluster member state moved

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster_member		uint32	10
vcluster_state		string	7
vd	Virtual Domain Name	string	32

37893 - MSGID_VC_DETECT_MEMB_DEAD

Message ID: 37893

Message Description: MSGID_VC_DETECT_MEMB_DEAD

Message Meaning: Virtual cluster member dead

Type: Event

Category: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37894 - MSGID_VC_DETECT_MEMB_JOIN

Message ID: 37894

Message Description: MSGID_VC_DETECT_MEMB_JOIN

Message Meaning: Virtual cluster member joined

Type: Event

Category: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha_group	HA Group Number - can be 1 - 256	uint8	3
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37895 - MESGID_VC_ADD_HADEV

Message ID: 37895

Message Description: MESGID_VC_ADD_HADEV

Message Meaning: Virtual cluster added HA device interface

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37896 - MESGID_VC_DEL_HADEV

Message ID: 37896

Message Description: MESGID_VC_DEL_HADEV

Message Meaning: Virtual cluster deleted HA device interface

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vcluster	virtual cluster id	uint32	10
vd	Virtual Domain Name	string	32

37897 - MESSGID_HADEV_READY

Message ID: 37897

Message Description: MESSGID_HADEV_READY

Message Meaning: HA device interface ready

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37898 - MESSGID_HADEV_FAIL

Message ID: 37898

Message Description: MESSGID_HADEV_FAIL

Message Meaning: HA device interface failed

Type: Event

Category: HA

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37899 - MESGID_HADEV_PEERINFO

Message ID: 37899

Message Description: MESGID_HADEV_PEERINFO

Message Meaning: HA device interface peer information

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37900 - MESGID_HBDEV_DELETE

Message ID: 37900

Message Description: MESGID_HBDEV_DELETE

Message Meaning: Heartbeat device interface deleted

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37901 - MESGID_HBDEV_DOWN

Message ID: 37901

Message Description: MESGID_HBDEV_DOWN

Message Meaning: Heartbeat device interface down

Type: Event

Category: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
hbdn_reason	heartbeat down reason	string	18
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37902 - MESGID_HBDEV_UP

Message ID: 37902

Message Description: MESGID_HBDEV_UP

Message Meaning: Heartbeat device interface up

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devintfname	HA device Interface Name	string	32
eventtime		uint64	20
ha_role	The HA role in the cluster	string	6
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37903 - MESGID_SYNC_STATUS

Message ID: 37903

Message Description: MESGID_SYNC_STATUS

Message Meaning: Synchronization status with master

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
sync_status	The sync status with the master	string	11
sync_type	The sync type with the master	string	14
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37904 - MESGID_HA_ACTIVITY

Message ID: 37904

Message Description: MESGID_HA_ACTIVITY

Message Meaning: Device set as HA master

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37905 - MESGID_HA_ENABLE_SET_AS_MASTER

Message ID: 37905

Message Description: MESGID_HA_ENABLE_SET_AS_MASTER

Message Meaning: Admin user set the current device as HA master

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37906 - MESGID_HA_DISABLE_SET_AS_MASTER

Message ID: 37906

Message Description: MESGID_HA_DISABLE_SET_AS_MASTER

Message Meaning: Admin user unset the current device as HA master

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37907 - MESGID_VLAN_HB_UP

Message ID: 37907

Message Description: MESGID_VLAN_HB_UP

Message Meaning: VLAN heartbeat started

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37908 - MESGID_VLAN_HB_DOWN

Message ID: 37908

Message Description: MESGID_VLAN_HB_DOWN

Message Meaning: VLAN heartbeat lost

Type: Event

Category: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37909 - MESGID_VLAN_HB_DOWN_SUM

Message ID: 37909

Message Description: MESGID_VLAN_HB_DOWN_SUM

Message Meaning: VLAN heartbeat lost summary

Type: Event

Category: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

37910 - MESGID_HA_ACTIVITY_INFO

Message ID: 37910

Message Description: MESGID_HA_ACTIVITY_INFO

Message Meaning: Device set as HA master

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
activity	HA activity message	string	128
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ha-prio	HA Priority	uint8	3
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38010 - LOG_ID_FIPS_ENCRY_FAIL

Message ID: 38010

Message Description: LOG_ID_FIPS_ENCRY_FAIL

Message Meaning: FIPS CC encryption failed

Type: Event

Category: USER

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38011 - LOG_ID_FIPS_DECRY_FAIL

Message ID: 38011

Message Description: LOG_ID_FIPS_DECRY_FAIL

Message Meaning: FIPS CC decryption failed

Type: Event

Category: USER

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

38012 - LOG_ID_ENTROPY_TOKEN

Message ID: 38012

Message Description: LOG_ID_ENTROPY_TOKEN

Message Meaning: Seeding from entropy source

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38031 - LOG_ID_FSSO_LOGON

Message ID: 38031

Message Description: LOG_ID_FSSO_LOGON

Message Meaning: FSSO logon successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
reason	Reason	string	256
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38032 - LOG_ID_FSSO_LOGOFF

Message ID: 38032

Message Description: LOG_ID_FSSO_LOGOFF

Message Meaning: FSSO logoff successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
server	AD server FQDN or IP	string	64

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38033 - LOG_ID_FSSO_SVR_STATUS

Message ID: 38033

Message Description: LOG_ID_FSSO_SVR_STATUS

Message Meaning: FSSO Active Directory server authentication status

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38400 - LOGID_EVENT_NOTIF_SEND_SUCC

Message ID: 38400

Message Description: LOGID_EVENT_NOTIF_SEND_SUCC

Message Meaning: Notification message sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

38401 - LOGID_EVENT_NOTIF_SEND_FAIL

Message ID: 38401

Message Description: LOGID_EVENT_NOTIF_SEND_FAIL

Message Meaning: Notification message send failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
eventtime		uint64	20
from	Sender Email Address for Notification	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
profile	Profile Name	string	64
profilegroup	Profile Group Name	string	4
profiletype	Profile Type	string	64

Log Field Name	Description	Data Type	Length
service	Name of Service	string	64
sess_duration	Session Duration	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
to	Recipient Email Addresses for Notification	string	512
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
virus	Virus Name	string	128

38402 - LOGID_EVENT_NOTIF_DNS_FAIL

Message ID: 38402

Message Description: LOGID_EVENT_NOTIF_DNS_FAIL

Message Meaning: MMSC hostname unresolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
profile	Profile Name	string	64
profiletype	Profile Type	string	64
profile_vd	Virtual Domain Name	string	64

Log Field Name	Description	Data Type	Length
service	Name of Service	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38403 - LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE

Message ID: 38403

Message Description: LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE

Message Meaning: Insufficient system resource notification

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38404 - LOGID_EVENT_NOTIF_HOSTNAME_ERROR

Message ID: 38404

Message Description: LOGID_EVENT_NOTIF_HOSTNAME_ERROR

Message Meaning: FortiGuard hostname unresolvable

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
hostname	Hostname	string	128
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38405 - LOGID_NOTIF_CODE_SENDTO_SMS_PHONE

Message ID: 38405

Message Description: LOGID_NOTIF_CODE_SENDTO_SMS_PHONE

Message Meaning: Guest user account login information sent to phone

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38406 - LOGID_NOTIF_CODE_SENDTO_SMS_TO

Message ID: 38406

Message Description: LOGID_NOTIF_CODE_SENDTO_SMS_TO

Message Meaning: Guest user account login information sent as SMS

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38407 - LOGID_NOTIF_CODE_SENDTO_EMAIL

Message ID: 38407

Message Description: LOGID_NOTIF_CODE_SENDTO_EMAIL

Message Meaning: Guest user account login information sent to email

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38408 - LOGID_EVENT_OFTP_SSL_CONNECTED

Message ID: 38408

Message Description: LOGID_EVENT_OFTP_SSL_CONNECTED

Message Meaning: SSL connection established

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED

Message ID: 38409

Message Description: LOGID_EVENT_OFTP_SSL_DISCONNECTED

Message Meaning: SSL connection closed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38410 - LOGID_EVENT_OFTP_SSL_FAILED

Message ID: 38410

Message Description: LOGID_EVENT_OFTP_SSL_FAILED

Message Meaning: SSL connection failed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38411 - LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO

Message ID: 38411

Message Description: LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO

Message Meaning: Two-factor authentication code sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38412 - LOGID_EVENT_TOKEN_CODE_SENDTO

Message ID: 38412

Message Description: LOGID_EVENT_TOKEN_CODE_SENDTO

Message Meaning: Token activation code sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

38420 - LOGID_EVENT_HTTPS_CONNECTION

Message ID: 38420

Message Description: LOGID_EVENT_HTTPS_CONNECTION

Message Meaning: HTTPS connection

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
reason	Reason	string	256
remote	Remote IP Address	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38656 - LOGID_EVENT_RAD_RPT_PROTO_ERROR

Message ID: 38656

Message Description: LOGID_EVENT_RAD_RPT_PROTO_ERROR

Message Meaning: RADIUS protocol error

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38657 - LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND

Message ID: 38657

Message Description: LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND

Message Meaning: RADIUS profile not found

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38658 - LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND

Message ID: 38658

Message Description: LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND

Message Meaning: RADIUS profile CTX not found

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38659 - LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED

Message ID: 38659

Message Description: LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED

Message Meaning: RADIUS accounting stop message missing

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38660 - LOGID_EVENT_RAD_RPT_ACCT_EVENT

Message ID: 38660

Message Description: LOGID_EVENT_RAD_RPT_ACCT_EVENT

Message Meaning: RADIUS accounting event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38661 - LOGID_EVENT_RAD_RPT_OTHER

Message ID: 38661

Message Description: LOGID_EVENT_RAD_RPT_OTHER

Message Meaning: RADIUS endpoint block event or other event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR

Message ID: 38662

Message Description: LOGID_EVENT_RAD_STAT_PROTO_ERROR

Message Meaning: RADIUS accounting protocol error

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND

Message ID: 38663

Message Description: LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND

Message Meaning: RADIUS accounting profile not found

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED

Message ID: 38665**Message Description:** LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED**Message Meaning:** RADIUS accounting stop message missing**Type:** Event**Category:** USER**Severity:** Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT

Message ID: 38666

Message Description: LOGID_EVENT_RAD_STAT_ACCT_EVENT

Message Meaning: RADIUS accounting event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38667 - LOGID_EVENT_RAD_STAT_OTHER

Message ID: 38667

Message Description: LOGID_EVENT_RAD_STAT_OTHER

Message Meaning: RADIUS other accounting event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
count	Number of Packets	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

38668 - LOGID_EVENT_RAD_STAT_EP_BLK

Message ID: 38668

Message Description: LOGID_EVENT_RAD_STAT_EP_BLK

Message Meaning: RADIUS endpoint block event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
acct_stat	Accounting state (RADIUS)	string	14
carrier_ep	The FortiOS Carrier end-point identification	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
rsso_key	RADIUS SSO attribute value	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP

Message ID: 39424

Message Description: LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP

Message Meaning: SSL VPN tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN

Message ID: 39425

Message Description: LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN

Message Meaning: SSL VPN tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL

Message ID: 39426

Message Description: LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL

Message Meaning: SSL VPN login fail

Type: Event

Category: VPN

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS

Message ID: 39936

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS

Message Meaning: SSL VPN statistics

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY**Message ID:** 39937**Message Description:** LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY**Message Meaning:** SSL VPN deny**Type:** Event**Category:** VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS

Message ID: 39938**Message Description:** LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS**Message Meaning:** SSL VPN pass**Type:** Event**Category:** VPN**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT

Message ID: 39939

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT

Message Meaning: SSL VPN timeout

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE

Message ID: 39940

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE

Message Meaning: SSL VPN close

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY

Message ID: 39941

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY

Message Meaning: SSL VPN system busy

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK

Message ID: 39942

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK

Message Meaning: SSL VPN certificate ok

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON

Message ID: 39943

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON

Message Meaning: SSL VPN new connection

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT

Message ID: 39944

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_ALERT

Message Meaning: SSL VPN alert

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc		string	128
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL

Message ID: 39945

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL

Message Meaning: SSL VPN exit fail

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR

Message ID: 39946

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR

Message Meaning: SSL VPN exit error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP

Message ID: 39947

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP

Message Meaning: SSL VPN tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN

Message ID: 39948

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN

Message Meaning: SSL VPN tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
rcvdbyte	Received Bytes	uint64	20
reason	Reason	string	256
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS

Message ID: 39949

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS

Message Meaning: SSL VPN statistics

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User Name Group	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
nextstat	Time interval in seconds for the next statistics	uint32	10
rcvdbyte	Received Bytes	uint64	20
remip	Remote IP	ip	39
sentbyte	Bytes Sent	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG

Message ID: 39950

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG

Message Meaning: SSL VPN unknown tag

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR

Message ID: 39951

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR

Message Meaning: SSL VPN tunnel error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE

Message ID: 39952

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE

Message Meaning: SSL VPN enter conserve mode

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE

Message ID: 39953

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE

Message Meaning: SSL VPN leave conserve mode

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dst_host		string	64
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40001 - LOG_ID_PPTP_TUNNEL_UP

Message ID: 40001

Message Description: LOG_ID_PPTP_TUNNEL_UP

Message Meaning: PPTP tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40002 - LOG_ID_PPTP_TUNNEL_DOWN

Message ID: 40002

Message Description: LOG_ID_PPTP_TUNNEL_DOWN

Message Meaning: PPTP tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40003 - LOG_ID_PPTP_TUNNEL_STAT

Message ID: 40003

Message Description: LOG_ID_PPTP_TUNNEL_STAT

Message Meaning: PPTP tunnel status

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10

Log Field Name	Description	Data Type	Length
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40014 - LOG_ID_PPTP_REACH_MAX_CON

Message ID: 40014

Message Description: LOG_ID_PPTP_REACH_MAX_CON

Message Meaning: PPTP client connection limit reached

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL

Message ID: 40017

Message Description: LOG_ID_L2TPD_CLIENT_CON_FAIL

Message Meaning: L2TP client connection failed

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40019 - LOG_ID_L2TPD_CLIENT_DISCON

Message ID: 40019

Message Description: LOG_ID_L2TPD_CLIENT_DISCON

Message Meaning: L2TP client disconnected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40021 - LOG_ID_PPTP_NOT_CONIG

Message ID: 40021

Message Description: LOG_ID_PPTP_NOT_CONIG

Message Meaning: PPTP not configured in VDOM

Type: Event

Category: VPN

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40022 - LOG_ID_PPTP_NO_IP_AVAIL

Message ID: 40022

Message Description: LOG_ID_PPTP_NO_IP_AVAIL

Message Meaning: PPTP IP addresses unavailable

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40024 - LOG_ID_PPTP_OUT_MEM

Message ID: 40024

Message Description: LOG_ID_PPTP_OUT_MEM

Message Meaning: PPTP config list insufficient memory

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40034 - LOG_ID_PPTP_START

Message ID: 40034

Message Description: LOG_ID_PPTP_START

Message Meaning: PPTPD started

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40035 - LOG_ID_PPTP_START_FAIL

Message ID: 40035

Message Description: LOG_ID_PPTP_START_FAIL

Message Meaning: PPTPD failed to start

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40036 - LOG_ID_PPTP_EXIT

Message ID: 40036

Message Description: LOG_ID_PPTP_EXIT

Message Meaning: PPTPD exited

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40037 - LOG_ID_PPTPD_SVR_DISCON

Message ID: 40037

Message Description: LOG_ID_PPTPD_SVR_DISCON

Message Meaning: PPTPD disconnected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40038 - LOG_ID_PPTPD_CLIENT_CON

Message ID: 40038

Message Description: LOG_ID_PPTPD_CLIENT_CON

Message Meaning: PPTPD client connected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40039 - LOG_ID_PPTPD_CLIENT_DISCON

Message ID: 40039

Message Description: LOG_ID_PPTPD_CLIENT_DISCON

Message Meaning: PPTPD client disconnected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40101 - LOG_ID_L2TP_TUNNEL_UP

Message ID: 40101

Message Description: LOG_ID_L2TP_TUNNEL_UP

Message Meaning: L2TP tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39

Log Field Name	Description	Data Type	Length
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40102 - LOG_ID_L2TP_TUNNEL_DOWN

Message ID: 40102

Message Description: LOG_ID_L2TP_TUNNEL_DOWN

Message Meaning: L2TP tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

40103 - LOG_ID_L2TP_TUNNEL_STAT

Message ID: 40103

Message Description: LOG_ID_L2TP_TUNNEL_STAT

Message Meaning: L2TP tunnel status

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User Name Group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
remip	Remote IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
tunnelid	Tunnel ID	uint32	10
tunnelip	Tunnel IP	ip	39
tunneltype	Tunnel Type	string	64
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40114 - LOG_ID_L2TPD_START

Message ID: 40114

Message Description: LOG_ID_L2TPD_START

Message Meaning: L2TPD started

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40115 - LOG_ID_L2TPD_EXIT

Message ID: 40115

Message Description: LOG_ID_L2TPD_EXIT

Message Meaning: L2TPD exited

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40118 - LOG_ID_L2TPD_CLIENT_CON

Message ID: 40118

Message Description: LOG_ID_L2TPD_CLIENT_CON

Message Meaning: L2TP client connected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

40704 - LOG_ID_EVENT_SYS_PERF

Message ID: 40704

Message Description: LOG_ID_EVENT_SYS_PERF

Message Meaning: System performance statistics

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
bandwidth	Bandwidth	string	42
cpu	CPU Usage	uint8	3
date	Date	string	10
devid	Device ID	string	16
disk	Disk Usage	uint8	3
disklograte	Disk Log Rate	uint64	20
eventtime		uint64	20
fazlograte	FortiAnalyzer Logging Rate	uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mem	Memory Usage	uint8	3
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
setuprate	Session Setup Rate	uint64	20
subtype	Log Subtype	string	20
time	Time	string	8
totalsession	Total Number of Sessions	uint32	10
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

40960 - LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR

Message ID: 40960

Message Description: LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR

Message Meaning: Web proxy forward server error

Type: Event

Category: WAD

Severity: Notice

Log Field Name	Description	Data Type	Length
addr_type	Address Type	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fqdn	Fully Qualified Domain Name	string	256
fwserver_name		string	32
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
port	Port Number	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41000 - LOG_ID_UPD_FGT_SUCC

Message ID: 41000

Message Description: LOG_ID_UPD_FGT_SUCC

Message Meaning: FortiGate updated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41001 - LOG_ID_UPD_FGT_FAIL

Message ID: 41001

Message Description: LOG_ID_UPD_FGT_FAIL

Message Meaning: FortiGate update failed

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41002 - LOG_ID_UPD_SRC_VIS

Message ID: 41002**Message Description:** LOG_ID_UPD_SRC_VIS**Message Meaning:** Source visibility signature package updated**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41006 - LOG_ID_UPD_FSA_VIRDB

Message ID: 41006

Message Description: LOG_ID_UPD_FSA_VIRDB

Message Meaning: FortiSandbox AV database updated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	string	64

41984 - LOG_ID_EVENT_VPN_CERT_LOAD

Message ID: 41984

Message Description: LOG_ID_EVENT_VPN_CERT_LOAD

Message Meaning: Certificate loaded

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL

Message ID: 41985

Message Description: LOG_ID_EVENT_VPN_CERT_REMOVAL

Message Meaning: Certificate removed

Type: Event

Category: VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41986 - LOG_ID_EVENT_VPN_CERT_REGEN

Message ID: 41986**Message Description:** LOG_ID_EVENT_VPN_CERT_REGEN**Message Meaning:** Certificate regenerated**Type:** Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41987 - LOG_ID_EVENT_VPN_CERT_UPDATE

Message ID: 41987

Message Description: LOG_ID_EVENT_VPN_CERT_UPDATE

Message Meaning: Certificate updated

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE

Message ID: 41988

Message Description: LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE

Message Meaning: SSL setting changed

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

41989 - LOG_ID_EVENT_VPN_CERT_ERR

Message ID: 41989

Message Description: LOG_ID_EVENT_VPN_CERT_ERR

Message Meaning: Certificate error

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED

Message ID: 41990

Message Description: LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED

Message Meaning: Certificate update failed

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
method	Method	string	64
msg	Message	string	
name	Name	string	128
reason	Reason	string	256
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

41991 - LOG_ID_EVENT_VPN_CERT_EXPORT

Message ID: 41991

Message Description: LOG_ID_EVENT_VPN_CERT_EXPORT

Message Meaning: Certificate exported

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cert-type	Certification type	string	6
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
name	Name	string	128
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

42201 - LOG_ID_NETX_VMX_ATTACH

Message ID: 42201

Message Description: LOG_ID_NETX_VMX_ATTACH

Message Meaning: VMX instance successfully attached

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

42202 - LOG_ID_NETX_VMX_DETACH

Message ID: 42202**Message Description:** LOG_ID_NETX_VMX_DETACH**Message Meaning:** VMX instance successfully detached**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

42203 - LOG_ID_NETX_VMX_DENIED

Message ID: 42203

Message Description: LOG_ID_NETX_VMX_DENIED

Message Meaning: VMX instance successfully denied

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43008 - LOG_ID_EVENT_AUTH_SUCCESS

Message ID: 43008

Message Description: LOG_ID_EVENT_AUTH_SUCCESS

Message Meaning: Authentication success

Type: Event

Category: USER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43009 - LOG_ID_EVENT_AUTH_FAILED

Message ID: 43009**Message Description:** LOG_ID_EVENT_AUTH_FAILED**Message Meaning:** Authentication failed**Type:** Event**Category:** USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43010 - LOG_ID_EVENT_AUTH_LOCKOUT

Message ID: 43010**Message Description:** LOG_ID_EVENT_AUTH_LOCKOUT**Message Meaning:** Authentication lockout**Type:** Event**Category:** USER**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43011 - LOG_ID_EVENT_AUTH_TIME_OUT

Message ID: 43011

Message Description: LOG_ID_EVENT_AUTH_TIME_OUT

Message Meaning: Authentication timed out

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43012 - LOG_ID_EVENT_AUTH_FSAE_AUTH_SUCCESS

Message ID: 43012

Message Description: LOG_ID_EVENT_AUTH_FSAE_AUTH_SUCCESS

Message Meaning: FSSO authentication successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43013 - LOG_ID_EVENT_AUTH_FSAE_AUTH_FAIL

Message ID: 43013

Message Description: LOG_ID_EVENT_AUTH_FSAE_AUTH_FAIL

Message Meaning: FSSO authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON

Message ID: 43014

Message Description: LOG_ID_EVENT_AUTH_FSAE_LOGON

Message Meaning: FSSO logon authentication status

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF

Message ID: 43015

Message Description: LOG_ID_EVENT_AUTH_FSAE_LOGOFF

Message Meaning: FSSO logoff authentication status

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS

Message ID: 43016

Message Description: LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS

Message Meaning: NTLM authentication successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL

Message ID: 43017

Message Description: LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL

Message Meaning: NTLM authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
adgroup	AD Group Name	string	128
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL

Message ID: 43018

Message Description: LOG_ID_EVENT_AUTH_FGOVRD_FAIL

Message Meaning: FortiGuard override failed

Type: Event

Category: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message	string	
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS

Message ID: 43020

Message Description: LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS

Message Meaning: FortiGuard override successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS

Message ID: 43025

Message Description: LOG_ID_EVENT_AUTH_PROXY_SUCCESS

Message Meaning: Explicit proxy authentication successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED

Message ID: 43026

Message Description: LOG_ID_EVENT_AUTH_PROXY_FAILED

Message Meaning: Explicit proxy authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT

Message ID: 43027

Message Description: LOG_ID_EVENT_AUTH_PROXY_TIME_OUT

Message Meaning: Explicit proxy authentication timed out

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43028 - LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED

Message ID: 43028

Message Description: LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED

Message Meaning: Explicit proxy user group query failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS

Message ID: 43029

Message Description: LOG_ID_EVENT_AUTH_WARNING_SUCCESS

Message Meaning: FortiGuard authentication override successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
category		uint32	10
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
expiry	FortiGuard override expiry timestamp	string	64
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
oldwprof	Old Web Filter Profile	string	64
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
scope	FortiGuard Override Scope	string	16
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL

Message ID: 43030

Message Description: LOG_ID_EVENT_AUTH_WARNING_TBL_FULL

Message Meaning: FortiGuard authentication override failed

Type: Event

Category: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
initiator	Original login user name for Fortiguard override	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43032 - LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED

Message ID: 43032

Message Description: LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED

Message Meaning: Explicit proxy authentication user limit reached

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43033 - LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN

Message ID: 43033

Message Description: LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN

Message Meaning: Explicit proxy authentication user concurrent check failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43034 - LOG_ID_EVENT_AUTH_PROXY_NO_RESP

Message ID: 43034

Message Description: LOG_ID_EVENT_AUTH_PROXY_NO_RESP

Message Meaning: Explicit proxy authentication no response

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
agent		string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
url		string	512
vd	Virtual Domain Name	string	32

43037 - LOG_ID_EVENT_AUTH_IPV4_FLUSH

Message ID: 43037

Message Description: LOG_ID_EVENT_AUTH_IPV4_FLUSH

Message Meaning: Auth IPv4 logon flush

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43038 - LOG_ID_EVENT_AUTH_IPV6_FLUSH

Message ID: 43038

Message Description: LOG_ID_EVENT_AUTH_IPV6_FLUSH

Message Meaning: Auth IPv6 logon flush

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43039 - LOG_ID_EVENT_AUTH_LOGON

Message ID: 43039

Message Description: LOG_ID_EVENT_AUTH_LOGON

Message Meaning: Auth logon

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message	string	
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43040 - LOG_ID_EVENT_AUTH_LOGOUT

Message ID: 43040

Message Description: LOG_ID_EVENT_AUTH_LOGOUT

Message Meaning: Auth logout

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
group	User name group	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
srcip	Source IP	ip	39
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT

Message ID: 43041

Message Description: LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT

Message Meaning: Disclaimer accepted

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE

Message ID: 43042

Message Description: LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE

Message Meaning: Disclaimer declined

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS

Message ID: 43043

Message Description: LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS

Message Meaning: Email collecting succeeded

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL

Message ID: 43044

Message Description: LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL

Message Meaning: Email collecting failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
authproto	The protocol that initiated the authentication	string	512
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
eventtime		uint64	20
group	User name group	string	64
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
reason	Reason	string	256
srcip	Source IP	ip	39
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS

Message ID: 43045

Message Description: LOG_ID_EVENT_AUTH_8021X_SUCCESS

Message Meaning: 802.1x authentication succeeded

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
stamac		string	17

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43046 - LOG_ID_EVENT_AUTH_8021X_FAIL

Message ID: 43046

Message Description: LOG_ID_EVENT_AUTH_8021X_FAIL

Message Meaning: 802.1x authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
interface		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
reason	Reason	string	256
stamac		string	17
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43050 - LOG_ID_EVENT_AUTH_FSAE_CONNECT

Message ID: 43050

Message Description: LOG_ID_EVENT_AUTH_FSAE_CONNECT

Message Meaning: FSSO server connected

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43051 - LOG_ID_EVENT_AUTH_FSAE_DISCONNECT

Message ID: 43051

Message Description: LOG_ID_EVENT_AUTH_FSAE_DISCONNECT

Message Meaning: FSSO server disconnected

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message	string	
server	AD server FQDN or IP	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43264 - LOGID_MMS_STATS

Message ID: 43264

Message Description: LOGID_MMS_STATS

Message Meaning: MMS statistics

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
checksum	for MMS Statistics	uint32	10
date	Date	string	10
devid	Device ID	string	16
duration	Duration	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
infected	Infected MMS	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msgproto	Message Protocol Number	string	16
scanned	Number of Scanned MMSs	uint32	10
subtype	Log Subtype	string	20
suspicious	Number of Suspicious MMSs	uint32	10
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43520 - LOG_ID_EVENT_WIRELESS_SYS

Message ID: 43520

Message Description: LOG_ID_EVENT_WIRELESS_SYS

Message Meaning: Wireless system activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43521 - LOG_ID_EVENT_WIRELESS_ROGUE

Message ID: 43521

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE

Message Meaning: Rogue AP activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43522 - LOG_ID_EVENT_WIRELESS_WTP

Message ID: 43522

Message Description: LOG_ID_EVENT_WIRELESS_WTP

Message Meaning: Physical AP activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43524 - LOG_ID_EVENT_WIRELESS_STA

Message ID: 43524

Message Description: LOG_ID_EVENT_WIRELESS_STA

Message Meaning: Wireless client activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43525 - LOG_ID_EVENT_WIRELESS_ONWIRE

Message ID: 43525

Message Description: LOG_ID_EVENT_WIRELESS_ONWIRE

Message Meaning: Rogue AP activity

Type: Event**Category:** WIRELESS**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4

Log Field Name	Description	Data Type	Length
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43526 - LOG_ID_EVENT_WIRELESS_WTPR

Message ID: 43526

Message Description: LOG_ID_EVENT_WIRELESS_WTPR

Message Meaning: Physical AP radio activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43527 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG

Message ID: 43527

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG

Message Meaning: Rogue AP status configured

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR

Message ID: 43528

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_ERROR

Message Meaning: Physical AP radio activity

Type: Event

Category: WIRELESS

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4

Log Field Name	Description	Data Type	Length
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43529 - LOG_ID_EVENT_WIRELESS_CLB

Message ID: 43529

Message Description: LOG_ID_EVENT_WIRELESS_CLB

Message Meaning: Wireless client load balancing

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE

Message ID: 43530

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE

Message Meaning: Wireless bridge intrusion detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rss	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threatype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH

Message ID: 43531

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH

Message Meaning: Wireless broadcasting deauthentication detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rss	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP

Message ID: 43532

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP

Message Meaning: Wireless null SSID probe response detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI

Message ID: 43533

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI

Message Meaning: Wireless invalid MAC OUI detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
invalidmac	the MAC address with invalid OUI	string	17
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR

Message ID: 43534

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR

Message Meaning: Wireless long duration attack detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
duration	Duration of the last threatening packet captured from TA	uint32	10
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threatype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV

Message ID: 43535

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV

Message Meaning: Wireless Weak WEP IV detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rss	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
weakwepiv	Weak Wep Initiation Vector	string	8

43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD

Message ID: 43542

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD

Message Meaning: Wireless EAPOL packet flooding detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eapolcnt	EAPOL packet count	uint32	10
eapoltype	EAPOL packet type	string	16
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threatype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD

Message ID: 43544

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD

Message Meaning: Wireless management flooding detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
mgmtcnt	The number of unauthorized client flooding managemet frames	uint32	10
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH

Message ID: 43546

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH

Message Meaning: Wireless spoofed deauthentication detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rss	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP

Message ID: 43548

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP

Message Meaning: Wireless ASLEAP attack detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
ds	direction with distribution system	string	8
encrypt	whether the packet is encrypted or not	uint8	3
eventtime		uint64	20
frametype	Frame Type	string	32
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rsi	Received signal strength indicator	uint8	3
seq	Sequence	string	16
sndetected	SN of the AP which detected the rogue AP	string	36
subtype	Log Subtype	string	20
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

Log Field Name	Description	Data Type	Length
threattype	WIDS threat type	string	64
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE

Message ID: 43550

Message Description: LOG_ID_EVENT_WIRELESS_STA_LOCATE

Message Meaning: Wireless station presence detection

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
noise		int8	4
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
signal	Signal	int8	4
sn	Serial Number	string	64
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN

Message ID: 43551

Message Description: LOG_ID_EVENT_WIRELESS_WTP_JOIN

Message Meaning: Physical AP join

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE

Message ID: 43552

Message Description: LOG_ID_EVENT_WIRELESS_WTP_LEAVE

Message Meaning: Physical AP leave

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL

Message ID: 43553

Message Description: LOG_ID_EVENT_WIRELESS_WTP_FAIL

Message Meaning: Physical AP fail

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE

Message ID: 43554

Message Description: LOG_ID_EVENT_WIRELESS_WTP_UPDATE

Message Meaning: Physical AP update

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET

Message ID: 43555

Message Description: LOG_ID_EVENT_WIRELESS_WTP_RESET

Message Meaning: Physical AP reset

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK

Message ID: 43556**Message Description:** LOG_ID_EVENT_WIRELESS_WTP_KICK**Message Meaning:** Physical AP kick**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE

Message ID: 43557

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE

Message Meaning: Physical AP add failure

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR

Message ID: 43558

Message Description: LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR

Message Meaning: Physical AP config error

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH

Message ID: 43559

Message Description: LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH

Message Meaning: Physical AP SN mismatch

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED

Message ID: 43560

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED

Message Meaning: Wireless system restarted

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP

Message ID: 43561

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP

Message Meaning: Wireless system hostapd up

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN

Message ID: 43562

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN

Message Meaning: Wireless system hostapd down

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT

Message ID: 43563

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_DETECT

Message Meaning: Rogue AP detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33

Log Field Name	Description	Data Type	Length
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR

Message ID: 43564

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR

Message Meaning: Rogue AP off air

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR

Message ID: 43565

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR

Message Meaning: Rogue AP on air

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE

Message ID: 43566

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE

Message Meaning: Rogue AP off wire

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT

Message ID: 43567

Message Description: LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT

Message Meaning: Fake AP detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR

Message ID: 43568

Message Description: LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR

Message Meaning: Fake AP on air

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED

Message ID: 43569

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED

Message Meaning: Rogue AP suppressed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED

Message ID: 43570

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED

Message Meaning: Rogue AP unsuppressed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG

Message ID: 43571

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG

Message Meaning: Rogue AP change detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
age	time in seconds - time passed since last seen	uint32	10
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
apstatus	Access Point Status	uint8	3
aptype	AP Type	uint8	3
bssid	Service Set ID	string	17
channel	Channel	uint8	3
date	Date	string	10
detectionmethod	Detection Method	string	21
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
level	Log Level	string	11
live	time in seconds	uint32	10
logdesc	Log Description	string	
logid	Log ID	string	10
manuf	Manufacturer name	string	20
msg	Log Message	string	
noise		int8	4
onwire	A flag to indicate if the AP is onwire or not	string	3
radioband	Radio Band	string	64
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
rate		uint8	4
security	Security	string	40
signal	Signal	int8	4
snclosest	SN of the AP closest to the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43572 - LOG_ID_EVENT_WIRELESS_STA ASSO

Message ID: 43572

Message Description: LOG_ID_EVENT_WIRELESS_STA ASSO

Message Meaning: Wireless client associated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH

Message ID: 43573

Message Description: LOG_ID_EVENT_WIRELESS_STA_AUTH

Message Meaning: Wireless client authenticated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43574 - LOG_ID_EVENT_WIRELESS_STA_DASS

Message ID: 43574

Message Description: LOG_ID_EVENT_WIRELESS_STA_DASS

Message Meaning: Wireless client deassociated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT

Message ID: 43575

Message Description: LOG_ID_EVENT_WIRELESS_STA_DAUT

Message Meaning: Wireless client deauthenticated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE

Message ID: 43576

Message Description: LOG_ID_EVENT_WIRELESS_STA_IDLE

Message Meaning: Wireless client idle

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43577 - LOG_ID_EVENT_WIRELESS_STA_DENY

Message ID: 43577

Message Description: LOG_ID_EVENT_WIRELESS_STA_DENY

Message Meaning: Wireless client denied

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43578 - LOG_ID_EVENT_WIRELESS_STA_KICK

Message ID: 43578

Message Description: LOG_ID_EVENT_WIRELESS_STA_KICK

Message Meaning: Wireless client kicked

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43579 - LOG_ID_EVENT_WIRELESS_STA_IP

Message ID: 43579

Message Description: LOG_ID_EVENT_WIRELESS_STA_IP

Message Meaning: Wireless client IP assigned

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP

Message ID: 43580

Message Description: LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP

Message Meaning: Wireless client left WTP

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN

Message ID: 43581

Message Description: LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN

Message Meaning: Wireless client WTP disconnected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED

Message ID: 43582

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED

Message Meaning: Rogue AP status configured

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED

Message ID: 43583

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED

Message Meaning: Rogue AP status configured

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE

Message ID: 43584

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE

Message Meaning: Rogue AP status configured

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED

Message ID: 43585

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED

Message Meaning: Rogue AP status configured

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
apstatus	Access Point Status	uint8	3
bssid	Service Set ID	string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN

Message ID: 43586

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN

Message Meaning: Physical AP radio DARRP channel change

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START

Message ID: 43587

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START

Message Meaning: Physical AP radio DARRP start

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN

Message ID: 43588

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN

Message Meaning: Physical AP radio oper channel change

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR

Message ID: 43589

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_RADAR

Message Meaning: Physical AP radio radar detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL

Message ID: 43590

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_NOL

Message Meaning: Physical AP radio channel removed from NOL

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS

Message ID: 43591

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS

Message Meaning: Physical AP radio country config success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY

Message ID: 43592

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY

Message Meaning: Physical AP radio oper country

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER

Message ID: 43593

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER

Message Meaning: Physical AP radio config TX power

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER

Message ID: 43594

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER

Message Meaning: Physical AP radio oper TX power

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY

Message ID: 43595

Message Description: LOG_ID_EVENT_WIRELESS_CLB_DENY

Message Meaning: Wireless client load balancing denied

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY

Message ID: 43596

Message Description: LOG_ID_EVENT_WIRELESS_CLB_RETRY

Message Meaning: Wireless client load balancing retry

Type: Event

Category: WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
radioband	Radio Band	string	64
reason	Reason	string	256
sn	Serial Number	string	64
ssid	Base Service Set ID	string	33
stacount	Number of stations/clients	uint32	10
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vap		string	36
vd	Virtual Domain Name	string	32

43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD

Message ID: 43597**Message Description:** LOG_ID_EVENT_WIRELESS_WTP_ADD**Message Meaning:** Physical AP add**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS

Message ID: 43598

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS

Message Meaning: Physical AP add XSS

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL

Message ID: 43599

Message Description: LOG_ID_EVENT_WIRELESS_WTP_DEL

Message Meaning: Physical AP delete

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP

Message ID: 43600

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP

Message Meaning: Physical AP radio DARRP stop

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
bandwidth	Bandwidth	string	42

Log Field Name	Description	Data Type	Length
cfgtxpower	Config TX power	uint32	10
configcountry	Config Country	string	4
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
opercountry	Operating Country	string	4
opertxpower	Operating TX power	uint32	10
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON

Message ID: 43601

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON

Message Meaning: Wireless station sign on

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS

Message ID: 43602

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS

Message Meaning: Wireless station sign on success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE

Message ID: 43603

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE

Message Meaning: Wireless station sign on failed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST

Message ID: 43604

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST

Message Meaning: Captive-portal VAP e-mail collect request sent

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS

Message ID: 43605

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS

Message Meaning: Captive-portal VAP e-mail collect success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE

Message ID: 43606

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE

Message Meaning: Captive-portal VAP e-mail collect failed

Type: Event

Category: WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK

Message ID: 43607

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK

Message Meaning: Captive-portal VAP disclaimer agreed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE

Message ID: 43608

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE

Message Meaning: Captive-portal VAP disclaimer declined

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
channel	Channel	uint8	3
date	Date	string	10
devid	Device ID	string	16
encryption	Encryption Method	string	12
eventtime		uint64	20
group	User Group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mpsk		string	33
msg	Log Message	string	
radioband	Radio Band	string	64
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
security	Security	string	40
sn	Serial Number	string	64
srcip	Source IP	ip	39
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vap		string	36
vd	Virtual Domain Name	string	32

43609 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_START

Message ID: 43609

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_START

Message Meaning: DARRP optimization start

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43610 - LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_STOP

Message ID: 43610

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_DARRP_STOP

Message Meaning: DARRP optimization stop

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP

Message ID: 43611

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_UP

Message Meaning: Wireless controller start

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED

Message ID: 43612

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED

Message Meaning: Wireless controller configuration loaded

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR

Message ID: 43613

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ERR

Message Meaning: Physical AP error

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION

Message ID: 43614

Message Description: LOG_ID_EVENT_WIRELESS_DHCP_STAVATION

Message Meaning: DHCP Starvation detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
client_addr		string	17
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
sn	Serial Number	string	64
source_mac		string	17
ssid	Base Service Set ID	string	33
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vap		string	36
vapmode		string	17
vd	Virtual Domain Name	string	32
xid		uint32	10

43615 - LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL

Message ID: 43615

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL

Message Meaning: Wireless controller IPsec setup failed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43617 - LOG_ID_EVENT_WIRELESS_WTPPROF_ADJUSTED

Message ID: 43617

Message Description: LOG_ID_EVENT_WIRELESS_WTPPROF_ADJUSTED

Message Meaning: Wireless wtp profile has been adjusted

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43618 - LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS

Message ID: 43618

Message Description: LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS

Message Meaning: Physical AP image receive success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43621 - LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG

Message ID: 43621

Message Description: LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG

Message Meaning: Wireless wtp data channel changed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
meshmode	Mesh mode	string	19
msg	Log Message	string	
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
snmeshparent	SN of the mesh parent	string	36
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43776 - LOG_ID_EVENT_NAC_QUARANTINE

Message ID: 43776

Message Description: LOG_ID_EVENT_NAC_QUARANTINE

Message Meaning: NAC quarantine

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
admin		string	64

Log Field Name	Description	Data Type	Length
banned_rule	NAC quarantine Banned Rule Name	string	80
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE

Message ID: 43777

Message Description: LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE

Message Meaning: NAC anomaly quarantine

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
admin		string	64
banned_rule	NAC quarantine Banned Rule Name	string	80
banned_src	NAC quarantine Banned Source IP	string	16
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
dst_int	Destination Interface	string	64
duration	Duration	uint32	10
eventtime		uint64	20
group	User group Name	string	64
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
proto	Protocol Number	uint8	3
sensor	NAC Sensor Name	string	36
service	Name of Service	string	64
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
src_int	Source Interface	string	64
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN

Message ID: 43800

Message Description: LOG_ID_EVENT_ELBC_BLADE_JOIN

Message Meaning: Blade ready to process traffic

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE

Message ID: 43801

Message Description: LOG_ID_EVENT_ELBC_BLADE_LEAVE

Message Meaning: Blade not ready to process traffic

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND

Message ID: 43802

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND

Message Meaning: Master blade found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST

Message ID: 43803

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST

Message Meaning: Master blade lost

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE

Message ID: 43804

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE

Message Meaning: Master blade changed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchassisid	New Chassis ID	uint8	

Log Field Name	Description	Data Type	Length
newslot	New Slot Number	uint8	
oldchassisid	Original Chassis Number	uint8	
oldslot	Original Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND

Message ID: 43805

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND

Message Meaning: ELBC channel active

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchannel	New Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST

Message ID: 43806

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST

Message Meaning: ELBC channel inactive

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
oldchannel	Original Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE

Message ID: 43807

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE

Message Meaning: ELBC channel failover

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
newchannel	New Channel Number	uint8	
oldchannel	Original Channel Number	uint8	
slot	Slot Number	uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE

Message ID: 43808

Message Description: LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE

Message Meaning: ELBC chassis active

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE

Message ID: 43809**Message Description:** LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE**Message Meaning:** ELBC chassis inactive**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
action	Action	string	32
chassisid	Chassis ID	uint8	
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
informationsource	Information Source	string	
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

44544 - LOGID_EVENT_CONFIG_PATH

Message ID: 44544

Message Description: LOGID_EVENT_CONFIG_PATH

Message Meaning: Path configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44545 - LOGID_EVENT_CONFIG_OBJ

Message ID: 44545

Message Description: LOGID_EVENT_CONFIG_OBJ

Message Meaning: Object configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44546 - LOGID_EVENT_CONFIG_ATTR

Message ID: 44546

Message Description: LOGID_EVENT_CONFIG_ATTR

Message Meaning: Attribute configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44547 - LOGID_EVENT_CONFIG_OBJATTR

Message ID: 44547

Message Description: LOGID_EVENT_CONFIG_OBJATTR

Message Meaning: Object attribute configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44548 - LOGID_EVENT_CONFIG_EXEC

Message ID: 44548

Message Description: LOGID_EVENT_CONFIG_EXEC

Message Meaning: Action performed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44549 - LOGID_EVENT_CONFIG_OBJATTR_MTNER

Message ID: 44549

Message Description: LOGID_EVENT_CONFIG_OBJATTR_MTNER

Message Meaning: Object attribute configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgobj	configuration object	string	256

Log Field Name	Description	Data Type	Length
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44550 - LOGID_EVENT_CONFIG_OBJ_MTNER

Message ID: 44550

Message Description: LOGID_EVENT_CONFIG_OBJ_MTNER

Message Meaning: Object configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgobj	configuration object	string	256
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44551 - LOGID_EVENT_CONFIG_ATTR_MTNER

Message ID: 44551

Message Description: LOGID_EVENT_CONFIG_ATTR_MTNER

Message Meaning: Attribute configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgattr	configuration attribute	string	
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44552 - LOGID_EVENT_CONFIG_PATH_MTNER

Message ID: 44552

Message Description: LOGID_EVENT_CONFIG_PATH_MTNER

Message Meaning: Path configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
cfgpath	configuration path	string	128
cfgtid	config transaction id	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

44553 - LOGID_EVENT_CONFIG_FIXEDPORT_DIS

Message ID: 44553

Message Description: LOGID_EVENT_CONFIG_FIXEDPORT_DIS

Message Meaning: Policy attribute fixedport changed during upgrade

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45000 - LOG_ID_VSD_SSL_RCV_HS

Message ID: 45000

Message Description: LOG_ID_VSD_SSL_RCV_HS

Message Meaning: SSL handshake received

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45001 - LOG_ID_VSD_SSL_RCV_WRG_HS

Message ID: 45001

Message Description: LOG_ID_VSD_SSL_RCV_WRG_HS

Message Meaning: SSL incorrect handshake message received

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
expectedhandshake	Expected Handshake	string	
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
receivedhandshake	Received Handshake	string	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45002 - LOG_ID_VSD_SSL_SENT_HS

Message ID: 45002

Message Description: LOG_ID_VSD_SSL_SENT_HS

Message Meaning: SSL handshake sent

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45003 - LOG_ID_VSD_SSL_WRG_HS_LEN

Message ID: 45003

Message Description: LOG_ID_VSD_SSL_WRG_HS_LEN

Message Meaning: SSL handshake length invalid

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
len	SSL Handshake Message Length	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45004 - LOG_ID_VSD_SSL_RCV_CCS

Message ID: 45004

Message Description: LOG_ID_VSD_SSL_RCV_CCS

Message Meaning: SSL ChangeCipherSpec received

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45005 - LOG_ID_VSD_SSL_RSA_DH_FAIL

Message ID: 45005

Message Description: LOG_ID_VSD_SSL_RSA_DH_FAIL

Message Meaning: Diffie-Hellman parameters verification failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45006 - LOG_ID_VSD_SSL_SENT_CCS

Message ID: 45006

Message Description: LOG_ID_VSD_SSL_SENT_CCS

Message Meaning: SSL ChangeCipherSpec sent

Type: Event**Category:** SYSTEM**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45007 - LOG_ID_VSD_SSL_BAD_HASH

Message ID: 45007**Message Description:** LOG_ID_VSD_SSL_BAD_HASH**Message Meaning:** SSL Finished hash mismatch**Type:** Event**Category:** SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
local	Local IP for a PPPD Connection	ip	39
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
remote	Remote IP Address	ip	39
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45009 - LOG_ID_VSD_SSL_DECRY_FAIL

Message ID: 45009**Message Description:** LOG_ID_VSD_SSL_DECRY_FAIL**Message Meaning:** SSL decryption failed**Type:** Event**Category:** SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45010 - LOG_ID_VSD_SSL_SESSION_CLOSED

Message ID: 45010**Message Description:** LOG_ID_VSD_SSL_SESSION_CLOSED**Message Meaning:** SSL session closed**Type:** Event**Category:** SYSTEM**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45011 - LOG_ID_VSD_SSL_LESS_MINOR

Message ID: 45011

Message Description: LOG_ID_VSD_SSL_LESS_MINOR

Message Meaning: SSL minor version is less than configured minimum value

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
minminor		uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
recvminor		uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45012 - LOG_ID_VSD_SSL_REACH_MAX_CON

Message ID: 45012

Message Description: LOG_ID_VSD_SSL_REACH_MAX_CON

Message Meaning: SSL maximum connection limit reached

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45013 - LOG_ID_VSD_SSL_NOT_SUPPORT_CS

Message ID: 45013

Message Description: LOG_ID_VSD_SSL_NOT_SUPPORT_CS

Message Meaning: SSL CipherSuites not supported

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45016 - LOG_ID_VSD_SSL_HS_FIN

Message ID: 45016

Message Description: LOG_ID_VSD_SSL_HS_FIN

Message Meaning: SSL handshake completed

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45017 - LOG_ID_VSD_SSL_HS_TOO_LONG

Message ID: 45017

Message Description: LOG_ID_VSD_SSL_HS_TOO_LONG

Message Meaning: SSL handshake too long

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
len	SSL Handshake Message Length	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
max	Max Value	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45018 - LOG_ID_VSD_SSL_MORE_MINOR

Message ID: 45018

Message Description: LOG_ID_VSD_SSL_MORE_MINOR

Message Meaning: SSL minor version larger than configured maximum value

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
maxminor		uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
recvminor		uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45019 - LOG_ID_VSD_SSL_SENT_ALERT_ERR

Message ID: 45019**Message Description:** LOG_ID_VSD_SSL_SENT_ALERT_ERR**Message Meaning:** SSL alert error sent**Type:** Event**Category:** SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45020 - LOG_ID_VSD_SSL_SESSION_EXPIRE

Message ID: 45020**Message Description:** LOG_ID_VSD_SSL_SESSION_EXPIRE**Message Meaning:** SSL session state expired**Type:** Event**Category:** SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
addr	IP Address	string	80
created	Sessions Created	string	64
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
session_id	Session ID	uint32	10
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45021 - LOG_ID_VSD_SSL_SENT_ALERT

Message ID: 45021**Message Description:** LOG_ID_VSD_SSL_SENT_ALERT**Message Meaning:** SSL alert sent**Type:** Event**Category:** SYSTEM**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45022 - LOG_ID_VSD_SSL_RCV_CH

Message ID: 45022

Message Description: LOG_ID_VSD_SSL_RCV_CH

Message Meaning: SSL Client Hello received

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
major	Major Version	uint8	
minor	SSL Minor Version	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
ssl2		uint8	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45023 - LOG_ID_VSD_SSL_RCV_SH

Message ID: 45023

Message Description: LOG_ID_VSD_SSL_RCV_SH

Message Meaning: SSL Server Hello received

Type: Event**Category:** SYSTEM**Severity:** Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
cipher	Encryption Type	uint16	
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
major	Major Version	uint8	
minor	SSL Minor Version	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45024 - LOG_ID_VSD_SSL_SENT_SH

Message ID: 45024

Message Description: LOG_ID_VSD_SSL_SENT_SH

Message Meaning: SSL Server Hello sent

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
cipher	Encryption Type	uint16	
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
major	Major Version	uint8	
minor	SSL Minor Version	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45025 - LOG_ID_VSD_SSL_RCV_ALERT

Message ID: 45025

Message Description: LOG_ID_VSD_SSL_RCV_ALERT

Message Meaning: SSL alert received

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45026 - LOG_ID_VSD_SSL_RCV_ALERT_DEBUG

Message ID: 45026

Message Description: LOG_ID_VSD_SSL_RCV_ALERT_DEBUG

Message Meaning: SSL alert received

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45027 - LOG_ID_VSD_SSL_INVALID_CONT_TYPE

Message ID: 45027

Message Description: LOG_ID_VSD_SSL_INVALID_CONT_TYPE

Message Meaning: SSL Content Type invalid

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45029 - LOG_ID_VSD_SSL_BAD_CCS_LEN

Message ID: 45029

Message Description: LOG_ID_VSD_SSL_BAD_CCS_LEN

Message Meaning: SSL ChangeCipherSpec length incorrect

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45031 - LOG_ID_VSD_SSL_BAD_DH

Message ID: 45031

Message Description: LOG_ID_VSD_SSL_BAD_DH

Message Meaning: SSL Diffie-Hellman value invalid

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
max	Max Value	uint8	
min	Minimum Value	uint8	

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
policyid	Policy ID	uint32	10
received	Received Packet	uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45032 - LOG_ID_VSD_SSL_PUB_KEY_TOO_BIG

Message ID: 45032

Message Description: LOG_ID_VSD_SSL_PUB_KEY_TOO_BIG

Message Meaning: SSL certificate public key too big for SSL offloading

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10
len	SSL Handshake Message Length	uint32	10
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
max	Max Value	uint8	
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45033 - LOG_ID_VSD_SSL_NOT_SUPPORT_CM

Message ID: 45033

Message Description: LOG_ID_VSD_SSL_NOT_SUPPORT_CM

Message Meaning: SSL Compression Methods are not supported

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45034 - LOG_ID_VSD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH

Message ID: 45034

Message Description: LOG_ID_VSD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH

Message Meaning: Server Key Exchange hash algorithm mismatch

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
identidx	use 'id' ?	uint32	10

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
received	Received Packet	uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45035 - LOG_ID_VSD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH

Message ID: 45035

Message Description: LOG_ID_VSD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH

Message Meaning: Server Key Exchange signature algorithm mismatch

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
expectedsignature	Expected Signature	uint8	
identidx	use 'id' ?	uint32	10
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
policyid	Policy ID	uint32	10
receivedsignature	Received Signature	uint8	
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

45057 - LOG_ID_FCC_ADD

Message ID: 45057

Message Description: LOG_ID_FCC_ADD

Message Meaning: FortiClient connection added

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	32
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
used_for_type	Connection for the type	uint32	10
user	User Name	string	256
vd	Virtual Domain Name	string	32

45058 - LOG_ID_FCC_CLOSE

Message ID: 45058

Message Description: LOG_ID_FCC_CLOSE

Message Meaning: FortiClient connection closed

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45061 - LOG_ID_FCC_CLOSE_BY_TYPE

Message ID: 45061

Message Description: LOG_ID_FCC_CLOSE_BY_TYPE

Message Meaning: FortiClient connection closed by type

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
action	EndPoint Action	string	32
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
ip	Source IP	ip	39
level	Log Level	string	11
license_limit	Maximum Number of FortiClients for the License	string	32
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
name	Display Name of the Connection	string	128
status	Status	string	23
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
used_for_type	Connection for the type	uint32	10
user	User Name	string	256
vd	Virtual Domain Name	string	32

45071 - LOG_ID_FCC_VULN_SCAN

Message ID: 45071

Message Description: LOG_ID_FCC_VULN_SCAN

Message Meaning: FortiClient Vulnerability Scan

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
cveid	CVE ID	string	720
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
scantime		uint64	20
severity		string	10

Log Field Name	Description	Data Type	Length
srcip		ip	39
srcmac		string	17
srcname		string	64
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32
vendorurl		string	256
vulncat	Vulnerability Category	string	32
vulnid		uint32	10
vulnname		string	128

45081 - LOG_ID_FCC_COMPL_CHANGE

Message ID: 45081

Message Description: LOG_ID_FCC_COMPL_CHANGE

Message Meaning: FortiClient compliance state changed

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcname		string	64
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45082 - LOG_ID_FCC_NOT_COMPL

Message ID: 45082

Message Description: LOG_ID_FCC_NOT_COMPL

Message Meaning: FortiClient not compliant

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45083 - LOG_ID_FCC_NOT_COMPL_DEBUG

Message ID: 45083

Message Description: LOG_ID_FCC_NOT_COMPL_DEBUG

Message Meaning: FortiClient not compliant

Type: Event

Category: ENDPOINT

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
devtype		string	32
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
srcip		ip	39
srcmac		string	17
srcport		uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45100 - LOG_ID_EC_REG_FAIL_LIMIT

Message ID: 45100

Message Description: LOG_ID_EC_REG_FAIL_LIMIT

Message Meaning: FortiClient registration failed

Type: Event

Category: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45101 - LOG_ID_EC_REG_SUCCEED

Message ID: 45101

Message Description: LOG_ID_EC_REG_SUCCEED

Message Meaning: FortiClient registered

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45102 - LOG_ID_EC_REG_RENEWED

Message ID: 45102

Message Description: LOG_ID_EC_REG_RENEWED

Message Meaning: FortiClient registration renewed

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45103 - LOG_ID_EC_REG_BLOCK

Message ID: 45103

Message Description: LOG_ID_EC_REG_BLOCK

Message Meaning: FortiClient registration blocked

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45104 - LOG_ID_EC_REG_UNBLOCK

Message ID: 45104

Message Description: LOG_ID_EC_REG_UNBLOCK

Message Meaning: FortiClient registration unblocked

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45105 - LOG_ID_EC_REG_DEREG

Message ID: 45105

Message Description: LOG_ID_EC_REG_DEREG

Message Meaning: FortiClient deregistered

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45106 - LOG_ID_EC_REG_LIC_UPGRADED

Message ID: 45106

Message Description: LOG_ID_EC_REG_LIC_UPGRADED

Message Meaning: FortiClient registration license upgraded

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45107 - LOG_ID_EC_CONF_DISTRIBUTED

Message ID: 45107

Message Description: LOG_ID_EC_CONF_DISTRIBUTED

Message Meaning: FortiClient configuration distributed

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45108 - LOG_ID_EC_FTCL_UNREG

Message ID: 45108**Message Description:** LOG_ID_EC_FTCL_UNREG**Message Meaning:** FortiClient unregistered**Type:** Event**Category:** ENDPOINT**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45109 - LOG_ID_EC_FTCL_LOGOFF

Message ID: 45109

Message Description: LOG_ID_EC_FTCL_LOGOFF

Message Meaning: FortiClient logged off

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45110 - LOG_ID_EC_FTCL_ENABLE_NOTSYNC

Message ID: 45110

Message Description: LOG_ID_EC_FTCL_ENABLE_NOTSYNC

Message Meaning: FortiClient synchronization disabled

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45111 - LOG_ID_EC_REG_SYNC_FAIL

Message ID: 45111

Message Description: LOG_ID_EC_REG_SYNC_FAIL

Message Meaning: FortiClient synchronization failed

Type: Event

Category: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45112 - LOG_ID_EC_REG_FAIL_KEY

Message ID: 45112

Message Description: LOG_ID_EC_REG_FAIL_KEY

Message Meaning: FortiClient registration failed due to wrong registration key

Type: Event

Category: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45113 - LOG_ID_EC_REG_FAIL_BLOCKED

Message ID: 45113

Message Description: LOG_ID_EC_REG_FAIL_BLOCKED

Message Meaning: FortiClient registration failed due to blocked UID

Type: Event

Category: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45114 - LOG_ID_EC_REG_QUARANTINE

Message ID: 45114**Message Description:** LOG_ID_EC_REG_QUARANTINE**Message Meaning:** FortiClient quarantined**Type:** Event**Category:** ENDPOINT**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45115 - LOG_ID_EC_REG_UNQUARANTINE

Message ID: 45115

Message Description: LOG_ID_EC_REG_UNQUARANTINE

Message Meaning: FortiClient un-quarantined

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45116 - LOG_ID_EC_REG_UNQUARANTINE_ALL

Message ID: 45116

Message Description: LOG_ID_EC_REG_UNQUARANTINE_ALL

Message Meaning: All FortiClient un-quarantined

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45117 - LOG_ID_EC_REG_FAIL_VER

Message ID: 45117

Message Description: LOG_ID_EC_REG_FAIL_VER

Message Meaning: FortiClient registration failed due to version too low

Type: Event

Category: ENDPOINT

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
fctuid		string	32
hostname	Endpoint Hostname	string	128
interface	Interface	string	32
ip	Source IP	ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
subtype	Log subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

45151 - LOG_ID_EVENT_DSSCC_FAIL

Message ID: 45151

Message Description: LOG_ID_EVENT_DSSCC_FAIL

Message Meaning: PCI DSS compliance check failed

Type: Event

Category: COMPLIANCE-CHECK

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Module	string	32
msg	Log Message	string	
reason	Reason	string	256
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45152 - LOG_ID_EVENT_DSSCC_PASS

Message ID: 45152**Message Description:** LOG_ID_EVENT_DSSCC_PASS**Message Meaning:** PCI DSS compliance check passed**Type:** Event**Category:** COMPLIANCE-CHECK**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
module	Module	string	32
msg	Log Message	string	
reason	Reason	string	256
result	Result	string	31
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

45161 - LOG_ID_EVENT_DSSCC_EXEC

Message ID: 45161

Message Description: LOG_ID_EVENT_DSSCC_EXEC

Message Meaning: PCI DSS compliance check executed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
ui	User Interface	string	64
user	User Name	string	256
vd	Virtual Domain Name	string	32

46000 - LOG_ID_VIP_REAL_SVR_ENA

Message ID: 46000

Message Description: LOG_ID_VIP_REAL_SVR_ENA

Message Meaning: VIP real server enabled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46001 - LOG_ID_VIP_REAL_SVR_DISA

Message ID: 46001

Message Description: LOG_ID_VIP_REAL_SVR_DISA

Message Meaning: VIP real server disabled

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46002 - LOG_ID_VIP_REAL_SVR_UP

Message ID: 46002

Message Description: LOG_ID_VIP_REAL_SVR_UP

Message Meaning: VIP real server up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46003 - LOG_ID_VIP_REAL_SVR_DOWN

Message ID: 46003

Message Description: LOG_ID_VIP_REAL_SVR_DOWN

Message Meaning: VIP real server down

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN

Message ID: 46004**Message Description:** LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN**Message Meaning:** VIP real server entered hold-down**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN

Message ID: 46005

Message Description: LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN

Message Meaning: VIP real server health check failed during hold-down

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
port	Port Number	uint16	5
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46006 - LOG_ID_VIP_REAL_SVR_FAIL

Message ID: 46006

Message Description: LOG_ID_VIP_REAL_SVR_FAIL

Message Meaning: VIP real server health check failed

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
monitor-name	Health Monitor Type	string	35
monitor-type	Health Monitor Name	string	32
msg	Message Text	string	
port	Port Number	uint16	5

Log Field Name	Description	Data Type	Length
server	Server IP Address	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32
vip	Virtual IP	string	64

46400 - LOG_ID_EVENT_EXT_SYS

Message ID: 46400

Message Description: LOG_ID_EVENT_EXT_SYS

Message Meaning: FortiExtender system activity

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46401 - LOG_ID_EVENT_EXT_LOCAL

Message ID: 46401

Message Description: LOG_ID_EVENT_EXT_LOCAL

Message Meaning: FortiExtender AC activity

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46402 - LOG_ID_EVENT_EXT_REMOTE

Message ID: 46402

Message Description: LOG_ID_EVENT_EXT_REMOTE

Message Meaning: Remote FortiExtender activity

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46403 - LOG_ID_EVENT_EXT_LOCAL_ERROR

Message ID: 46403

Message Description: LOG_ID_EVENT_EXT_LOCAL_ERROR

Message Meaning: FortiExtender AC activity error

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
ip		ip	39
level	Log Level	string	11
logdesc	Log Description	string	

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Message Text	string	
sn	Serial Number	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46501 - LOG_ID_INTERNAL_LTE_MODEM_DETECTION

Message ID: 46501

Message Description: LOG_ID_INTERNAL_LTE_MODEM_DETECTION

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46502 - LOG_ID_INTERNAL_LTE_MODEM_GPSD

Message ID: 46502

Message Description: LOG_ID_INTERNAL_LTE_MODEM_GPSD

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46503 - LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION

Message ID: 46503

Message Description: LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46504 - LOG_ID_INTERNAL_LTE_MODEM_BILLD

Message ID: 46504

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BILLD

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46505 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED

Message ID: 46505

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46506 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG

Message ID: 46506

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46507 - LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE

Message ID: 46507

Message Description: LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46508 - LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION

Message ID: 46508

Message Description: LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46509 - LOG_ID_INTERNAL_LTE_MODEM_REBOOT

Message ID: 46509

Message Description: LOG_ID_INTERNAL_LTE_MODEM_REBOOT

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46510 - LOG_ID_INTERNAL_LTE_MODEM_OP_MODE

Message ID: 46510

Message Description: LOG_ID_INTERNAL_LTE_MODEM_OP_MODE

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46511 - LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF

Message ID: 46511

Message Description: LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46512 - LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE

Message ID: 46512

Message Description: LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46513 - LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION

Message ID: 46513

Message Description: LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46514 - LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER

Message ID: 46514

Message Description: LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46515 - LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR

Message ID: 46515

Message Description: LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

46900 - LOG_ID_POE_STATUS_REPORT

Message ID: 46900

Message Description: LOG_ID_POE_STATUS_REPORT

Message Meaning: POE device status report

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47201 - LOG_ID_AMC_ENTER_BYPASS

Message ID: 47201

Message Description: LOG_ID_AMC_ENTER_BYPASS

Message Meaning: AMC card entered bypass mode

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47202 - LOG_ID_AMC_EXIT_BYPASS

Message ID: 47202

Message Description: LOG_ID_AMC_EXIT_BYPASS

Message Meaning: AMC card exited bypass mode

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47203 - LOG_ID_ENTER_BYPASS

Message ID: 47203

Message Description: LOG_ID_ENTER_BYPASS

Message Meaning: Bypass ports pair entered bypass mode

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

47204 - LOG_ID_EXIT_BYPASS

Message ID: 47204

Message Description: LOG_ID_EXIT_BYPASS

Message Meaning: Bypass ports pair exited bypass mode

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48000 - LOG_ID_WAD_SSL_RCV_HS

Message ID: 48000

Message Description: LOG_ID_WAD_SSL_RCV_HS

Message Meaning: SSL handshake received

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48001 - LOG_ID_WAD_SSL_RCV_WRG_HS

Message ID: 48001

Message Description: LOG_ID_WAD_SSL_RCV_WRG_HS

Message Meaning: SSL handshake length invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48002 - LOG_ID_WAD_SSL_SENT_HS

Message ID: 48002

Message Description: LOG_ID_WAD_SSL_SENT_HS

Message Meaning: SSL handshake sent

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48003 - LOG_ID_WAD_SSL_WRG_HS_LEN

Message ID: 48003

Message Description: LOG_ID_WAD_SSL_WRG_HS_LEN

Message Meaning: SSL handshake length invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48004 - LOG_ID_WAD_SSL_RCV_CCS

Message ID: 48004

Message Description: LOG_ID_WAD_SSL_RCV_CCS

Message Meaning: SSL ChangeCipherSpec received

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL

Message ID: 48005

Message Description: LOG_ID_WAD_SSL_RSA_DH_FAIL

Message Meaning: RSA verification of Diffie-Hellman parameters failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48006 - LOG_ID_WAD_SSL_SENT_CCS

Message ID: 48006

Message Description: LOG_ID_WAD_SSL_SENT_CCS

Message Meaning: SSL ChangeCipherSpec sent

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48007 - LOG_ID_WAD_SSL_BAD_HASH

Message ID: 48007

Message Description: LOG_ID_WAD_SSL_BAD_HASH

Message Meaning: SSL Finished hash mismatch

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
ssllocal		string	76

Log Field Name	Description	Data Type	Length
sslremote		string	76
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48009 - LOG_ID_WAD_SSL_DECRY_FAIL

Message ID: 48009

Message Description: LOG_ID_WAD_SSL_DECRY_FAIL

Message Meaning: SSL decryption failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
reason	Reason	string	256
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48011 - LOG_ID_WAD_SSL_LESS_MINOR

Message ID: 48011

Message Description: LOG_ID_WAD_SSL_LESS_MINOR

Message Meaning: SSL minor version less than configured minimum value

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS

Message ID: 48013

Message Description: LOG_ID_WAD_SSL_NOT_SUPPORT_CS

Message Meaning: SSL Cipher Suites not supported

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48016 - LOG_ID_WAD_SSL_HS_FIN

Message ID: 48016

Message Description: LOG_ID_WAD_SSL_HS_FIN

Message Meaning: SSL handshake completed

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48017 - LOG_ID_WAD_SSL_HS_TOO_LONG

Message ID: 48017

Message Description: LOG_ID_WAD_SSL_HS_TOO_LONG

Message Meaning: SSL handshake too long

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
handshake	Handshake	string	32
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48019 - LOG_ID_WAD_SSL_SENT_ALERT

Message ID: 48019

Message Description: LOG_ID_WAD_SSL_SENT_ALERT

Message Meaning: SSL alert sent

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48023 - LOG_ID_WAD_SSL_RCV_ALERT

Message ID: 48023

Message Description: LOG_ID_WAD_SSL_RCV_ALERT

Message Meaning: SSL alert received

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE

Message ID: 48027

Message Description: LOG_ID_WAD_SSL_INVALID_CONT_TYPE

Message Meaning: SSL Content Type invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN

Message ID: 48029

Message Description: LOG_ID_WAD_SSL_BAD_CCS_LEN

Message Meaning: SSL ChangeCipherSpec length invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48031 - LOG_ID_WAD_SSL_BAD_DH

Message ID: 48031

Message Description: LOG_ID_WAD_SSL_BAD_DH

Message Meaning: SSL Diffie-Hellman value invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG

Message ID: 48032

Message Description: LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG

Message Meaning: Certificate's public key too long

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT

Message ID: 48038

Message Description: LOG_ID_WAD_SSL_RCV_FATAL_ALERT

Message Meaning: SSL Fatal Alert received

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT

Message ID: 48039

Message Description: LOG_ID_WAD_SSL_SENT_FATAL_ALERT

Message Meaning: SSL fatal alert sent

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
action	Action	string	32
alert	Alert	string	256
date	Date	string	10
desc	Description	string	128
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48101 - LOG_ID_WAD_AUTH_FAIL_PSK

Message ID: 48101

Message Description: LOG_ID_WAD_AUTH_FAIL_PSK

Message Meaning: WANOpt peer PSK authentication failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
host	Host Name	string	256
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48102 - LOG_ID_WAD_AUTH_FAIL_OTH

Message ID: 48102

Message Description: LOG_ID_WAD_AUTH_FAIL_OTH

Message Meaning: WANOpt peer authentication failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
authgrp	Authorization Group	string	36
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log Message	string	
peer		string	36
policyid	Policy ID	uint32	10
serial	Serial Number	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48300 - LOG_ID_WRG_SVR_FGT_CONF

Message ID: 48300

Message Description: LOG_ID_WRG_SVR_FGT_CONF

Message Meaning: WANOpt server side FortiGate not properly configured

Type: Event

Category: WAD

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

48301 - LOG_ID_UNEXP_APP_TYPE

Message ID: 48301

Message Description: LOG_ID_UNEXP_APP_TYPE

Message Meaning: WANOpt unexpected application type

Type: Event

Category: WAD

Severity: Critical

Log Field Name	Description	Data Type	Length
app-type	Address Type	string	64
date	Date	string	10
devid	Device ID	string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
session_id	Session ID	uint32	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

51000 - LOG_ID_NB_TBL_CHG

Message ID: 51000

Message Description: LOG_ID_NB_TBL_CHG

Message Meaning: Neighbor table changed

Type: Event

Category: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
mac	Mac Address	string	17
msg	Message	string	
service	Name of Service	string	64
srcip		ip	39
src_int	Source Interface	string	64
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

52000 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY

Message ID: 52000

Message Description: LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY

Message Meaning: Security Rating summary

Type: Event

Category: SECURITY-AUDIT

Severity: Notice

Log Field Name	Description	Data Type	Length
auditscore		string	20
audittime		uint64	
criticalcount		uint32	
date		string	10
devid		string	16
eventtime		uint64	20
highcount		uint32	
level		string	11
logdesc		string	
logid		string	10
lowcount		uint32	
mediumcount		uint32	
passedcount		uint32	
subtype		string	20
time		string	8
type		string	16
vd		string	32

52001 - LOG_ID_EVENT_SECURITY_AUDIT_DEVICE_SUMMARY

Message ID: 52001

Message Description: LOG_ID_EVENT_SECURITY_AUDIT_DEVICE_SUMMARY

Message Meaning: Device audit summary

Type: Event

Category: SECURITY-AUDIT**Severity:** Notice

Log Field Name	Description	Data Type	Length
auditscore		string	20
audittime		uint64	
criticalcount		uint32	
date		string	10
devid		string	16
eventtime		uint64	20
highcount		uint32	
level		string	11
logdesc		string	
logid		string	10
lowcount		uint32	
mediumcount		uint32	
passedcount		uint32	
subtype		string	20
time		string	8
type		string	16
vd		string	32

52002 - LOG_ID_EVENT_SECURITY_AUDIT_CHECK_RESULT

Message ID: 52002**Message Description:** LOG_ID_EVENT_SECURITY_AUDIT_CHECK_RESULT**Message Meaning:** Test result**Type:** Event**Category:** SECURITY-AUDIT**Severity:** Notice

Log Field Name	Description	Data Type	Length
auditscore		string	20

Log Field Name	Description	Data Type	Length
audittime		uint64	
checkname		string	128
checkresult		string	10
checkseverity		string	10
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	
logid		string	10
sn		string	64
subtype		string	20
time		string	8
type		string	16
vd		string	32

52003 - LOG_ID_EVENT_SECURITY_AUDIT_CHECK_RESULT_NOT_PASS

Message ID: 52003

Message Description: LOG_ID_EVENT_SECURITY_AUDIT_CHECK_RESULT_NOT_PASS

Message Meaning: Test result not pass

Type: Event

Category: SECURITY-AUDIT

Severity: Alert

Log Field Name	Description	Data Type	Length
auditscore		string	20
audittime		uint64	
checkname		string	128
checkresult		string	10
checkseverity		string	10

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
eventtime		uint64	20
level		string	11
logdesc		string	
logid		string	10
sn		string	64
subtype		string	20
time		string	8
type		string	16
vd		string	32

53000 - LOG_ID_SDNC_CONNECTED

Message ID: 53000

Message Description: LOG_ID_SDNC_CONNECTED

Message Meaning: SDNC connected

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

53001 - LOG_ID_SDNC_DISCONNECTED

Message ID: 53001

Message Description: LOG_ID_SDNC_DISCONNECTED

Message Meaning: SDNC disconnected

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
action	Action	string	32
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
user	User Name	string	256
vd	Virtual Domain Name	string	32

53002 - LOG_ID_SDNC_SUBSCRIBE

Message ID: 53002

Message Description: LOG_ID_SDNC_SUBSCRIBE

Message Meaning: SDNC subscribe

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

53003 - LOG_ID_SDNC_UNSUBSCRIBE

Message ID: 53003

Message Description: LOG_ID_SDNC_UNSUBSCRIBE

Message Meaning: SDNC unsubscribe

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid	Device ID	string	16
eventtime		uint64	20
level	Log Level	string	11
logdesc	Log Description	string	
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Message Text	string	
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
vd	Virtual Domain Name	string	32

GTP

41216 - LOGID_GTP_FORWARD

Message ID: 41216

Message Description: LOGID_GTP_FORWARD

Message Meaning: GTP forward

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41217 - LOGID_GTP_DENY

Message ID: 41217

Message Description: LOGID_GTP_DENY

Message Meaning: GTP deny

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41218 - LOGID_GTP_RATE_LIMIT

Message ID: 41218

Message Description: LOGID_GTP_RATE_LIMIT

Message Meaning: GTP rate limit

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41219 - LOGID_GTP_STATE_INVALID

Message ID: 41219

Message Description: LOGID_GTP_STATE_INVALID

Message Meaning: GTP state invalid

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41220 - LOGID_GTP_TUNNEL_LIMIT

Message ID: 41220

Message Description: LOGID_GTP_TUNNEL_LIMIT

Message Meaning: Tunnel limit GTP message. These messages occur only when the maximum number of GTP tunnels is reached. No new tunnels are created when the maximum number is reached

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3

Log Field Name	Description	Data Type	Length
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-gsn	User Plane GSN	ip	39
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41221 - LOGID_GTP_TRAFFIC_COUNT

Message ID: 41221

Message Description: LOGID_GTP_TRAFFIC_COUNT

Message Meaning: Statistic summary information when the GTP tunnel is being torn down

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128

Log Field Name	Description	Data Type	Length
c-bytes	Control Plane Data Bytes	uint64	20
c-ggsn	Control Plane GGSN IP Address	ip	39
c-ggsn-teid	Control Plane GGSN Tunnel Endpoint Identifier	uint32	10
c-pkts	Control Plane Packets	uint64	20
c-sgsn	Control Plane SGSN IP Address	ip	39
c-sgsn-teid	Control Plane SGSN Tunnel Endpoint Identifier	uint32	10
date	Date	string	10
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-bytes	User Plane Data Bytes	uint64	20
u-ggsn	user plane ggsn IP address	ip	39

Log Field Name	Description	Data Type	Length
u-ggsn-teid	user plane ggsn teid	uint32	10
u-pkts	User Plane Packets	uint64	20
u-sgsn	user plane sgsn IP address	ip	39
u-sgsn-teid	user plane sgsn tunnel endpoint identifier	uint32	10
uli		string	32
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41222 - LOGID_GTP_USER_DATA

Message ID: 41222

Message Description: LOGID_GTP_USER_DATA

Message Meaning: GTP user data

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
profile	Profile Name	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512

Log Field Name	Description	Data Type	Length
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
user_data	user traffic content inside gtp-u tunnel	string	256
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41223 - LOGID_GTPV2_FORWARD

Message ID: 41223

Message Description: LOGID_GTPV2_FORWARD

Message Meaning: GTPv2 forward message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3

Log Field Name	Description	Data Type	Length
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41224 - LOGID_GTPV2_DENY

Message ID: 41224

Message Description: LOGID_GTPV2_DENY

Message Meaning: GTPv2 deny message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41225 - LOGID_GTPV2_RATE_LIMIT

Message ID: 41225

Message Description: LOGID_GTPV2_RATE_LIMIT

Message Meaning: GTPv2 rate limit message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41226 - LOGID_GTPV2_STATE_INVALID

Message ID: 41226

Message Description: LOGID_GTPV2_STATE_INVALID

Message Meaning: GTPv2 state invalid message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41227 - LOGID_GTPV2_TUNNEL_LIMIT

Message ID: 41227

Message Description: LOGID_GTPV2_TUNNEL_LIMIT

Message Meaning: Tunnel limit GTP (version 2) message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128

Log Field Name	Description	Data Type	Length
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cptheid	Control Plane teid (either downlink or uplink)	uint32	10
date	Date	string	10
dstport	Destination Port	uint16	5
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41228 - LOGID_GTPV2_TRAFFIC_COUNT

Message ID: 41228

Message Description: LOGID_GTPV2_TRAFFIC_COUNT

Message Meaning: Statistic summary information when the GTPv2 tunnel is being torn down

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-bytes	Control Plane Data Bytes	uint64	20
c-pkts	Control Plane Packets	uint64	20
cpdladdr	Control Plane Downlink IP Address	ip	39
cpdlisraddr	Control Plane ISR Downlink IP Address	ip	39
cpdlisrteid	control plane ISR downlink tunnel endpoint identifier	uint32	10
cpdlteid	control plane downlink tunnel endpoint identifier	uint32	10
cpuladdr	control plane uplink IP address	ip	39
cpulteid	control plane uplink teid	uint32	10
date	Date	string	10
duration	tunnel duration	uint32	10
end-usr-address	End user IP Address	ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14

Log Field Name	Description	Data Type	Length
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
u-bytes	User Plane Data Bytes	uint64	20
u-pkts	User Plane Packets	uint64	20
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41229 - LOGID_GTPU_FORWARD

Message ID: 41229

Message Description: LOGID_GTPU_FORWARD

Message Meaning: GTPU forward message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3

Log Field Name	Description	Data Type	Length
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41230 - LOGID_GTPU_DENY

Message ID: 41230

Message Description: LOGID_GTPU_DENY

Message Meaning: GTPU deny message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
vd	Virtual Domain Name	string	32
version	Version	uint32	64

IPS

16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP

Message ID: 16384

Message Description: LOGID_ATTCK_SIGNATURE_TCP_UDP

Message Meaning: Attack detected by UCP/TCP signature

Type: IPS

Category: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040

Log Field Name	Description	Data Type	Length
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

16385 - LOGID_ATTCK_SIGNATURE_ICMP

Message ID: 16385

Message Description: LOGID_ATTCK_SIGNATURE_ICMP

Message Meaning: Attack detected by ICMP signature

Type: IPS

Category: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrold		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
icmpcode	Destination Port of the ICMP message	string	6
icmpid	Source port of the ICMP message	string	8
icmptype	The type of ICMP message	string	6
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32

16386 - LOGID_ATTCK_SIGNATURE_OTHERS

Message ID: 16386

Message Description: LOGID_ATTCK_SIGNATURE_OTHERS

Message Meaning: Attack detected by other signature

Type: IPS

Category: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	64
dstintfrold		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
ref	URL of the FortiGuard IPS database entry for the attack.	string	
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

16399 - LOGID_ATTACK_MALICIOUS_URL

Message ID: 16399

Message Description: LOGID_ATTACK_MALICIOUS_URL

Message Meaning: Attack detected by a malicious URL

Type: IPS

Category: MALICIOUS-URL

Severity: Alert

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256

Log Field Name	Description	Data Type	Length
attackcontext		string	2040
attackcontextid		string	10
attackid		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
eventtime		uint64	20
eventtype		string	32
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
ref		string	
service		string	36
sessionid		uint32	10
severity		string	8
srcintf		string	64
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip		ip	39
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
url		string	512
user		string	256
vd		string	32

Traffic

2 - LOG_ID_TRAFFIC_ALLOW

Message ID: 2

Message Description: LOG_ID_TRAFFIC_ALLOW

Message Meaning: Allowed traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17

Log Field Name	Description	Data Type	Length
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37

Log Field Name	Description	Data Type	Length
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
transport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwvlanid		uint32	10

3 - LOG_ID_TRAFFIC_DENY

Message ID: 3

Message Description: LOG_ID_TRAFFIC_DENY

Message Meaning: Traffic violation

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66

Log Field Name	Description	Data Type	Length
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwpvlanid		uint32	10

4 - LOG_ID_TRAFFIC_OTHER_START

Message ID: 4

Message Description: LOG_ID_TRAFFIC_OTHER_START

Message Meaning: Traffic other session start

Type: Traffic**Category:** FORWARD**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10

Log Field Name	Description	Data Type	Length
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36

Log Field Name	Description	Data Type	Length
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwvlanid		uint32	10

5 - LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW

Message ID: 5

Message Description: LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW

Message Meaning: Traffic allowed ICMP

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66

Log Field Name	Description	Data Type	Length
dstosname		string	66
dstosversion		string	66
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwvlanid		uint32	10

6 - LOG_ID_TRAFFIC_OTHER_ICMP_DENY

Message ID: 6

Message Description: LOG_ID_TRAFFIC_OTHER_ICMP_DENY

Message Meaning: Traffic denied ICMP

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66

Log Field Name	Description	Data Type	Length
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37

Log Field Name	Description	Data Type	Length
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwpvlanid		uint32	10

7 - LOG_ID_TRAFFIC_OTHER_INVALID

Message ID: 7

Message Description: LOG_ID_TRAFFIC_OTHER_INVALID

Message Meaning: Traffic other invalid

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66

Log Field Name	Description	Data Type	Length
comment		string	1024
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
fctuid		string	32
group	User group name	string	64
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

8 - LOG_ID_TRAFFIC_WANOPT

Message ID: 8

Message Description: LOG_ID_TRAFFIC_WANOPT

Message Meaning: WAN optimization traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
dstcountry	Country name for the destination IP	string	64

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
fctuid		string	32
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
polycname		string	36
policytype		string	24
poluid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39

Log Field Name	Description	Data Type	Length
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint32	10
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint32	10

9 - LOG_ID_TRAFFIC_WEBCACHE

Message ID: 9

Message Description: LOG_ID_TRAFFIC_WEBCACHE

Message Meaning: Web cache traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64

Log Field Name	Description	Data Type	Length
apprisk	Application Risk Level	string	16
comment		string	1024
countwaf		uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36

Log Field Name	Description	Data Type	Length
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint32	10

Log Field Name	Description	Data Type	Length
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint32	10

10 - LOG_ID_TRAFFIC_EXPLICIT_PROXY

Message ID: 10

Message Description: LOG_ID_TRAFFIC_EXPLICIT_PROXY

Message Meaning: Explicit proxy traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
comment		string	1024
countwaf		uint32	10
craction	Action performed by Client Reputation	uint32	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
dstcountry	Country name for the destination IP	string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
srccountry	Country name for Source IP	string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5

Log Field Name	Description	Data Type	Length
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint32	10
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint32	10

11 - LOG_ID_TRAFFIC_FAIL_CONN

Message ID: 11

Message Description: LOG_ID_TRAFFIC_FAIL_CONN

Message Meaning: Failed connection attempts

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
centralnatid	Central NAT ID	uint32	10
comment		string	1024
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid	Device serial number	string	16
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstname	The destination name.	string	66
dstport	Destination Port	uint16	5
dstssid	Destination SSID	string	33
dstuuid	UUID of the Destination IP address	string	37
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
sessionid	Session ID	uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32

12 - LOG_ID_TRAFFIC_MULTICAST

Message ID: 12

Message Description: LOG_ID_TRAFFIC_MULTICAST

Message Meaning: Multicast traffic

Type: Traffic

Category: MULTICAST

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66

Log Field Name	Description	Data Type	Length
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

13 - LOG_ID_TRAFFIC_END_FORWARD

Message ID: 13

Message Description: LOG_ID_TRAFFIC_END_FORWARD

Message Meaning: Forward traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10

Log Field Name	Description	Data Type	Length
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apasn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66

Log Field Name	Description	Data Type	Length
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
polycymode		string	8
polycynname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256

Log Field Name	Description	Data Type	Length
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwvlanid		uint32	10

14 - LOG_ID_TRAFFIC_END_LOCAL

Message ID: 14

Message Description: LOG_ID_TRAFFIC_END_LOCAL

Message Meaning: Local traffic

Type: Traffic

Category: LOCAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66

Log Field Name	Description	Data Type	Length
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
poluuid	UUID of the Firewall Policy	string	37

Log Field Name	Description	Data Type	Length
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39

Log Field Name	Description	Data Type	Length
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

15 - LOG_ID_TRAFFIC_START_FORWARD

Message ID: 15

Message Description: LOG_ID_TRAFFIC_START_FORWARD

Message Meaning: Forward traffic session start

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
apsn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10

Log Field Name	Description	Data Type	Length
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwpvlanid		uint32	10

16 - LOG_ID_TRAFFIC_START_LOCAL

Message ID: 16

Message Description: LOG_ID_TRAFFIC_START_LOCAL

Message Meaning: Local traffic session start

Type: Traffic

Category: LOCAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66

Log Field Name	Description	Data Type	Length
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
sentbyte	Sent Bytes	uint64	20
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36

Log Field Name	Description	Data Type	Length
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

17 - LOG_ID_TRAFFIC_SNIFFER

Message ID: 17

Message Description: LOG_ID_TRAFFIC_SNIFFER

Message Meaning: Sniffer traffic

Type: Traffic**Category:** SNIFFER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
collectedemail		string	66
comment		string	1024
countapp		uint32	10
countav		uint32	10
countdlp		uint32	10
countemail		uint32	10
countips		uint32	10
countweb		uint32	10
date		string	10
devid		string	16
devtype		string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66

Log Field Name	Description	Data Type	Length
dstosversion		string	66
dstport		uint16	5
dstserver		uint32	10
dstssid		string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
level		string	11
logid		string	10
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
osversion		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluid		string	37
proto		uint8	3
rcvdbyte		uint64	20
rcvdpkt		uint32	10
sentbyte		uint64	20
sentpkt		uint32	10
service		string	63

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
shaperdroprcvdbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint32	10
srcssid		string	33
srcuuid		string	37
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
unauthuser		string	66
unauthuser		string	66
unauthusersource		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user		string	256
vd		string	32
vpn		string	32
vpntype		string	14

19 - LOG_ID_TRAFFIC_BROADCAST

Message ID: 19

Message Description: LOG_ID_TRAFFIC_BROADCAST

Message Meaning: Broadcast traffic

Type: Traffic

Category: MULTICAST

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66

Log Field Name	Description	Data Type	Length
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14

20 - LOG_ID_TRAFFIC_STAT

Message ID: 20

Message Description: LOG_ID_TRAFFIC_STAT

Message Meaning: Forward traffic statistics

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10

Log Field Name	Description	Data Type	Length
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
centralnatid	Central NAT ID	uint32	10
collectedemail	Email address from Email Collection Captive Portal	string	66
comment		string	1024
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf	Destination Interface	string	32
dstintfrofe		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstosversion		string	66
dstport	Destination Port	uint16	5
dstserver		uint32	10
dstssid	Destination SSID	string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
osversion	OS version of the device	string	66
policyid	Firewall Policy ID	uint32	10
polycymode		string	8
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senteddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	63
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10

Log Field Name	Description	Data Type	Length
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint32	10
srcssid	Source SSID	string	33
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
unauthuser	Unauthenticated user name	string	66
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vwvlanid		uint32	10

21 - LOG_ID_TRAFFIC_SNIFFER_STAT

Message ID: 21

Message Description: LOG_ID_TRAFFIC_SNIFFER_STAT

Message Meaning: Sniffer traffic statistics

Type: Traffic

Category: SNIFFER

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
collectedemail		string	66
comment		string	1024
date		string	10
devid		string	16
devtype		string	32
dstcollectedemail		string	66
dstdevtype		string	32
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstosversion		string	66
dstport		uint16	5

Log Field Name	Description	Data Type	Length
dstserver		uint32	10
dstssid		string	33
dstunauthuser		string	66
dstunauthusersource		string	66
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
level		string	11
logid		string	10
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
osversion		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluuid		string	37
proto		uint8	3
rcvdbyte		uint64	20
rcvddelta		uint64	20
rcvdpkt		uint32	10
sentbyte		uint64	20
sentedelta		uint64	20
sentpkt		uint32	10
service		string	63

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
shaperdroprcvdbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint32	10
srcssid		string	33
srcuuid		string	37
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
unauthuser		string	66
unauthuser		string	66
unauthusersource		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user		string	256
vd		string	32
vpn		string	32
vpntype		string	14

VoIP

44032 - LOGID_EVENT_VOIP_SIP

Message ID: 44032

Message Description: LOGID_EVENT_VOIP_SIP

Message Meaning: Voip sip

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
from		string	128

Log Field Name	Description	Data Type	Length
kind		string	10
level		string	11
logid		string	10
policy_id		uint32	10
profile		string	64
proto		uint8	3
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
to		string	512
type		string	16
vd		string	32
voip_proto		string	4

44033 - LOGID_EVENT_VOIP_SIP_BLOCK

Message ID: 44033

Message Description: LOGID_EVENT_VOIP_SIP_BLOCK

Message Meaning: Voip sip block

Type: VoIP

Category: VOIP

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
count		uint32	10

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
from		string	128
kind		string	10
level		string	11
logid		string	10
message_type		string	16
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
request_name		string	64
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
to		string	512

Log Field Name	Description	Data Type	Length
type		string	16
vd		string	32
voip_proto		string	4

44034 - LOGID_EVENT_VOIP_SIP_FUZZING

Message ID: 44034

Message Description: LOGID_EVENT_VOIP_SIP_FUZZING

Message Meaning: Voip sip fuzzing

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	15
call_id		string	64
column		uint32	10
date		string	10
devid		string	16
dir		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
line		string	128
logid		string	10

Log Field Name	Description	Data Type	Length
malform_data		uint32	10
malform_desc		string	47
message_type		string	16
policy_id		uint32	10
profile		string	64
proto		uint8	3
request_name		string	64
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

44035 - LOGID_EVENT_VOIP_SCCP_REGISTER

Message ID: 44035

Message Description: LOGID_EVENT_VOIP_SCCP_REGISTER

Message Meaning: Voip sccp register

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39

Log Field Name	Description	Data Type	Length
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

44036 - LOGID_EVENT_VOIP_SCCP_UNREGISTER

Message ID: 44036

Message Description: LOGID_EVENT_VOIP_SCCP_UNREGISTER

Message Meaning: Voip sccp unregister

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

44037 - LOGID_EVENT_VOIP_SCCP_CALL_BLOCK

Message ID: 44037

Message Description: LOGID_EVENT_VOIP_SCCP_CALL_BLOCK

Message Meaning: Voip sccp call block

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_port		uint16	5
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
logid		string	10
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
reason		string	128
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23

Log Field Name	Description	Data Type	Length
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

44038 - LOGID_EVENT_VOIP_SCCP_CALL_INFO

Message ID: 44038

Message Description: LOGID_EVENT_VOIP_SCCP_CALL_INFO

Message Meaning: Voip sccp call info

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	15
date		string	10
devid		string	16
dstip		ip	39
dst_int		string	16
dst_port		uint16	5
duration		uint32	10
epoch		uint32	10
eventtime		uint64	20
event_id		uint32	10
kind		string	10
level		string	11
locip		ip	39
locport		uint16	5
logid		string	10

Log Field Name	Description	Data Type	Length
phone		string	64
policy_id		uint32	10
profile		string	64
proto		uint8	3
remip		ip	39
remport		uint16	5
session_id		uint32	10
srcip		ip	39
src_int		string	16
src_port		uint16	5
status		string	23
subtype		string	20
time		string	8
type		string	16
vd		string	32
voip_proto		string	4

WAF

30248 - LOGID_WAF_SIGNATURE_BLOCK

Message ID: 30248

Message Description: LOGID_WAF_SIGNATURE_BLOCK

Message Meaning: Web application firewall blocked application by signature

Type: WAF

Category: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30249 - LOGID_WAF_SIGNATURE_PASS

Message ID: 30249

Message Description: LOGID_WAF_SIGNATURE_PASS

Message Meaning: Web application firewall passed application by signature

Type: WAF

Category: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30250 - LOGID_WAF_SIGNATURE_ERASE

Message ID: 30250

Message Description: LOGID_WAF_SIGNATURE_ERASE

Message Meaning: Web application firewall erased application by signature

Type: WAF**Category:** WAF-SIGNATURE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30251 - LOGID_WAF_CUSTOM_SIGNATURE_BLOCK

Message ID: 30251

Message Description: LOGID_WAF_CUSTOM_SIGNATURE_BLOCK

Message Meaning: Web application firewall blocked application by custom signature

Type: WAF

Category: WAF-CUSTOM-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30252 - LOGID_WAF_CUSTOM_SIGNATURE_PASS

Message ID: 30252

Message Description: LOGID_WAF_CUSTOM_SIGNATURE_PASS

Message Meaning: Web application firewall allowed application by custom signature

Type: WAF

Category: WAF-CUSTOM-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30253 - LOGID_WAF_METHOD_BLOCK

Message ID: 30253

Message Description: LOGID_WAF_METHOD_BLOCK

Message Meaning: Web application firewall blocked application by HTTP method

Type: WAF

Category: WAF-HTTP-METHOD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
date	Date	string	10
direction	Direction	string	

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Http Method	string	
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512

Log Field Name	Description	Data Type	Length
user	User Name	string	256
vd	Virtual Domain Name	string	32

30255 - LOGID_WAF_ADDRESS_LIST_BLOCK

Message ID: 30255

Message Description: LOGID_WAF_ADDRESS_LIST_BLOCK

Message Meaning: Web application firewall blocked application by address list

Type: WAF

Category: WAF-ADDRESS-LIST

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30257 - LOGID_WAF_CONSTRAINTS_BLOCK

Message ID: 30257

Message Description: LOGID_WAF_CONSTRAINTS_BLOCK

Message Meaning: Web application firewall blocked application by HTTP constraints

Type: WAF

Category: WAF-HTTP-CONSTRAINT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
constraint	WAF http protocol restrictions	string	
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30258 - LOGID_WAF_CONSTRAINTS_PASS

Message ID: 30258

Message Description: LOGID_WAF_CONSTRAINTS_PASS

Message Meaning: Web application firewall allowed application by HTTP constraints

Type: WAF

Category: WAF-HTTP-CONSTRAINT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
constraint	WAF http protocol restrictions	string	
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30259 - LOGID_WAF_URL_ACCESS_PERMIT

Message ID: 30259

Message Description: LOGID_WAF_URL_ACCESS_PERMIT

Message Meaning: Web application firewall allowed application by URL access permit

Type: WAF

Category: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30260 - LOGID_WAF_URL_ACCESS_BYPASS

Message ID: 30260

Message Description: LOGID_WAF_URL_ACCESS_BYPASS

Message Meaning: Web application firewall allowed application by URL access bypass

Type: WAF

Category: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30261 - LOGID_WAF_URL_ACCESS_BLOCK

Message ID: 30261

Message Description: LOGID_WAF_URL_ACCESS_BLOCK

Message Meaning: Web application firewall blocked application by URL access

Type: WAF

Category: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
date	Date	string	10
direction	Direction	string	
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

Web

12288 - LOG_ID_WEB_CONTENT_BANWORD

Message ID: 12288

Message Description: LOG_ID_WEB_CONTENT_BANWORD

Message Meaning: Web content banned word found

Type: Web

Category: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12289 - LOG_ID_WEB_CONTENT_MMS_BANWORD

Message ID: 12289

Message Description: LOG_ID_WEB_CONTENT_MMS_BANWORD

Message Meaning: Web content MMS banned word found

Type: Web

Category: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12290 - LOG_ID_WEB_CONTENT_EXEMPTWORD

Message ID: 12290

Message Description: LOG_ID_WEB_CONTENT_EXEMPTWORD

Message Meaning: Web content exempt word found

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256

Log Field Name	Description	Data Type	Length
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12291 - LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD

Message ID: 12291

Message Description: LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD

Message Meaning: Web content MMS exempt word found

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12292 - LOG_ID_WEB_CONTENT_KEYWORD

Message ID: 12292

Message Description: LOG_ID_WEB_CONTENT_KEYWORD

Message Meaning: Message contained a key word in the profile list

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12293 - LOG_ID_WEB_CONTENT_SEARCH

Message ID: 12293

Message Description: LOG_ID_WEB_CONTENT_SEARCH

Message Meaning: Search phrase detected

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12305 - LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF

Message ID: 12305

Message Description: LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF

Message Meaning: Web content MMS banned word

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
banword	Banned word	string	128
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12544 - LOG_ID_URL_FILTER_BLOCK

Message ID: 12544

Message Description: LOG_ID_URL_FILTER_BLOCK

Message Meaning: URL address was blocked because it was found in the URL filter list

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12545 - LOG_ID_URL_FILTER_EXEMPT

Message ID: 12545

Message Description: LOG_ID_URL_FILTER_EXEMPT

Message Meaning: URL address was exempted because it was found in the URL filter list

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12546 - LOG_ID_URL_FILTER_ALLOW

Message ID: 12546

Message Description: LOG_ID_URL_FILTER_ALLOW

Message Meaning: URL address was allowed because it was found in the URL filter list

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12547 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK

Message ID: 12547

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK

Message Meaning: The request contained an invalid domain name

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK

Message ID: 12548

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK

Message Meaning: HTTP certificate request contained an invalid domain name

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS

Message ID: 12549

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS

Message Meaning: HTTP request contained an invalid name so the session has been filtered by IP only

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS

Message ID: 12550

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS

Message Meaning: HTTPS request contained an invalid name so the session has been filtered by IP only

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK

Message ID: 12551

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK

Message Meaning: Insufficient resources

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS

Message ID: 12552

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS

Message Meaning: Getting the host name failed

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12553 - LOG_ID_URL_FILTER_INVALID_CERT

Message ID: 12553

Message Description: LOG_ID_URL_FILTER_INVALID_CERT

Message Meaning: Server certificate validation failed

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12554 - LOG_ID_URL_FILTER_INVALID_SESSION

Message ID: 12554

Message Description: LOG_ID_URL_FILTER_INVALID_SESSION

Message Meaning: SSL session blocked because its identification number was unknown

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK

Message ID: 12555

Message Description: LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK

Message Meaning: SSL session blocked

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS

Message ID: 12556

Message Description: LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS

Message Meaning: SSL session ignored

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rcvdbyte	Received Bytes	uint64	20
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE

Message ID: 12557

Message Description: LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE

Message Meaning: The FortiGuard Analysis and Management Service is not active. You must enable this service

Type: Web

Category: URLFILTER

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
vd	Virtual domain name	string	32

12558 - LOG_ID_URL_FILTER_RATING_ERR

Message ID: 12558

Message Description: LOG_ID_URL_FILTER_RATING_ERR

Message Meaning: Rating error occurred

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
referralurl		string	512
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
url	The URL address	string	512
urltype	URL filter type	string	8
user	User name	string	256
vd	Virtual domain name	string	32

12559 - LOG_ID_URL_FILTER_PASS

Message ID: 12559

Message Description: LOG_ID_URL_FILTER_PASS

Message Meaning: URL passed because it was in the URL filter list

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
user	User name	string	256
vd	Virtual domain name	string	32

12560 - LOG_ID_URL_WISP_BLOCK

Message ID: 12560

Message Description: LOG_ID_URL_WISP_BLOCK

Message Meaning: URL blocked by Websense service

Type: Web

Category: URLFILTER**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12561 - LOG_ID_URL_WISP_REDIR

Message ID: 12561

Message Description: LOG_ID_URL_WISP_REDIR

Message Meaning: URL blocked with redirect message by Websense service

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12562 - LOG_ID_URL_WISP_ALLOW

Message ID: 12562

Message Description: LOG_ID_URL_WISP_ALLOW

Message Meaning: URL allowed by Websense service

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512

Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12800 - LOG_ID_WEB_FTGD_ERR

Message ID: 12800

Message Description: LOG_ID_WEB_FTGD_ERR

Message Meaning: Rating error occurred (error)

Type: Web

Category: FTGD_ERR

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12801 - LOG_ID_WEB_FTGD_WARNING

Message ID: 12801

Message Description: LOG_ID_WEB_FTGD_WARNING

Message Meaning: Rating error occurred (warning)

Type: Web

Category: FTGD_ERR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

12802 - LOG_ID_WEB_FTGD_QUOTA

Message ID: 12802

Message Description: LOG_ID_WEB_FTGD_QUOTA

Message Meaning: Daily FortiGuard quota status

Type: Web

Category: FTGD_QUOTA

Severity: Information

Log Field Name	Description	Data Type	Length
catdesc	Web category description	string	64
date	Date	string	10
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
level	Log Level	string	11
logid	Log ID	string	10
profile	Web Filter profile name	string	64
quotaexceeded	Quota has been exceeded	string	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

13056 - LOG_ID_WEB_FTGD_CAT_BLK

Message ID: 13056

Message Description: LOG_ID_WEB_FTGD_CAT_BLK

Message Meaning: URL belongs to an blocked category within the firewall policy

Type: Web

Category: FTGD_BLK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64

Log Field Name	Description	Data Type	Length
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13057 - LOG_ID_WEB_FTGD_CAT_WARN

Message ID: 13057

Message Description: LOG_ID_WEB_FTGD_CAT_WARN

Message Meaning: URL belongs to a category with warnings enabled

Type: Web

Category: FTGD_BLK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13312 - LOG_ID_WEB_FTGD_CAT_ALLOW

Message ID: 13312

Message Description: LOG_ID_WEB_FTGD_CAT_ALLOW

Message Meaning: URL belongs to an allowed category within the firewall policy

Type: Web

Category: FTGD_ALLOW

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13313 - LOG_ID_WEB_FTGD_RULE_ALLOW

Message ID: 13313

Message Description: LOG_ID_WEB_FTGD_RULE_ALLOW

Message Meaning: URL belongs to an override rule

Type: Web

Category: FTGD_ALLOW

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
mode	Rating override mode	string	32
msg	Log message	string	512
ovrdid	URL rating override ID	uint32	10
ovrdtbl	Rating override table	string	128
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
ruledata	Rule data	string	512
ruletype	Rule type	string	9

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13314 - LOG_ID_WEB_FTGD_OFF_SITE_ALLOW

Message ID: 13314

Message Description: LOG_ID_WEB_FTGD_OFF_SITE_ALLOW

Message Meaning: URL belongs to an override rule

Type: Web

Category: FTGD_ALLOW

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
mode	Rating override mode	string	32
msg	Log message	string	512
ovrdid	URL rating override ID	uint32	10
ovrdtbl	Rating override table	string	128
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
ruledata	Rule data	string	512
ruletype	Rule type	string	9
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING

Message ID: 13315

Message Description: LOG_ID_WEB_FTGD_QUOTA_COUNTING

Message Meaning: FortiGuard web filter category quota counting log message

Type: Web

Category: FTGD_QUOTA_COUNTING

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED

Message ID: 13316

Message Description: LOG_ID_WEB_FTGD_QUOTA_EXPIRED

Message Meaning: FortiGuard web filter category quota expired log message

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13317 - LOG_ID_WEB_URL

Message ID: 13317

Message Description: LOG_ID_WEB_URL

Message Meaning: URL has been visited

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX

Message ID: 13568

Message Description: LOG_ID_WEB_SCRIPTFILTER_ACTIVEX

Message Meaning: ActiveX script removed

Type: Web

Category: ACTIVEXFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE

Message ID: 13573

Message Description: LOG_ID_WEB_SCRIPTFILTER_COOKIE

Message Meaning: Cookie removed

Type: Web**Category:** COOKIEFILTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET

Message ID: 13584

Message Description: LOG_ID_WEB_SCRIPTFILTER_APPLET

Message Meaning: Java applet removed

Type: Web

Category: APPLETFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER

Message ID: 13600

Message Description: LOG_ID_WEB_SCRIPTFILTER_OTHER

Message Meaning: Script entity removed

Type: Web

Category: SCRIPTFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13601 - LOG_ID_WEB_WF_COOKIE

Message ID: 13601

Message Description: LOG_ID_WEB_WF_COOKIE

Message Meaning: Cookie removed entirely

Type: Web

Category: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13602 - LOG_ID_WEB_WF_REFERER

Message ID: 13602

Message Description: LOG_ID_WEB_WF_REFERER

Message Meaning: Referrer removed from request

Type: Web

Category: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32

13603 - LOG_ID_WEB_WF_COMMAND_BLOCK

Message ID: 13603

Message Description: LOG_ID_WEB_WF_COMMAND_BLOCK

Message Meaning: Command blocked

Type: Web

Category: WEBFILTER_COMMAND_BLOCK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
reqtype	Request type	string	8
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32

13616 - LOG_ID_CONTENT_TYPE_BLOCK

Message ID: 13616

Message Description: LOG_ID_CONTENT_TYPE_BLOCK

Message Meaning: Blocked by HTTP header content type

Type: Web


Category: CONTENT**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
contenttype	Content Type from HTTP header	string	64
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
type	Log type	string	16
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32



FORTINET®



Copyright© 2018 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.